

The **amsrefs** package

Michael Downes and David M. Jones
American Mathematical Society

Version 2.14, 2013/03/07

Contents

1	Introduction	3
2	Package options	3
3	More about the <code>\bib</code> command	3
3.1	Field names for the <code>\bib</code> command	3
3.2	Bibliography entry types	4
4	Customizing the bibliography style	5
5	Miscellaneous commands provided by the amsrefs package	6
6	Implementation	9
6.1	Overview	9
6.1.1	Normal L ^A T _E X processing of cites	9
6.2	How cites are processed by amsrefs	10
6.3	Data structures	11
6.4	Preliminaries	12
6.5	Utilities	13
6.6	Declaring package options	16
6.6.1	The <code>? </code> option	18
6.7	Loading auxiliary packages	18
6.7.1	The <code>lite</code> option	18
6.8	Key-value setup	18
6.8.1	Standard field names (the <code>bib</code> group)	19
6.8.2	Auxiliary properties (the <code>prop</code> group)	20
6.9	Bibliography type specifications	20
6.10	The standard bibliography types	23
6.11	The <code>biblist</code> environment	27
6.12	Processing bibliography entries	30
6.12.1	<code>\@bibdef</code> Implementations	32
6.12.2	<code>\bib@exec</code> Implementations	35
6.12.3	Resolving cross-references	37
6.12.4	Bib field preprocessing	40
6.12.5	Date setup	42
6.12.6	Language setup	43
6.12.7	Citation label setup	44

6.12.8	Printing the bibliography	47
6.13	Name, journal and publisher abbreviations	49
6.14	Processing <code>.ltb</code> files	49
6.15	Citation processing	53
6.15.1	The <code>\citesel</code> structure	53
6.15.2	The basic <code>\cite</code> command	53
6.15.3	Fancier <code>\cite</code> commands	59
6.15.4	The <code>\nocite</code> command	60
6.15.5	Citation sorting	61
6.15.6	Range compression	62
6.15.7	Munging the <code>.aux</code> file	65
6.15.8	Back references	67
6.15.9	<code>hyperref</code> , <code>showkeys</code> and <code>shaderef</code> support	68
6.16	Lexical structure of names	69
6.16.1	Text accents	69
6.16.2	Text symbols	70
6.16.3	<code>\edef</code> -like macros for names	72
6.17	Name parsing	74
6.18	Extracting initials	78
6.18.1	The algorithm	79
6.18.2	The implementation	80
6.19	Generating alphabetic labels	86
6.19.1	The algorithm	86
6.19.2	The implementation	87
6.20	Generating short alphabetic labels	91
6.21	Formatting series	92
6.22	Formatting names and series of names	96
6.23	The <code>partial</code> field	102
6.24	Special formatting for other fields	102
6.25	<code>BIBTeX</code> support	108
6.26	Implementing package options	108
6.26.1	The <code>alphabetic</code> option	108
6.26.2	The <code>shortalphabetic</code> option	108
6.26.3	The <code>backrefs</code> option	108
6.26.4	The <code>citation-order</code> option	109
6.26.5	The <code>initials</code> option	109
6.26.6	The <code>logical-quotes</code> option	110
6.26.7	The <code>non-compressed-cites</code> option	110
6.26.8	The <code>non-sorted-cites</code> option	110
6.26.9	The <code>short-journals</code> option	110
6.26.10	The <code>short-publishers</code> option	110
6.26.11	The <code>short-months</code> option	110
6.26.12	The <code>y2k</code> option	111
6.26.13	The <code>bibtex-style</code> option	111
6.26.14	The <code>msc-links</code> option	111
6.26.15	The <code>author-year</code> option	112

6.27 The <code>amsbst</code> package	119
--	-----

1 Introduction

The `amsrefs` package is a `LATEX` package for bibliographies that provides an archival data format similar to the format of Bib`TEX` database files, but adapted to make direct processing by `LATEX` easier. The package can be used either in conjunction with Bib`TEX` or as a replacement for Bib`TEX`.

This document is written for anyone who wants to implement a new bibliography style for `amsrefs` or who is just curious about how the package is implemented. The reader should be familiar with the contents of the “User’s Guide to the `amsrefs` Package” [1] (`amsrdoc.tex`).

For the publisher or implementor, the chief advantages of the `amsrefs` package are as follows:

Preservation of structure The internal structural information of the bibliography entries is not lost when they are imported from the database file into the `LATEX` document. This takes on its greatest significance when archiving documents in `LATEX` form or transmitting them to another user (such as a publisher).

Deferred formatting This means that the style of the bibliography can be readily changed without reimporting everything from the original database(s).

Setup requires only `LATEX` knowledge All bibliography setup can be done in `LATEX`; learning another programming language (such as the one used in Bib`TEX` `bst` files) is unnecessary.

2 Package options

In addition to the options documented in the user’s guide, there are a few additional options that were omitted either because they are obsolete or deprecated options included only for backwards compatibility or because they are still considered experimental and not yet ready for widespread use.

? Informational option. This causes `amsrefs` to display a pointer to the User’s Guide on the terminal and in the log file. (In previous versions, it displayed much more material, including a summary of package options.)

traditional-quotes, logical-quotes With the *traditional quotes* option (default), quotation marks produced by `\bibquotes` (§5) fall outside of other punctuation, “like this,” whereas with the *logical quotes* option the order is reversed, “like this”.

3 More about the `\bib` command

3.1 Field names for the `\bib` command

In addition to the fields discussed in the user’s guide, the following fields are used internally:

fulljournal Used internally by `\DefineJournal`.

name Used internally by the `name` bibliography type and `\DefineName`.

transition A dummy field used inside `\BibSpecs` when we want to force an action unconditionally.

The following fields are included for backwards compatibility:

institution, school These are provided as aliases for `organization` for compatibility with `BIBTEX`.

place A synonym for `address`. In earlier versions of `amsrefs`, `place` was preferred and `address` was considered as an alias for `place`. However, this seemed like a gratuitous incompatibility with `BIBTEX` to me, so I have reinstated `address` as the primary field and `place` is now an undocumented alias.

The following fields are reserved for future use:

doi Digital Object Identifier

setup This is a special field that can be used to give arbitrary commands to be executed at the beginning of the current `\bib` entry, after all the fields have been read. The idea is that one can alter the formatting of an individual entry through this field, to handle special cases.

This is fully implemented, but I've been unable to think of any good examples of its use; so, I've decided to suppress it until such an example comes to light.

url Universal Resource Locator.

3.2 Bibliography entry types

The following additional entry types (or, really, pseudo-entry types) are used internally by `amsrefs`:

`collection.article`

`proceedings.article`

`partial`

`conference`

`innerbook`

`name`

`nameLE`

`nameBE`

`nameinverted`

`publisher`

The following are currently undocumented aliases for various of the standard types:

`miscellaneous`

`periodical`

4 Customizing the bibliography style

If you use the `amsrefs` package as is, the bibliography style you get is the kind of style customarily seen in AMS publications. The recommended way to get a different bibliography style is to write a L^AT_EX package which loads the `amsrefs` package with `\RequirePackage` and then makes the desired changes by using suitable `\BibSpec` commands as explained below. Thus, the general form of the custom package will be

```
\ProvidesPackage{xyzbib}[2002/11/06 v1.28]

\RequirePackage{amsrefs}\relax

\BibSpec{article}{

}

\BibSpec{book}{

}
```

The interior formatting within entries is specified by `\BibSpec` commands, one for each entry type. To illustrate, let's look at an example style specification for entries of type `article`:

```
\BibSpec{article}{%
  +{}{\PrintAuthors}  {author}
  +{},{}{ \textit}     {title}
  +{},{}{ }          {journal}
  +{}{\textbf}        {volume}
  +{}{\parenthesize} {date}
  +{},{}{ }          {pages}
  +{},{}{ }          {note}
  +{.}{ }            {transition}
  +{}{ }            {review}
}
```

It should be pretty obvious that each line specifies the formatting for a particular field. After reading the data for a particular `\bib` command, L^AT_EX steps through the style specification and for each field listed, prints the field with the given formatting *if and only if the field has a nonempty value*. The `+` character at the beginning of each field specification must be followed by three arguments: the punctuation to be added if the field is nonempty; space and/or other material to be added after the punctuation; and the field name. It is permissible for the second part to end with a command that takes an argument, such as `\textbf`, in which case it will receive the field's value as its argument. By defining a suitable command and using it here you can place material after the field contents as well as before; `\parenthesize` is an example of this.

The reason that the punctuation and the following space are specified separately is that between them there is a crucial boundary for line breaks. If you put a `\linebreak` command at the end of a field value, the break point will

actually be carried onward to a suitable point after the next bit of punctuation (whose actual value may vary depending on which of the following fields is the first to turn up with a nonempty value).

The meaning of the `\parenthesize` command, supplied by `amsrefs`, should be obvious. The meaning of the `\PrintAuthors` command is a different story. But I don't think it is all that hard to understand. If we have two or more author names which were given separately, and we need to combine them into a conventional name list using commas and the word "and", then it would be nice if we had a command which could take a list of names and Do The Right Thing. And that is just what `\PrintAuthors` is.

The `rkeyval` package allows keys to be defined as additive: if the key occurs more than once, each successive value will be concatenated to the previous value, along with a prefix. The setup done by `amsrefs` for the `author` field is

```
\DefineAdditiveKey{bib}{author}{\name}
```

This means that if two names are given, as in

```
author={Bertram, A.},  
author={Wentworth, R.},
```

then the final value of the `author` field seen when L^AT_EX processes the style specification will be

```
\name{Bertram, A.}\name{Wentworth, R.}
```

The `transition` field in our `\BibSpec` example is a dummy field to be used when punctuation or other material must be added at a certain point in the bibliography without regard to the emptiness or non-emptiness of the fields after it. The `transition` field always tests as non-empty but has no printed content. So when you use it you always get the indicated punctuation and space at the indicated point in the list of fields. If it were the last thing in this `\BibSpec` example, it could serve just to put in the final period that is always wanted. But in AMS bibliographies, if a *Mathematical Reviews* reference is given, it is conventionally printed *after* the final period. Using the `transition` field as shown here ensures that the final period will be always printed, even when the `review` field is empty.

5 Miscellaneous commands provided by the `amsrefs` package

Most of the following commands are helper commands for use in `\BibSpec` statements. The others are intended for use in bibliography data.

`\parenthesize` This command adds parentheses around its argument. It is useful in `\BibSpec` statements because there is no special provision for adding material after the field value.

`\bibquotes` This command is much like `\parenthesize` but it adds quotes around its argument and it has one other important difference: there are special arrangements to print the closing quote *after* a following comma or similar punctuation (unless the `amsrefs` package is invoked with the

`logical-quotes` option, in which case `\bibquotes` puts the closing quote immediately after the quoted material).

`\voltext` This is used to format volume numbers. By default, it precedes the volume number by “vol.”

`\issuetext` This is used to format issue numbers. By default, it precedes the volume number by “no.”

`\editiontext` This command produces “ed.” following an edition number. See `\PrintEdition` for more information.

`\DashPages` This command is similar in spirit to `\voltext` but more complicated in its implementation. It takes one argument which is expected to contain one or more page numbers or a range of page numbers. The argument is printed with a prefix of “p.” if it seems to be a single page number, otherwise with a prefix of “pp.”.

`\tsub`, `\tsub`, `\tprime` These are for text subscripts and superscripts, with `\tprime` producing a superscript prime symbol. Unlike the standard `\textsuperscript` and `\textsubscript` functions provided by L^AT_EX, these do not use math mode at all.¹

`\nopunct` This command causes following punctuation to be omitted if it is added with the internal function `\@addpunct`.

`\PrintPrimary` This is a relatively complicated function that determines the “primary” contributors for an entry and formats them, or replaces them by `\sameauthors` if appropriate. It should be used when an entry type might have editors or translators instead of authors. It prefers authors over editors and editors over translators and generates a warning if there are no primary contributors.

`\PrintAuthors` This is used to format the list of authors as the primary contributors for an entry type.

`\PrintEditorsA` This is similar to `\PrintAuthors` but adds (ed.) or (eds.) following the editors.

`\PrintEditorsB` This is similar to `\PrintEditorsA` but puts parentheses around the entire list of editors. It’s used by, for example, the `article` type to print the editors of a `proceedings` or `collection`.

`\PrintEditorsC` Similar to `\PrintEditorsA` but precedes the editors by Edited by. It’s used when the editors should be treated as subsidiary contributors, rather than the primary contributor.

`\PrintTranslatorsA` This is similar to `\PrintEditorsA` but adds (trans.) following the translators.

`\PrintTranslatorsB` This is similar to `\PrintEditorsB`. It’s not currently used, but is provided for symmetry.

`\PrintTranslatorsC` Similar to `\PrintEditorsC` but precedes the translators by Translated by.

¹There is one drawback: If you don’t want to get the prime symbol for `\tprime` from the `cmsy` font, you will need to redefine `\tprime` in some suitable way.

`\sameauthors` This is a function of one argument. If you use the default set of `\BibSpecs` from the `amsrefs`, `\sameauthors` is applied to the author name for a given `\bib` command if it matches exactly the author name of the preceding `\bib` command. Change the definition of `\sameauthors` if you don't want to get a `bysame` dash.

`\bysame` This is a horizontal rule of length 3 em. The default definition of `\sameauthors` prints `\bysame` instead of the author names.

`\Plural`, `\SingularPlural` These are helper functions that allow you to conditionally print singular or plural forms such as `(ed.)` or `(eds.)` depending on the number of names in the current name list. The definition of `\PrintEditorsA` reads, in part,

```
... (ed\Plural{s}.) ...
```

`\PrintReviews` This is similar to `\AuthorList` but is used for printing (possibly multiple) MR numbers given in the `review` field.

`\BibField` This is for more complicated programming tasks such as may be necessary for some `\BibSpecs`. It takes one argument, a field name, and yields the contents of that field for the current `\bib` entry.

`\IfEmptyBibField` If one writes

```
\IfEmptyBibField{isbn}{A}{B}
```

then the commands in A will be executed if the `isbn` field is empty, otherwise the commands in B.

`\PrintEdition` If a bibliography entry has

```
edition={2}
```

and the `\BibSpec` used `\PrintEdition` to handle this field, then the edition information will be printed as “2nd ed.”—that is, the number is converted to cardinal form and “ed.” is added (taken from `\editiontext`).

`\CardinalNumeric` This provides the conversion to cardinal number form used by `\PrintEdition`.

`\PrintDate`, `\PrintYear` These functions convert a date in canonical form (ISO 8601) to the form required by the current bibliography style. You can get your preferred date form by redefining these functions or by changing your `\BibSpec` statements to use another function of your own devising. The original definition of `\PrintDate` adds parentheses (as for the year of a journal article in normal AMS style), whereas the `\PrintYear` function simply prints the year without any additional material (as for a book's year of publication in normal AMS style).

`\mdash`, `\ndash` These are short forms for `\textemdash` and `\textendash`, recommended instead of the more usual `---` and `--` notation. From the `textcmds` package.

et cetera ... [mjd,2002-01-03] See the `.dtx` files for further possibilities that I have not managed to get properly documented yet!

6 Implementation

6.1 Overview

It will be a while yet before we get to any actual code. First we need to understand what the code needs to accomplish in order to provide the user interface described above in a way that is as compatible as possible with existing L^AT_EX mechanisms.

6.1.1 Normal L^AT_EX processing of cites

First L^AT_EX pass Various commands are written to the `.aux` file that are mostly used by BibT_EX.

1. A `\cite{moo}` command writes one line to the `.aux` file: `\citation{moo}`. This indicates to BibT_EX that it should include ‘moo’ in the list of cited items to be searched for. The `\cite` command also checks to see if `\b@moo` contains the corresponding citation label, but since this is the first pass, the label won’t be known yet, so L^AT_EX emits an ‘Undefined citation’ warning and prints a placeholder (i.e., `???`) instead of the citation label.
2. A `\bibliographystyle{har}` command writes one line to the `.aux` file: `\bibstyle{har}`. This indicates to BibT_EX that it should use `har.bst` to determine the style for sorting and formatting the bibliography items.
3. A `\bibliography{hij,klm,...}` command writes one line to the `.aux` file: `\bibdata{hij,klm,...}`. This indicates to BibT_EX that it should look in `hij.bib`, `klm.bib`, ... for bibliographic data. The `\bibliography` also tries to input the `.bb1` file, but on the first pass it won’t exist yet.

On the first pass all `\cite`’s normally are reported as undefined because the `.bb1` file has not yet been created.

BibT_EX pass For a document named `xyz.tex`, the command `bibtex xyz` is used to invoke BibT_EX. It looks in `xyz.aux` to find the citation information written there by L^AT_EX. For each `\citation` line, BibT_EX searches for a corresponding entry in the specified `.bib` files and formats it. The entire list is then sorted in whatever way dictated by the bibliography style, and written out to the file `xyz.bb1`. This normally produces entries that look something like:

```
\bibitem{BGL} P. Busch, M. Grabowski and P. J. Lahti:  
{\it Operational Quantum Physics.}  
Springer Verlag, New York (1995).
```

Second L^AT_EX pass Now the `.bb1` file exists and contains some `\bibitem` commands. At `\begin{document}`, L^AT_EX reads the `.aux` file, hoping to find some `\bibcite` commands, but it will not find them until the next time around. `\citation`, `\bibstyle`, and `\bibdata` commands in the `.aux` file are simply ignored by L^AT_EX. Then L^AT_EX proceeds to typeset the body of the document.

1. Instances of `\cite` still print question marks.
2. The `\bibliography` command causes L^AT_EX to input `xyz.bb1` and typeset its contents.

3. A `\bibitem{moo}` command writes one line to the `.aux` file: `\bibcite{moo}{9}`, where 9 is the current item number.
4. A `\bibitem[Moody]{moo}` command writes one line to the `.aux` file: `\bibcite{moo}{Moody}`, using the supplied label instead of a number.

Third L^AT_EX pass Now the `.aux` file contains some `\bibcite` commands. Once again, L^AT_EX reads the `.aux` file when it reaches `\begin{document}`.

1. A `\bibcite{moo}{Moody}` causes L^AT_EX to define `\b@moo` with ‘Moody’ as the replacement text.
2. If two `\bibcite` commands have the same citation key, L^AT_EX gives a warning message. This happens at `\begin{document}`, during the reading of the `.aux` file.
3. Instances of `\cite` in the body of the document will print the appropriate labels obtained from the `.aux` file.
4. If there are any `\cite` commands for which the `.aux` file did not have a `\bibcite` command, L^AT_EX will give an ‘Undefined citation’ warning. This often happens if the `.aux` file is incomplete due to a T_EX error on the preceding pass.

6.2 How cites are processed by `amsrefs`

In order to support its additional features (e.g., author-year citations and the `backrefs` option), the `amsrefs` package stores additional information for each cite in the macro `\b@whatever`. Instead of simply using the defined or undefined status of this macro to trigger the standard warnings, we add some boolean flags to allow us to discriminate more finely what the current situation is.

- Each time an item is cited in the body of the document, a `backref` entry is added to the info of that item. The `backref` info is the current page and section location. Section location is a bit hard to get right without better support from the document class. So we provide a hook to allow it to work better when the support is there.
- When a cite occurs, if the info is undefined then a warning is issued and the info structure is created. A `\citation` command and a `\citedest` command (providing backref info) are written to the `.aux` file. Because the backref info includes page number, it has to be a non-immediate write. An undefined info structure would normally happen only on a first pass when no `.aux` file exists, or when a new cite is added. I.e., when the corresponding `\citation` command is not yet present in the `.aux` file.
- When a citation command occurs in the `.aux` file, it initializes the info structure if necessary, setting the “bib-info-present” flag to 0.
- When a `\citedest` command occurs in the `.aux` file, it initializes the info structure if necessary—but this shouldn’t happen: if the corresponding `\citation` command did not already get processed, then something is wrong. So normally, the `\citedest` command merely needs to add its backref info to the existing info structure.

- When a `\bibcite` command occurs in the `.aux` file, it will normally find that `\b@whatever` is already defined, if the bibliography occurs after all the `\cite` commands. What it must do is fill in the appropriate blank slots in the info structure set up by a previous `\citation` command.
- The `.aux` file is actually processed two times, once at the beginning of the document and once at the end. In the latter case, `\bibcite` should give a warning if the backref-list is empty, since that means there were no `\cite` commands for the given key.
- When processing the bibliography: The `\bib` command needs to check if it is using a key that is already used by another `\bib` command.

We therefore have

```
\b@xyz -> \citesel 00{label}{year}{backref-list}
```

where the first 0 is replaced by 1 if there has already been another citation for the same key earlier in the document (some citation styles use abbreviated forms for all instances after the first), and the second 0 is replaced by 1 if the same key was already used by an earlier `\bib` command.

Because the backref-list often includes page number information, it cannot be built on the fly as we go along; instead we have to write the information to the `.aux` file and read it in at the beginning of the next run.

If there was no `\bibcite` in the `.aux` file for a given key, then the info is

```
\b@xyz -> \citesel 00{}{}{backref-list}
```

If there was neither `\citation` nor `\bibcite` in the `.aux` file for a given key, then the `\cite` command should find that `\b@xyz` is undefined.

If the author-year option is in effect, the “label” contains the author last names instead of a label:

```
\b@xyz -> \citesel 00{\name{Smith}\name{Jones}}{...}{...}
```

Full name information is included in the data because some citation styles give full names at the first citation and abbreviated forms for subsequent instances.

6.3 Data structures

The result of scanning the key/value pairs of a `\bib` command is an assignment statement for `\rsk@toks`. (Cf. the `rkeyval` package.) For example, consider the entry

```
\bib{miller83}{article}{%
  author={Miller, G.},
  title={Eine Bemerkung zur Darstellung von Polynomen \"uber
    Verb\"{a}nden}*{language={german}},
  journal={J. Math. Sent.},
  volume={10},
  year={1983},
  pages={26\ndash 30},}
```

The scanned result is to assign

```
\global\rsk@toks{%
```

```

\set:bib'author{Miller, G.}{}%
\set:bib'title{Eine Bemerkung zur Darstellung von Polynomen
  \"uber Verb\"{a}nden}{language={german}}%
\set:bib'journal{J. Math. Sent.}{}%
\set:bib'volume{10}{}%
\set:bib'year{1983}{}%
\set:bib'pages{26\ndash 30}{}%
}

```

The code in the last arg of `\RestrictedSetKeys` then invokes `\bib@exec` to do something with the value of `\rsk@toks`.

```
\bib@exec{miller83}{\the\rsk@toks}{\setbib@article}{}}
```

6.4 Preliminaries

1 `(*pkg)`

Standard declaration of package name and date.

2 `\NeedsTeXFormat{LaTeX2e}[1995/12/01]`

3 `\ProvidesPackage{amsrefs}[2013/03/07 v2.14]`

`\amsrefs@warning@nl`

4 `\def\amsrefs@warning@nl{\PackageWarningNoLine{amsrefs}}`

Backward handling for beta and jpa options.

```

5 \@ifpackagewith{amsrefs}{beta}{}%
6   \amsrefs@warning@nl{The beta option is obsolete}%
7 }{}%
8 \@ifpackagewith{amsrefs}{jpa}{}%
9   \amsrefs@warning@nl{The jpa option is obsolete}%
10 }{}%
11 \IfFileExists{url.sty}{}%
12   \RequirePackage{url}\relax
13   \gobble
14 }{}%
15   \firstofone
16 }
17 {
18   \DeclareRobustCommand{\url}[1]{%
19     \def\@tempa{\#1}%
20     \texttt{\@urlsetup $\expandafter\strip@prefix\meaning\@tempa$}%
21   }%
22   \def\@urlsetup{%
23     \check@mathfonts \textfont\@ne\the\font \textfont\z@\the\font
24     \apply\@urlfix{\do+\do=\do:\do-\do.\do,\do;}\%
25     \apply\@urlbreak{\do\&\do/\do?\}\%
26   }%
27   \def\@urlbreak#1{%
28     \mathcode`#1="8000
29     \begingroup \lccode`\~=\#1 \lowercase{\endgroup \edef`~}%
30     {\mathchar\number`#1\penalty\hyphenpenalty}%
31   }%

```

```

32   \def\@urlfix#1{%
33     \mathcode`#=`\#1\relax
34   }%
35 }
36 \@ifundefined{NormalCatcodes}{\RequirePackage{pcatcode}\relax}{}%
37 \PushCatcodes\NormalCatcodes
38 %% WARNING WARNING WARNING: Catcode of apostrophe ' is letter
39 %% throughout this file.
40 \catcode`'=11 % letter

```

6.5 Utilities

Some of these useful functions are also found in AMS document classes.

`\after@deleting@token` Similar in concept to `\afterassignment`, except it deletes the next token in the stream before putting its argument back into the input. Useful for skipping past tokens during parsing.

```

41 \def\after@deleting@token#1{%
42   \afterassignment#1%
43   \let\@let@token= % Don't delete this space!
44 }

```

`\@isempty` Some frequently used tests for empty arguments. Note that an argument consisting entirely of spaces (e.g., `\@isempty{\ }`) counts as empty.

```

45 \long\def\@isempty#1{\@xisempty#1@..\@nil}
46
47 \long\def\@xisempty#1#2#3#4#5\@nil{%
48   \ifx#3#4\@xp\@firstoftwo\else\@xp\@secondoftwo\fi
49 }
50
51 \long\def\@ifnotempty#1{\@isempty{#1}{}}

```

`\macro{text}`

```

52 \def\macro{text}{\expandafter\strip@prefix\meaning}

```

`\vdef` “Verbatim” def.

```

53 \def\vdef#1#2{%
54   \def#1{#2}%
55   \edef#1{\macro{text}{#1}}%
56 }

```

`\auto@protect` Sometimes it’s convenient to render a given control sequence unexpandable for a time. `\auto@protect` provides a way to do that.²

An earlier version of this code read simply `\let#1\relax` but that had the disadvantage of making all `\auto@protected` macros compare equal via `\ifx`. This version allows macros to keep their identities under comparisons.

```

57 \def\auto@protect#1{\def#1{@nx#1}}

```

²There really should be a special name for macros that, like `\auto@protect`, take a control sequence as an argument and redefine that control sequence in order to achieve some special effect. Pending happier inspiration, I’m going to call them “wrapper” macros.

```
\auto@stringify
58 \def\auto@stringify#1{\def#1{\string#1}}
\g@undef Globally undefine a control sequence.
59 \def\g@undef#1{\global\let#1\relax}
\@concat Concatenate onto the end of a token list. Expands everything.
60 \def\@concat#1#2{\edef#1{#1#2}}
\add@toks@ This saves a few tokens of main memory and a lot of typing.
61 \def\add@toks@{\addto@hook\toks@}
\@append Append an element to a \do-delimited list. As long as the element to be appended (#2) is a single token, nothing is expanded. If it contains multiple tokens, all tokens after the first will be expanded.
62 \def\@append#1#2{%
63   \begingroup
64     \def\do{\@nx\do\@nx}%
65     \edef\@tempa{\def\@nx#1{#1\do#2}}%
66   \exp\endgroup
67   \@tempa
68 }
\@apply Apply a macro to each element of a \do-delimited list.
69 \def\@apply#1#2{%
70   \let\do#1%
71   #2%
72 }
\get@numberof This is a generic macro for counting the number of elements in a LATEX-style list. The first argument is a \count register that will receive the final count; the second argument is the control sequence that separates elements of the list, and the third argument is the list itself. So, for example,
\get@numberof\@tempcnta\do\dospecials
would count the number of special characters in \dospecials and store the number in \@tempcnta.
73 \def\get@numberof#1#2#3{%
74   \begingroup
75     \def#2{\advance\@tempcnta\@ne \@gobble}%
76     \@tempcnta\z@
77     #3\relax
78     \edef\@tempb{\#1=\the\@tempcnta\relax}%
79   \exp\endgroup
80   \@tempb
81 }
```

\safe@set This is a quick and dirty way of extracting an integer prefix from a string and assigning it to a counter. If the string does not begin with an integer, the counter receives the value 0. The suffix after the integer prefix is discarded. (But bad things will happen if the string contains the token \nil.)

```
82 \def\safe@set#1#2{%
83   \afterassignment\@nilgobble
84   #1=0#2\relax\@nil
85 }
```

\chomp Vaguely reminiscent of Perl's `chomp` function, which removes a substring from the end of a variable, but ours works with tokens (more-or-less) and takes the substring to be removed as its second argument. Note the use of \empty to anchor the chomped substring to the end of the string. Note also that the second argument will be fully expanded during the chomping.

```
86 \def\@chomp#1#2{%
87   \begingroup
88     \toks@\emptytoks
89     \def\@chomper##1##2\@empty##3\@nil{%
90       \ifx\@let@token\bgroup
91         \toks@{\{\##1}\##2}%
92       \else
93         \toks@{\##1##2}%
94       \fi
95     }%
96     \xp\chomp@ #1\@empty#2\@empty\@nil
97     \edef\@tempa{\def\@nx#1\xp{\the\toks@}}%
98   \xp\endgroup
99   \@tempa
100 }
```

\chomp@ Before passing control to \chomper, we peek ahead at the next token in the stream. That way, if the next token is an open brace, we know we need to surround \chomper's first argument with braces. Unfortunately, this might still remove braces from the second argument, but I think that's ok for our purposes.

```
101 \def\chomp@{%
102   \futurelet\@let@token
103   \@chomper
104 }
```

\amsrefs@warning

```
105 \def\amsrefs@warning{\PackageWarning{amsrefs}}
```

\amsrefs@error

```
106 \def\amsrefs@error{\PackageError{amsrefs}}
```

\MessageBreakNS This suppresses the leading space in \on@line in error and warning messages.

```
107 \def\MessageBreakNS{\MessageBreak\romannumeral`^\^@}
```

\@addpunct The \@addpunct function is defined by AMS document classes and the `amsfonts` package. But if we find it undefined we had better define it.

```
108 \@ifundefined{@addpunct}{%
109     \def\@addpunct#1{%
110         \relax\ifhmode
111             \ifnum\spacefactor>\@m \else#1\fi
112         \fi
113     }
114     \def\frenchspacing{%
115         \sfcode`\!.1006
116         \sfcode`\?1005
117         \sfcode`\!1004
118         \sfcode`\!:1003
119         \sfcode`\;1002
120         \sfcode`\,,1001\relax
121     }
122 }{}}
```

\nopunct Omit any following punctuation that would normally be inserted by \@addpunct.

```
123 \providecommand{\nopunct}{\spacefactor \nopunctsfcode}
```

\nopunctsfcode

```
124 \def\nopunctsfcode{1007 }
```

6.6 Declaring package options

We call the `ifoption` package to facilitate some option tests.

```
125 \RequirePackage{ifoption}[2000/02/15]
```

The `sorted` option is a no-op and is no longer documented. I'm only leaving it here for backwards compatibility.

```
126 \DeclareExclusiveOptions{sorted,citation-order}
```

The `alphabetic` option corresponds to the standard `alpha` biblio style with labels like Knu66 (three letters from name plus two digits of year). Maybe should provide an alias LllYY for this option. Numeric is the default since it is commoner in AMS publications.

```
127 \DeclareExclusiveOptions{alphabetic,shortalphabetic,author-year,numERIC}
```

y2k

```
128 \DeclareBooleanOption{y2k}
```

nobysame

```
129 \DeclareBooleanOption{nobysame}
```

The standard `abrv` bibliography style uses abbreviations for month names and journal names, and first names of people are abbreviated to their initials. Since the second test bibliography that I tested with had unabbreviated month names but abbreviated journal names, perhaps it is a good idea to let these choices be specified separately.

```
130 \DeclareBooleanOption{short-journals}
```

```
131 \DeclareBooleanOption{short-publishers}
```

The `short-journals` and `short-publishers` options only affect journal and publisher names that are defined with `\DefineJournal` and `\DefinePublisher` commands.

```
132 \DeclareBooleanOption{short-months}
```

```
133 \DeclareBooleanOption{initials}
```

Nevertheless, it's to be expected that the preceding four options would typically be used together, so we provide a short-hand for requesting them all.

```
134 \DeclareOption{abbrev}{%
```

```
135     \@pass@options
```

```
136         \@currext
```

```
137         {initials,short-months,short-journals,short-publishers}%

```

```
138         \@currname

```

```
139 }
```

In the bibliography, if a title or something is enclosed in quotes, should the closing quotes go inside the punctuation (logical position) rather than outside (traditional)? These options give you a choice.

```
140 \DeclareExclusiveOptions{traditional-quotes,logical-quotes}
```

A sequence of cites will be sorted and ranges of length three or greater will be compressed if these options so indicate. Note that the `non-sorted-cites` option automatically disables compression. This is probably a feature.

```
141 \DeclareExclusiveOptions{sorted-cites,non-sorted-cites}
```

```
142 \DeclareExclusiveOptions{non-compressed-cites,compressed-cites}
```

In the bibliography, print page numbers showing where each entry was cited.

```
143 \DeclareBooleanOption{backrefs}
```

Option for giving information about the available options:

```
144 \DeclareBooleanOption{?}
```

This option means to forgo loading of the `textcmds` and `mathscinet` packages.

```
145 \DeclareBooleanOption{lite}
```

This option can be used by later releases as a sign that fall-back adaptations need to be done.

```
146 \DeclareBooleanOption{beta}
```

```
147 \DeclareBooleanOption{bibtex-style}
```

```
148 \DeclareBooleanOption{msc-links}
```

```
149 \ExecuteOptions{numeric,traditional-quotes,sorted-cites,compressed-cites}
```

```
150
```

```
151 \ProcessOptions\relax
```

```
152
```

```
153 \ProcessExclusiveOptions
```

```

154 \IfOption{backrefs}{%
155   \IfFileExists{backref.sty}{%
156     \RequirePackage{backref}[1999/05/30]
157   }{%
158     \amsrefs@warning@nl{The backrefs option cannot be used^^J%
159       unless the backref package is also installed.^^J%
160       (backref is part of the hyperref package)}%
161   }%
162 }{}%
163
164 \IfOption{msc-links}{%
165   \IfFileExists{hyperref.sty}{%
166     \RequirePackage{hyperref}[1999/07/08]
167   }{%
168     \amsrefs@warning@nl{The msc-links option cannot be used^^J%
169       unless the hyperref package is installed}%
170   }%
171 }{}%

```

6.6.1 The ? option

```

172 \IfOption{?}{%
173   \typeout{^^J%
174     Documentation for the amsrefs package is found in amsrdoc.dvi^^J%
175     (or .pdf or .tex).
176   }%
177 }{}%
178 }{}%

```

6.7 Loading auxiliary packages

Now, if these other packages make use of the `pcatcode` package like they should, then we don't need to make any fuss here about the special catcode of `'`. Just load the packages.

```
179 \RequirePackage{rkeyval}[2001/12/22]
```

6.7.1 The lite option

In my opinion, this is misguided, since `amsrefs` shouldn't be loading these packages to begin with. But it's too late to change it now.

```

180 \IfOption{lite}{% True? Then don't load the next two packages.
181 }{%
182   False? OK, let's load them:
183   \RequirePackage{textcmds}[2001/12/14]
184   \RequirePackage{mathscinet}[2002/01/01]
185 }

```

6.8 Key-value setup

`\BibField` This provides easy access to individual fields for user-defined formatting functions.

```
185 \newcommand{\BibField}[1]{\csname bib'#1\endcsname}
```

`\IfEmptyBibField` A convenient partial application of `\rvkIfEmpty`.

```
186 \newcommand{\IfEmptyBibField}{\rvkIfEmpty{bib}}
```

6.8.1 Standard field names (the bib group)

And here are the predefined key names. You could always add some more if you needed them. Only worry is about compatibility if you want to share your data with other people.

\fld@elt We want the list macros used above to be unexpandable except when special
 \name processing is done. (It's not clear to me there's any real benefit to using these instead of just using \do{---dmj})

```
187 \let\fld@elt=?
188 \let\name=?
```

First the fields that could be repeated more than once in a single entry. Maybe publisher should be allowed to repeat also, for co-published works. But then need to worry about the address handling.

```
189 \DefineAdditiveKey{bib}{author}{\name}
190 \DefineAdditiveKey{bib}{editor}{\name}
191 \DefineAdditiveKey{bib}{translator}{\name}
192 \DefineAdditiveKey{bib}{contribution}{\fld@elt}
193 \DefineAdditiveKey{bib}{isbn}{\fld@elt}
194 \DefineAdditiveKey{bib}{issn}{\fld@elt}
195 \DefineAdditiveKey{bib}{review}{\fld@elt}
196 \DefineAdditiveKey{bib}{partial}{\fld@elt}

197 \DefineSimpleKey{bib}{accessdate}
198 \DefineSimpleKey{bib}{address}
199 \DefineSimpleKey{bib}{book}
200 \DefineSimpleKey{bib}{booktitle}
201 \DefineSimpleKey{bib}{conference}
202 \% \DefineSimpleKey{bib}{contributor}
203 \DefineSimpleKey{bib}{copula}
204 \DefineSimpleKey{bib}{date}
205 \DefineSimpleKey{bib}{doi}
206 \DefineSimpleKey{bib}{edition}
207 \DefineSimpleKey{bib}{eprint}
208 \DefineSimpleKey{bib}{fulljournal}
209 \DefineSimpleKey{bib}{hyphenation}
210 \DefineSimpleKey{bib}{institution}
211 \DefineSimpleKey{bib}{journal}
212 \DefineSimpleKey{bib}{label}
213 \DefineSimpleKey{bib}{language}
214 \DefineSimpleKey{bib}{name}
215 \DefineSimpleKey{bib}{note}
216 \DefineSimpleKey{bib}{number}
217 \DefineSimpleKey{bib}{organization}
218 \DefineSimpleKey{bib}{pages}
219 \DefineSimpleKey{bib}{part}
220 \DefineSimpleKey{bib}{place}
221 \DefineSimpleKey{bib}{publisher}
222 \DefineSimpleKey{bib}{reprint}
```

```

223 \DefineSimpleKey{bib}{school}
224 \DefineSimpleKey{bib}{series}
225 \DefineSimpleKey{bib}{setup}
226 \DefineSimpleKey{bib}{status}
227 \DefineSimpleKey{bib}{subtitle}
228 \DefineSimpleKey{bib}{title}
229 \DefineSimpleKey{bib}{translation}
230 \DefineSimpleKey{bib}{type}
231 \DefineSimpleKey{bib}{url}
232 \DefineSimpleKey{bib}{volume}
233 \DefineSimpleKey{bib}{xref}
234 \DefineSimpleKey{bib}{year}

```

The `transition` key is used when we want to insert punctuation or other material at a given point in the sequence unconditionally. The key appears to have a non-empty value to `\IfEmptyBibField`, but its value (expansion) is empty.

```
235 \DefineDummyKey{bib}{transition}
```

6.8.2 Auxiliary properties (the prop group)

```

236 \DefineSimpleKey{prop}{inverted}
237 \DefineSimpleKey{prop}{language}

```

6.9 Bibliography type specifications

`\BibSpec` Accumulate specification material in `\toks@`, then define `\setbib@TYPE` from it.

```

238 \newcommand{\BibSpec}[2]{%
239     \toks@\emptytoks
240     \@ifnotempty{#2}{%

```

The `\@ifnextchar` removes an optional + at the beginning of a specification. From then on, each time `\bibs@spec@scan` is invoked, it expects to find four arguments. The four `\@emptys` appended to the specification (#2) below ensure that this is so.

```

241     \@ifnextchar{+}{\@xp\bibs@spec@scan@gobble}{\bibs@spec@scan}%
242     #2\@empty\@empty\@empty\@empty
243 }
244     \@xp\edef\csname setbib@#1\endcsname{\the\toks@}%
245 }

```

`\bibs@spec@scan` The `\bibs@spec@scan` function scans one field specification from the second arg of `\BibSpec`. Each field specification has the form

```
+{punctuation}{prelim material}{field name}
```

Note however that because the initial + is stripped off by `\BibSpec` (see above), the actual order that `\bibs@spec@scan` reads the field specification is

```
#1={punctuation} #2={prelim material} #3={field name} #4=+
```

where the fourth argument is actually expected to be either the + from the following specification, or one of the special `\@empty` tokens inserted by `\BibSpec`.

If it is neither of these special values, it means we have a malformed specification; so, we issue an error and then try to pick up where we left off.

```

246 \def\bibspec@scan#1#2#3#4{%
247   \add@toks@{\bib@append{#1}{#2}}%
248   \edef\@tempa{%
249     \toks@{\the\toks@ \xp\cnx\csname bib'#3\endcsname}%
250   }%
251   \@tempa
252   \ifx\@empty#4%
253     \xp\@gobble % end the recursion
254   \else
255     \ifx +#4\else\bibspec@scan@error\fi
256   \fi
257   \bibspec@scan
258 }

\bibspec@scan@error
259 \def\bibspec@scan@error{\amsrefs@error{Bad BibSpec: Expected '+'}}

```

`\bib@append` The function `\bib@append` prints the value of a field, together with associated punctuation and font changes, unless the value is empty. Arg 1 is punctuation (that may need to be swapped with a preceding line break), arg 2 gives the space to be added after the punctuation, and possibly a function to be applied to the contents of arg 3, which is a macro containing the field value. So if we have `\moo` and `\bib'pages`, from `pages={21\ndash 44}`, then we want to arrange to call

```
\moo{21\ndash 44}
```

We don't want to simply call `\moo\bib'bar` because that makes it rather difficult for `\moo` to look at the contents of `\bib@bar`.

```

260 \def\bib@append#1#2#3{%
261   \ifx\@empty#3%
262   \else

```

Known bug: Need better error message here.

```

263   \ifx\relax#3%
264     \errmessage{#3=\relax}%
265   \else
266     \begingroup
267       \series@index\m@ne
268       \def\current@bibfield{#3}%
269       \@ifempty{#1}{%
270         \temptokena{\ifnum\lastkern=\@ne\ignorespaces\fi #2}%
271       }{%
272         \temptokena{\SwapBreak{#1}#2}%
273       }%
274       \toks@\xp{#3}%
275       \edef\@tempa{\the\temptokena{\the\toks@}}%

```

```

276          \rkvIfAdditive#3{}{%
277              \get@current@properties
278              \select@auxlanguage
279          }%
280          \atempa
281      \endgroup
282  \fi
283 \fi
284 }

\select@auxlanguage
285 \def\select@auxlanguage{%
286     \ifx\prop'language\empty
287     \else
288         \xp\selectlanguage\xp{\prop'language}%
289     \fi
290 }

```

\erase@field There are some fields that can appear in more than one place in a reference, depending on context. For example, if a book has an editor but no author, the editor appears at the beginning of the entry, but if the book has both an editor and an author, the editor appears at the end of the entry. A simple way to handle this is to “erase” the `editor` field after printing it, which is what `\erase@field` is for.

The obvious definition of `\erase@field` is

```
\def\erase@field#1{\global\let#1\empty}
```

but that doesn’t work because the top-level value of `rkeyval` fields isn’t `\empty`; instead, it contains a setter function used by `\RestrictedSetKeys` when processing a key-value list (see `\rkv@DSAK`, `\rsk@set@a` and `\rsk@set@b`).

On the other hand, rewriting the field locally won’t work either, since `\erase@field` will typically be executed inside the group established by `\bib@append`. Instead, we want to rewrite the value right after `\bib@append`’s group ends. One way to do this would be to keep a list of fields to be erased and have `\bib@append` iterate over the list after its `\endgroup`.

However, as long as the call to `\erase@field` is never nested within any deeper groups, it’s simpler just to use `\aftergroup`, which is what we’ll do (“Sufficient unto the day is the evil thereof” and all that).

```

291 \def\erase@field#1{%
292     \aftergroup\let\aftergroup#1\aftergroup\empty
293 }
```

\get@current@properties This retrieves the auxiliary properties for the current field value, as defined by `\current@bibfield` and `\series@index`.

```

294 \def\get@current@properties{%
295     \begingroup
296         \xp\get@nth@property\xp\atempa\current@bibfield\series@index
```

```

297     \edef\@tempa{%
298         \nx\RestrictedSetKeys{}{prop}{%
299             \def\nx\@tempa{\nx\prop@reset \nx\the\nx\rsk@toks}%
300             }{\@tempa}%
301         }%
302         \@tempa
303     \xp\endgroup
304     \@tempa
305 }

```

`\BibSpecAlias` This is a `\def` rather than a `\let` because using `\let` would make `\BibSpecAlias` statements order-sensitive in a way that seems frequently to be a stumbling block to unwary package writers. But then we should probably do at least the simplest kind of infinite loop check.

```

306 \newcommand{\BibSpecAlias}[2]{%
307     \xp\def\xp{@tempa\xp{\csname setbib@\#1\xp\endcsname}%
308     \xp\ifx\csname setbib@\#2\endcsname\@tempa
309         \amsrefs@error{%
310             Mirror alias #1->#2 not allowed (infinite loop)}\ehc
311     \else
312         \xp\def\csname setbib@\#1\xp\endcsname
313             \xp{\csname setbib@\#2\endcsname}%
314     \fi
315 }

```

6.10 The standard bibliography types

```

316 \BibSpec{article}{%
317     +{}  {\PrintAuthors}           {author}
318     +{}, { \textit}               {title}
319     +{.} { }
320     +{:} { \textit}               {subtitle}
321     +{,} { \PrintContributions}  {contribution}
322     +{.} { \PrintPartials}       {partial}
323     +{,} { }
324     +{}  { \textbf}               {journal}

```

The date form is tricky depending on presence or absence of DOI.

```

325     +{}  { \PrintDatePV}          {date}
326     +{,} { \issuetext}           {number}
327     +{,} { \eprintpages}         {pages}
328     +{,} { }
329     +{,} { \PrintDOI}            {doi}
330     +{,} { available at \eprint} {eprint}
331     +{}  { \parenthesize}        {language}
332     +{}  { \PrintTranslation}   {translation}
333     +{;} { \PrintReprint}        {reprint}
334     +{.} { }
335     +{.} {}
336     +{}  {\SentenceSpace \PrintReviews} {review}
337 }

```

```

338
339 \BibSpec{partial}{%
340   +{} {}                                {part}
341   +{} { \textit}                           {subtitle}
342   +{}, { \PrintContributions}             {contribution}
343   +{}, { }                               {journal}
344   +{} { \textbf}                          {volume}
345   +{} { \PrintDatePV}                   {date}
346   +{}, { \issuetext}                   {number}
347   +{}, { \eprintpages}                 {pages}
348 }
349
350 \BibSpec{contribution}{%
351   +{} {}                                {type}
352   +{} { by \PrintNameList}              {author}
353 }
354
355 \BibSpec{book}{%
356   +{} { \PrintPrimary}                  {transition}
357   +{}, { \textit}                      {title}
358   +{}, { }                            {part}
359   +{} { \textit}                      {subtitle}
360   +{}, { \PrintEdition}                {edition}
361   +{} { \PrintEditorsB}               {editor}
362   +{}, { \PrintTranslatorsC}          {translator}
363   +{}, { \PrintContributions}         {contribution}
364   +{}, { }                            {series}
365   +{}, { \voltext}                   {volume}
366   +{}, { }                            {publisher}
367   +{}, { }                            {organization}
368   +{}, { }                            {address}
369   +{}, { \PrintDateB}                 {date}
370   +{}, { }                            {status}
371   +{} { \parenthesize}                {language}
372   +{} { \PrintTranslation}            {translation}
373   +{} { \PrintReprint}                {reprint}
374   +{}, { }                            {note}
375   +{}, { }                            {transition}
376   +{} { \SentenceSpace \PrintReviews} {review}
377 }
378
379 \BibSpec{collection.article}{%
380   +{} { \PrintAuthors}                {author}
381   +{}, { \textit}                     {title}
382   +{}, { }                           {part}
383   +{} { \textit}                     {subtitle}
384   +{}, { \PrintContributions}        {contribution}
385   +{}, { \PrintConference}           {conference}
386   +{} { \PrintBook}                  {book}
387   +{}, { }                           {booktitle}

```

```

388    +{,} { \PrintDateB}           {date}
389    +{,} { pp.^}                {pages}
390    +{,} { }                     {status}
391    +{,} { \PrintDOI}            {doi}
392    +{,} { available at \eprint} {eprint}
393    +{} { \parenthesize}         {language}
394    +{} { \PrintTranslation}    {translation}
395    +{:} { \PrintReprint}        {reprint}
396    +{.} { }                     {note}
397    +{.} {}                      {transition}
398    +{} { \SentenceSpace \PrintReviews} {review}
399 }

400

401 \BibSpec{conference}{%
402    +{} {}                      {title}
403    +{} { \PrintConferenceDetails} {transition}
404 }

405

406 \BibSpec{innerbook}{%
407    +{,} { }                     {title}
408    +{.} { }                     {part}
409    +{:} { }                     {subtitle}
410    +{,} { \PrintEdition}         {edition}
411    +{} { \PrintEditorsB}         {editor}
412    +{,} { \PrintTranslatorsC}    {translator}
413    +{,} { \PrintContributions}   {contribution}
414    +{,} { }                     {series}
415    +{,} { \voltext}              {volume}
416    +{,} { }                     {publisher}
417    +{,} { }                     {organization}
418    +{,} { }                     {address}
419    +{,} { \PrintDateB}           {date}
420    +{.} { }                     {note}
421 }

422

423 \BibSpec{report}{%
424    +{} { \PrintPrimary}          {transition}
425    +{,} { \textit}               {title}
426    +{.} { }                     {part}
427    +{:} { \textit}               {subtitle}
428    +{,} { \PrintEdition}         {edition}
429    +{,} { \PrintContributions}   {contribution}
430    +{,} { Technical Report }   {number}
431    +{,} { }                     {series}
432    +{,} { }                     {organization}
433    +{,} { }                     {address}
434    +{,} { \PrintDateB}           {date}
435    +{,} { \eprint}               {eprint}
436    +{,} { }                     {status}
437    +{} { \parenthesize}          {language}

```

```

438     +{} { \PrintTranslation}           {translation}
439     +{}; { \PrintReprint}            {reprint}
440     +{.} { }                      {note}
441     +{.} {}                     {transition}
442     +{} {\SentenceSpace \PrintReviews} {review}
443 }
444
445 \BibSpec{thesis}{%
446     +{} {\PrintAuthors}             {author}
447     +{,} { \textit}                {title}
448     +{:} { \textit}                {subtitle}
449     +{,} { \PrintThesisType}       {type}
450     +{,} { }                     {organization}
451     +{,} { }                     {address}
452     +{,} { \PrintDateB}            {date}
453     +{,} { \eprint}                {eprint}
454     +{,} { }                     {status}
455     +{} { \parenthesize}          {language}
456     +{} { \PrintTranslation}       {translation}
457     +{} { \PrintReprint}           {reprint}
458     +{.} { }                     {note}
459     +{.} {}                      {transition}
460     +{} {\SentenceSpace \PrintReviews} {review}
461 }
462
463 \BibSpec{webpage}{%
464     +{} {\PrintAuthors}             {author}
465     +{,} { \emph}                  {title}
466     +{:} { \emph}                  {subtitle}
467     +{} { \PrintDate}               {date}
468     +{,} { \url}                   {url}
469     +{.} { Accessed \PrintDateField} {accessdate}
470     +{.} { }                     {note}
471     +{.} {}                      {transition}
472 }
473 %   \begin{macrocode}
474 \BibSpecAlias{periodical}{book}
475 \BibSpecAlias{collection}{book}
476 \BibSpecAlias{proceedings}{book}
477 \BibSpecAlias{manual}{book}
478 \BibSpecAlias{miscellaneous}{book}
479 \BibSpecAlias{misc}{miscellaneous}
480 \BibSpecAlias{unpublished}{book}
481 \BibSpecAlias{proceedings.article}{collection.article}
482 \BibSpecAlias{techreport}{report}

\setbib@incollection
483 \edef\setbib@incollection{%
484     \expandafter\csname setbib@collection.article\endcsname
485 }

```

```
\setbib@inproceedings
486 \edef\setbib@inproceedings{%
487   \exp@nx\csname setbib@collection.article\endcsname
488 }
```

Some more entry types for implementing abbreviations.

```
489 \BibSpec{name}{%
490   +{} {\PrintAuthors} {name}
491 }
492
493 \BibSpec{publisher}{%
494   +{}, {} { } {publisher}
495   +{}, {} { } {address}
496 }
```

6.11 The biblist environment

The `biblist` environment can be used with a section or chapter heading.
Use a standard L^AT_EX counter for numbering bibliography items.

```
497 \newcounter{bib}
498 \DefineSimpleKey{biblist}{prefix}
499 \DefineSimpleKey{biblist}{labels}
```

```
biblist
500 \newenvironment{biblist}{%
501   \setcounter{bib}\z@
502   \biblist
503 }{%
504   \endbiblist
505 }
```

```
biblist*
506 \newenvironment{biblist*}{%
507   \biblist
508 }{%
509   \endbiblist
510 }
```

```
\biblistfont
511 \newcommand{\biblistfont}{%
512   \normalfont
513   \footnotesize
514 }
```

`\amsrefs@lbibitem` Reference processing at the AMS sometimes results in raw `\bibitem` entries
`\amsrefs@bibitem` being interspersed with `\bib` entries in a bibliography. For that to work, we
need to modify `\@lbibitem` and `\@bibitem` to interoperate more smoothly with
`amsrefs`.

```
515 \def\amsrefs@lbibitem[#1]#2{%
```

```

516   \begingroup
517     \def\CurrentBib{#2}%
518     \def\thebib{#1}%
519     \@nbrlistfalse
520     \item\leavevmode
521     \if@filesw
522       {\let\protect\noexpand
523        \immediate\write\auxout{\string\bibcite{#2}{{#1}{}}}}%
524     \fi
525   \endgroup
526   \ignorespaces
527 }
528
529 \def\amsrefs@bibitem#1{%
530   \def\CurrentBib{#1}%
531   \item
532   \if@filesw
533     \immediate\write\auxout{\string\bibcite{#1}{{\the\value{\@listctr}}}}%
534   \fi
535   \ignorespaces
536 }

\@biblist
537 \newcommand\@biblist[1][]{%
538   \stepcounter{bib@env}
539   \biblistfont
540   \labelsep .5em\relax
541   \let\@bibitem\amsrefs@bibitem
542   \let\@lbibitem\amsrefs@lbibitem
543   \list{\BibLabel}{%
544     \restore@labelwidth
545     \maxlabelwidth\z@%
546     \@nbrlisttrue
547     \def\@listctr{bib}%
548     \let\makelabel\bib@mklab
549     #1\relax
550   }%
551   \sloppy
}

Discourage page breaks within bibliography entries and disable them completely
for entries that are less than four lines long.

552 \interlinepenalty\@m
553 \clubpenalty\@M
554 \widowpenalty\clubpenalty
555 \frenchspacing
556 \ResetCapSFCodes
557 \c@ifstar{\@biblistsetup}{}%
558 }

\@biblistsetup

```

```

559 \newcommand{\@biblistsetup}[1]{%
560   \RestrictedSetKeys{}{\biblist}{\the\rsk@toks}{#1}%
561   \rkvIfEmpty{\biblist}{\prefix}{\%{%
562     \let\amsrefs@label@prefix\biblist'prefix
563   }%
564   \rkvIfEmpty{\biblist}{\labels}{\%{%
565     \@ifundefined{\amsrefs@option@\biblist'labels}{%
566       \amsrefs@warning{Invalid label style '\biblist'labels'}%
567     }%
568     \csname\amsrefs@option@\biblist'labels\endcsname
569   }%
570 }%
571 }

\@endbiblist Change error for empty list (no items) to warning, to allow authors to leave
their bibliography temporarily empty during writing:
572 \def\@endbiblist{%
573   \save@labelwidth
574   \def\@noitemerr{\@latex@warning{Empty bibliography list}}%
575   \global\let\previous@primary\empty
576   \endlist
577 }

\@maxlabelwidth
578 \newdimen\@maxlabelwidth

\bib@mklab
579 \def\bib@mklab#1{%
580   \settowidth\@tempdima{#1}%
581   \ifdim\@tempdima > \@maxlabelwidth
582     \global\@maxlabelwidth\@tempdima
583   \fi
584   #1\hfil
585 }

586 \newcounter{bib@env}

\save@labelwidth
587 \def\save@labelwidth{%
588   \if@filesw
589     \immediate\write\auxout{%
590       \string\newlabel{[bibenv:\the\c@bib@env]}{\the\@maxlabelwidth}%
591     }%
592   \fi
593 }

\restore@labelwidth
594 \def\restore@labelwidth{%
595   \exp\ifx\csname r@[bibenv:\the\c@bib@env]\endcsname\relax

```

```

596      \resetbiblist{00}%
597  \else
598      \@xp\labelwidth\csname r@[\bibenv:\the\c@bib@env]\endcsname
599      \leftmargin\labelwidth
600      \advance\leftmargin\labelsep
601  \fi
602 }

```

\ResetCapSFCodes Presumably this is here because there has been a problem in the past with packages that change the \catcodes of capital letters.

```

603 \providecommand{\ResetCapSFCodes}{%
604     \count@='`A
605     \def\@tempa{%
606         \sfcode\count@=\@m
607         \advance\count@\@ne
608         \ifnum\count@>`Z\relax \expandafter\@gobble \fi
609     \@tempa
610 }%
611 \@tempa
612 }

```

\CurrentBib In case this is undefined sometimes.

```
613 \def\CurrentBib{??}
```

```

\BibLabel
614 \newcommand{\BibLabel}{%
615     \hfill
616     \Hy@raisedlink{\hyper@anchorstart{cite.\CurrentBib}\hyper@anchorend}%
617     [\thebib]%
618 }

\resetbiblist
619 \newcommand{\resetbiblist}[1]{%
620     \settowidth\labelwidth{\def\thebib{\#1}\BibLabel}%
621     \leftmargin\labelwidth
622     \ifdim\labelwidth=\z@
623         \leftmargin=1em
624         \itemindent=-\leftmargin
625     \else
626         \advance\leftmargin\labelsep
627     \fi
628 }

```

6.12 Processing bibliography entries

There are several things one might want to do when a \bib entry is encountered:

1. Format and print it. This corresponds to the direct entry of bibliography items as described in section 2.1 of the users's guide.

2. Copy it into a .bb1 file. This corresponds to the use of \bibselect and an external .ltb database as described in section 2.2 of the user’s guide.
3. Store the full information in memory. This is done by \bib*.

\bib Here is where the rubber hits the road.

```

629 \newcommand{\bib}{%
630   \begingroup
631     \@ifstar{%
632       \c@tempswatrue
633       \let\@bibdef\star@bibdef
634       \BibItem
635     }{%
636       \c@tempswafalse
637       \BibItem
638     }%
639 }
```

\BibItem Arguments:

```

#1 <- citekey.
#2 <- bibtype.
```

```

640 \newcommand{\BibItem}[2]{%
641   \vdef\c@tempa{\#1}%
642   \edef\c@tempa{%
643     \edef\c@nx{\c@tempa{\c@nx\c@xp\c@nx\zap@space\c@tempa\space\c@nx\c@empty}}%
644   }%
645   \c@tempa
646   \edef\c@tempb{%
647     \c@nx\c@bibdef\c@xp\c@nx\csname setbib@\#2\endcsname{\#2}{\c@tempa}}%
648 }%
649 \c@tempb
650 }
```

\@bibdef \@bibdef is a pointer to the procedure that should be handed the entry’s key-value pairs. It has one of four values:

1. \star@bibdef
2. \normal@bibdef
3. \copy@bibdef
4. \selective@bibdef

Arguments:

```

#1 <- \setbib@bibtype.
#2 <- bibtype.
#3 <- citekey.
```

```

651 \AtBeginDocument{\let\@bibdef\normal@bibdef}
```

\bib@exec And \bib@exec is a pointer to the procedure that \normal@bibdef will invoke to process the key-value pairs after they've been parsed. It has one of these values:

1. \bib@store
2. \bib@print

Arguments:

```
#1 <- citekey.
#2 <- \the\rsk@toks.
#3 <- \setbib@bibtype.
```

```
652 \AtBeginDocument{\let\bib@exec\bib@print}
```

6.12.1 \@bibdef Implementations

\normal@bibdef *Arguments:*

```
#1 <- \setbib@bibtype.
#2 <- bibtype.
#3 <- citekey.
```

```
653 \def\normal@bibdef#1#2#3{%
```

\CurrentBibType is used by export-bibtex, but there might be a better way to handle it. (dmj)

```
654     \def\CurrentBibType{-#2}%
655     \ifx\relax#1%
656         \amsrefs@error{Undefined entry type: #2}\@ehc
657         \let#1\setbib@misc
658     \fi
659     \RestrictedSetKeys{}{bib}%
660     {\bib@exec{#3}{\the\rsk@toks}{#1}\endgroup}%
661 }
662
663 \let\@bibdef\normal@bibdef
```

\star@bibdef *Arguments:*

```
#1 <- \setbib@bibtype.
#2 <- bibtype.
#3 <- citekey.

664 \def\star@bibdef{%
665     \let\bib@exec\bib@store
666     \normal@bibdef
667 }
```

\copy@bibdef This is a variation that copies everything into the .bbl file. Used by \bibselect* and \bib* inside .ltb files.

```
668 \def\copy@bibdef{%
669     \if@tempswa
670         \xp\defer@bibdef
```

```

671     \else
672         \xp\copy@bibdef@a
673     \fi
674 }

\copy@bibdef@a
675 \def\copy@bibdef@a#1#2#3#4{%
676     \open@bbl@file
677     \process@xrefs{#4}%
678     \bbl@write{%
679         \string\bib\if@tempswa*\fi{#3}{#2}\string{\iffalse}\fi
680     }%
}

Since we're supplying our own definition of \rsk@set, we don't actually need
the group argument, so we leave it out to save a few tokens.

681     \RestrictedSetKeys{\global\let\rsk@set\bbl@copy}\empty
682         {\bbl@write{\iffalse\fi\string}^~J}%
683         \endgroup{#4}%
684 }

685 \catcode`\:=11
686
687 \def\modify@xref@fields{%
688     \let\set:bib'author\output@xref@a
689     \let\set:bib'editor\output@xref@a
690     \let\set:bib'translator\output@xref@a
691     \let\set:bib'journal\output@xref@a
692     \let\set:bib'publisher\output@xref@a
693     \def\set:bib'xref##1##2{\output@xref@{##1}\empty}%
694     \def\set:bib'book##1##2{\output@inner@xref@{##1}\empty}%
695     \let\set:bib'conference\set:bib'book
696     \let\set:bib'partial\set:bib'book
697     \let\set:bib'reprint\set:bib'book
698     \let\set:bib'translation\set:bib'book
699 }
700
701 \catcode`\:=12
702
703 \def\process@xrefs#1{%
704     \begingroup
705         \RestrictedSetKeys{\modify@xref@fields}{bib}{\the\rsk@toks}{#1}%
706     \endgroup
707 }
708
709 \def\output@xref@a#1#2{%
710     \def@tempa{#1}%
711     \lowercase{\def\@tempb{#1}}%
712     \ifx\@tempa\@tempb
713         \output@xref@{#1}%
714     \fi
}

```

```

715 }
716
717 \def\output@xref@#1{%
718   \@ifnotempty{#1}{%
719     \@ifundefined{bi@#1}{}{%
720       \begingroup
721         \let\star@bibdef\copy@bibdef@a
722         \csname bi@#1\endcsname
723       \endgroup
724     }%
725     \xp\g@undef\csname bi@#1\endcsname
726   }%
727 }
728
729 \def\output@inner@xref@#1{%
730   \in@={#1}%
731   \ifin@\else
732     \output@xref@{#1}%
733   \fi
734 }

\bbbl@copy
735 \def\bbbl@copy#1\endcsname#2{%
736   \begingroup
737     \def\@tempa{#1}%
738     \toks@{\{#2}\}%
739     \star@{\bbbl@copy@a}{}%
740 }

\bbbl@copy@a
741 \def\bbbl@copy@a#1{%
742   \@ifnotempty{#1}{%
743     \add@toks@{*{#1}}{%
744   }%
745     \bbbl@write{ \space\@tempa=\the\toks@,}%
746   \endgroup
747   \rsk@resume
748 }

\selective@bibdef This is a variation that ignores anything not having a known citation key. Used by \bibselect.

Arguments:
#1 <- \setbib@bibtype.
#2 <- bibtype.
#3 <- citekey.

749 \def\selective@bibdef#1#2#3{%
750   \xp\selbibdef@a\csname b@#3\endcsname{#1}{#2}{#3}%
751 }

```

```
\selbibdef@a
752 \def\selbibdef@a#1{%
753   \def\@tempa{\endgroup\@gobblefour}%
754   \ifx\relax#1\else \exp\selbibdef@b#1\@nil \fi
755   \@tempa
756 }
```

```
\selbibdef@b
757 \def\selbibdef@b#1#2#3\@nil{%
758   \ifx 1#2\let\@tempa\copy@bibdef\fi
759 }
```

\defer@bibdef This is a variation that ignores anything not having a known citation key. Used by **\bibselect**.

Arguments:

```
#1 <- \setbib@bibtype.
#2 <- bibtype.
#3 <- citekey.
#4 <- key-val pairs.

760 \def\defer@bibdef#1#2#3#4{%
761   \xp\gdef\csname bi@#3\endcsname{%
762     \bib*{#3}{#2}{#4}%
763   }%
764   \xp\addto@defer@list \csname bi@#3\endcsname
765   \endgroup
766 }
```

```
\bibdefer@list
767 \let\bibdefer@list\empty
```

```
\addto@defer@list
768 \def\addto@defer@list#1{%
769   \begingroup
770   \def\do{\@nx\do\@nx}%
771   \xdef\bibdefer@list{\bibdefer@list\do#1}%
772   \endgroup
773 }
```

6.12.2 \bib@exec Implementations

\bib@store This is the easy one. It just stores the entire set of key-value pairs in **\bi@citekey**.

```
774 \def\bib@store#1{%
775   \afterassignment\gobble
776   \xp\xdef\csname bi@#1\endcsname
777 }
```

```
\bib@print Arguments:
#1 <- citekey.
```

```

#2 <- \the\rsk@toks.
#3 <- \setbib@bibtype.

778 \def\bib@print#1#2#3{%
779     \bib@start{#1}%
780     \let\setbib@@#3%
781     #2\relax      % execute definitions locally
782     \bib@resolve@xrefs
783     \bib@field@patches
784     \bib@selectlanguage
785     \generate@label
786     \bib'setup
787     \bib@cite{#1}%
788     \kern@ne sp
789     \ifx\setbib@@\setbib@article
790         \ifx\bib'book@\empty
791             \ifx\bib'book@\empty
792                 \ifx\bib'conference@\empty
793                     \else
794                         \let\setbib@@\setbib@incollection
795                     \fi
796                 \else
797                     \let\setbib@@\setbib@incollection
798                 \fi
799             \else
800                 \let\setbib@@\setbib@incollection
801             \fi
802         \fi
803         \setbib@@
804     \bib@end
805 }

```

\bib@print@inner Note that the order of the arguments is reversed with respect to \bib@print.
Maybe that isn't such a great idea.

Arguments:

```

#1 <- \setbib@bibtype.
#2 <- \the\rsk@toks.

806 \def\bib@print@inner#1#2{%
807     \begingroup
808     #2\relax      % execute definitions locally
809     \bib@resolve@xrefs
810     \bib@field@patches
811     \bib'setup
812     #1%
813     \endgroup
814 }

```

\current@citekey

```
815 \let\current@citekey\empty
```

```
\prev@citekey
816 \let\prev@citekey\empty

\bib@start There used to be more to it.
817 \def\bib@start#1{%
818   \begingroup
819     \def\current@citekey{#1}%
820 }

\bib@end Instead of being handled by \bib@end, ending punctuation is normally handled
via the transition field (q.v.)
821 \def\bib@end{%
822   \relax
823   \xp\PrintBackRefs\xp{\CurrentBib}%
824   \par
825   \save@primary
826   \global\let\prev@citekey\current@citekey
827   \endgroup
828 }
```

6.12.3 Resolving cross-references

```
\bib@resolve@xrefs
829 \def\bib@resolve@xrefs{%
830   \xref@check@c\bib'xref
831   \xref@check@a\bib'author
832   \xref@check@a\bib'editor
833   \xref@check@a\bib'translator
834   \xref@check@b\bib'journal
835   \xref@check@b\bib'publisher
836 }

\xref@check@a Resolve a contributor (typically a \DefineName) alias. Requires rebuilding the
list.
837 \def\xref@check@a#1{%
838   \ifx\@empty#1\relax
839   \else
840     \begingroup
841       \toks@\emptytoks
842       \temptokenb\emptytoks
843       \series@index{z}
844       \def\name{\xref@check@aa#1}%
845       #1\relax
846       \edef\tmpa{%
847         \def\@nx#1{\the\toks@}%
848         \the\temptokenb
849       }%
850     \xp\endgroup
851     \tmpa
```

```

852      \fi
853 }

\xref@check@aa
854 \def\xref@check@aa#1#2{%
855   \advance\series@index\@ne
856   \def\@tempa{#2}%
857   \lowercase{\def\@tempb{#2}}%
858   \ifx\@tempa\@tempb
859     \ifx\@tempa\@empty
860       \add@toks{\{\name{}\}}%
861     \else
862       \@ifundefined{bi@#2}{%
863         \BibAbbrevWarning{#2}%
864         \add@toks{\{\name{#2}}%
865       }{%
866         \xref@check@ab#1{#2}%
867       }%
868     \fi
869   \else
870     \add@toks{\{\name{#2}}%
871   \fi
872 }

\xref@check@ab
873 \def\xref@check@ab#1#2{%
874   \csname bi@#2\endcsname
875   \ifx\@empty\bib' name
876     \@temptokena{#2}%
877   \else
878     \@temptokena\@xp{\bib' name}%
879     \get@property\@tempa\bib' name
880     \edef\@tempa{%
881       \c@nx\addto@hook\@temptokenb{%
882         \c@nx\reset@nth@property\c@nx#1\the\series@index{\@tempa}%
883       }%
884     }%
885     \@tempa
886   \fi
887   \edef\@tempa{\c@nx\add@toks{\c@nx\name{\the\@temptokena}}{}}%
888   \@tempa
889 }

\xref@check@b Resolve a journal or publisher alias (typically a \DefinePublisher or
\xref@check@b \DefineJournal alias).
890 \def\xref@check@b#1{%
891   \ifx\@empty#1%
892   \else
893     \toks@\@xp{#1}%

```

```

894     \edef\@tempb{\lowercase{\def\@nx\@tempa{\the\toks@}}}\%
895     \@tempb
896     \ifx\@tempa#1\relax % all lowercase
897         \c@ifundefined{bi@#1}{%
898             \BibAbbrevWarning{#1}%
899         }{%

```

We pass control to `\xref@check@c` here to handle inheritance of multiple fields properly. This means some of the checking we've just done gets done again, but I can live with that.

```

900         \let#1\@empty
901         \xref@check@c\@tempa
902     }%
903     \fi
904 \fi
905 }

```

`\xref@check@c` Resolve an xref field.

```

906 \def\xref@check@c#1{%
907     \ifx#1\@empty
908     \else
909         \begingroup
910             \apply\auto@protect\amsrefs@textsymbols
911             \apply\auto@protect\amsrefs@textaccents
912             \let\DSK@def\xref@add@toks
913             \let\DSK@append\xref@append
914             \toks@\@emptytoks
915             \let\bib@reset\@empty

```

The `\cfor` here is just a fancy way of expanding #1. (Or is it?)

```

916     \cfor\xref@ID:=#1\do{%
917         \c@ifundefined{bi@\xref@ID}{%
918             \XRefWarning{\xref@ID}%
919         }{%
920             \csname bi@\xref@ID\endcsname
921         }%
922     }%
923     \edef\@tempa{\endgroup\the\toks@}%
924     \@tempa
925 \fi
926 }

```

`\xref@add@toks` If any title occurs in an `xrefed` item, assume that it is a book title. This might not always be the best assumption? Let's see how it goes though. [mjd,2001-12-11]

Arguments:

```

#1 <- \bib'field.
#2 <- value.

```

```
927 \def\xref@add@toks#1#2#3{%
```

```

928     \ifx#1\empty
929         \edef\@tempa{%
930             \c@nx\add@toks@{\c@xp\c@nx\csname\rkv@setter#1\endcsname{#2}{#3}}%
931         }%
932         \@tempa
933     \else
934         \in@\bib'title{#1}%
935         \ifin@
936             \ifx\bib'booktitle\empty
937                 \edef\@tempa{%
938                     \c@nx\add@toks@{%
939                         \c@xp\c@nx\csname set:bib'booktitle\endcsname
940                     }%
941                 }%
942                 \@tempa
943                 \add@toks@{#2}{#3}%
944             \fi
945         \fi
946     \fi
947 }

948 \def\xref@append#1#2#3#4{%
949     \edef\@tempa{%
950         \c@nx\add@toks@{\c@xp\c@nx\csname\rkv@setter#2\endcsname{#3}{#4}}%
951     }%
952     \@tempa
953 }

```

```
\BibAbbrevWarning
954 \def\BibAbbrevWarning#1{\amsrefs@warning{Abbreviation '#1' undefined}}
```

```
\XrefWarning
955 \def\XrefWarning#1{\amsrefs@warning{Xref '#1' undefined}}
```

6.12.4 Bib field preprocessing

```
\current@primary
956 \let\current@primary\empty

\previous@primary
957 \let\previous@primary\empty

\save@primary
958 \IfOption{nobysame}{%
959     \let\save@primary\empty
960 }{%
961     \def\save@primary{%
962         \global\let\previous@primary\current@primary
963     }%
964 }
```

\bib@field@patches Depending on your point of view, this macro either puts the bibitem into a canonical form or, alternatively, it fudges the data to fit our model. Either way, it simplifies formatting the bibliography.

```

965 \def\bib@field@patches{%
966   \ifx\bib'author\@empty
967     \ifx\bib'editor\@empty
968       \let\current@primary\bib'translator
969       \let\print@primary\PrintTranslatorsA
970     \else
971       \let\current@primary\bib'editor
972       \let\print@primary\PrintEditorsA
973     \fi
974   \else
975     \let\current@primary\bib'author
976     \let\print@primary\PrintAuthors
977   \fi
978   \ifx\bib'address\@empty
979     \let\bib'address\bib'place
980   \fi
981   \ifx\bib'organization\@empty
982     \ifx\bib'institution\@empty
983       \let\bib'organization\bib'school
984     \else
985       \let\bib'organization\bib'institution
986     \fi
987   \fi
988   \ifx\bib'date\@empty
989     \ifx\bib'year\@empty
990       \let\bib@year\bib'status
991     \else
992       \bib@parsedate\bib'year
993     \fi
994   \else
995     \bib@parsedate\bib'date
996   \fi

```

Example 21 on page 74 of *Mathematics into Type* [2] seems to indicate that when the year serves as the volume number, the date should be suppressed. If so, this is where that is done.

```

997   \def@\tempa{year}%
998   \ifx\bib'volume@\tempa
999     \let\bib'volume\bib@year
1000    \let\bib'date\@empty
1001  \fi

```

Some journals have “numbers” but no “volumes”. AMS house style is to treat the number as volume.

```

1002  \ifx\setbib@@\setbib@article
1003    \ifx\bib'volume\@empty
1004      \ifx\bib'number\@empty\else

```

```

1005           \let\bib'volume\bib'number
1006           \let\bib'number\@empty
1007       \fi
1008   \fi
1009 \fi
1010 \bib@language@fixup
1011 }

```

6.12.5 Date setup

```

\bib@year
1012 \let\bib@year\@empty

\bib@month
1013 \let\bib@month\@empty

\bib@day
1014 \let\bib@day\@empty

\bib@parsedate Parse an ISO 8601 date into its year, month and day components, but without
                 actually verifying that any of the components are numeric. Hmm.
1015 \def\bib@parsedate#1{%
1016   \exp\bib@parsedate@a#1---\@nil
1017 }

\bib@parsedate@a
1018 \def\bib@parsedate@a#1-#2-#3-#4\@nil{%
1019   \def\bib@year{\#1}%
1020   \def\bib@month{\#2}%
1021   \def\bib@day{\#3}%

```

The rest of this macro tries to rewrite `\bib'date` into a normalized form. I'm not sure if this is a good idea.

```

1022 \ifx\@empty\bib@day
1023   \ifx\@empty\bib@month
1024     \let\bib'date\bib@year
1025   \else
1026     \def\bib'date{\#1-\#2}%
1027   \fi
1028 \else
1029   \def\bib'date{\#1-\#2-\#3}%
1030 \fi
1031 }

```

6.12.6 Language setup

```
\bib@language@fixup
1032 \def\bib@language@fixup{%
1033   \ifx\bib'hyphenation\empty
1034     \ifx\bib'language\empty
1035       \let\bib@language\biblanguagedefault
1036     \else
1037       \let\bib@language\bib'language
1038     \fi
1039   \else
1040     \let\bib@language\bib'hyphenation
1041   \fi
1042 \def@tempa##1 ##2@nil{\lowercase{\def\bib@language{##1}}}%
```

The mysterious \@firstofone here is to preserve the space before the \@nil.

```
1043   \@firstofone{\@xp\@tempa\bib@language} \@nil
1044 }
```

\bib@selectlanguage For \bib purposes we are interested mainly in testing whether the hyphenation patterns are the same. So we use an if-same-patterns test (by which babel's 'english' and 'american' compare as equal) rather than an if-same-language test. Also, the way that the \selectlanguage command checks to see whether a language has been properly defined for babel use is to see if \dateLANGUAGE is defined. And if we tried to select an undefined language, the result would be a L^AT_EX error.

```
1045 \def\bib@selectlanguage{%
1046   \@ifsame@patterns{\languagename}{\bib@language}{}{%
1047     \@ifundefined{date\bib@language}{}{%
1048       \@xp\selectlanguage\@xp{\bib@language}%
1049     }%
1050   }%
1051 }
```

```
\@ifsame@patterns
1052 \def\@ifsame@patterns#1#2{%
1053   \@xp\@ifsamepat\csname 1@#1\@xp\endcsname\csname 1@#2\endcsname
1054 }
```

```
\@ifsamepat
1055 \def\@ifsamepat#1#2{%
1056   \ifnum \ifx\relax#1\m@ne\else#1\fi = \ifx\relax#2\m@ne\else#2\fi
1057     \@xp\@firstoftwo
1058   \else
1059     \@xp\@secondoftwo
1060   \fi
1061 }
```

```
\languagename
\biblanguageEnglish
\biblanguagedefault
\bib@language
```

```

1062 \providecommand{\languagename}{english}
1063 \def\biblanguageEnglish{english}
1064 \let\biblanguageDefault\biblanguageEnglish
1065 \let\bib@language\empty

```

6.12.7 Citation label setup

```

\generate@label
1066 \let\generate@label\relax

\cite@label
1067 \def\cite@label{\@currentlabel}

\alpha@label
1068 \let\alpha@label\relax

\alpha@label@
1069 \def\alpha@label@{%
1070   \ifx\@empty\bib'@label
1071     \def\thebib{\CurrentBib}%
1072   \else
1073     \let\thebib\bib'@label
1074   \fi
1075 }%

\amsrefs@option@numeric
1076 \def\amsrefs@option@numeric{%
1077   \let\alpha@label\relax
1078   \let\generate@label\relax
1079   % \@nmbrlisttrue
1080 }

\amsrefs@option@alphabetic
1081 \def\amsrefs@option@alphabetic{%
1082   \let\alpha@label\alpha@label@
1083   \let\generate@label\generate@alphalabel
1084   \let\calc@author@part\calc@author@part@
1085   \let@suffix@format@\alph
1086   \let\append@label@year\append@label@year@
1087   % \@nmbrlistfalse
1088 }

\amsrefs@option@shortalphabetic
1089 \def\amsrefs@option@shortalphabetic{%
1090   \let\alpha@label\alpha@label@
1091   \let\generate@label\generate@alphalabel
1092   \let\calc@author@part\calc@author@part@short
1093   \let@suffix@format@\arabic
1094   \let\append@label@year\@empty
1095   % \@nmbrlistfalse
1096 }

```

\bib@cite When \bib@cite is called, author name and year are available in \bib@author and \bib@year.

Arguments:

```
#1 <- citekey.

1097 \def\bib@cite#1{%
1098   \def\CurrentBib{\#1}%
1099   \alpha@label           % modify \thebib if necessary
1100   \item\leavevmode
1101   \SK@\SK@{\label{\#1}}%
1102   \exp\bib@cite@a\csname b@\#1\endcsname
1103   \bibcite@write{\#1}%
1104 }

1105 \def\bib@cite@a#1{%
1106   \ifx\relax#1%
1107     \begingroup
1108       \auto@protect\etaltext
1109       \protected@edef\@tempa{%
1110         \gdef\@nx#1{%
1111           \@nx\citesel 01{\cite@label}{\bib@label@year}{}}%
1112       }%
1113     }%
1114     \exp\endgroup
1115     \@tempa
1116   \else
1117     \exp\bib@cite@check\exp#1#1\empty\empty\empty\empty\empty\empty
1118   \fi
1119 }
```

\bib@cite@check For the citation key we want to check if it is already defined. But there is a slight problem. There is already one control sequence in use for each bibliography entry, to store the label or the author/year information needed by \cite. If we introduce another control sequence to check whether a particular cite is multiply defined, then we double the number of control sequences used. For a large bibliography in a book this is fairly serious. This is addressed by using a \citesel function.

Arguments:

```
#1 <- \b@citekey.
#2 <- \citesel.
#3 <- cited?.
#4 <- used?.
#5 <- label.
#6 <- year.
#7 <- backrefs.

1120 \def\bib@cite@check#1#2#3#4#5#6#7{%
1121   \ifx 1#4\relax
1122     \DuplicateBibKeyWarning
```

```
1123 \else
```

This has gotten *way* out of hand.

```
1124     \begingroup
1125         \auto@protect\etaltext
1126         \Capply\auto@protect\amsrefs@textsymbols
1127         \Capply\auto@protect\amsrefs@textaccents
1128         \ctempswafalse
1129         \in@\CitePrintUndefined{#5}%
1130         \ifin@
1131             \let\@tempa\@empty
1132         \else
1133             \def\@tempa{#5}%
1134         \fi
1135         \ifx\@tempa\@empty
1136         \else
1137             \xp\ifx\xp\@currentlabel\cite@label
1138                 \edef\@tempb{\cite@label}%
1139             \else
1140                 \let\@tempb\cite@label
1141             \fi
1142             \ifx\@tempa\@tempb
1143                 \def\@tempa{#6}%
1144                 \ifx\@tempa\bib@label@year
1145                 \else
1146                     \ctempswatrue
1147                 \fi
1148             \else
1149                 \ctempswatrue
1150             \fi
1151         \fi
1152         \if@tempswa
1153             \@ifempty{#6}{%
1154                 \def\@tempa{#5}%
1155                 \let\@tempb\cite@label
1156             }{%
1157                 \def\@tempa{#5, #6}%
1158                 \def\@tempb{\cite@label, \bib@label@year}%
1159             }%
1160             \amsrefs@warning{Citation label for \extr@cite#1 is
1161                 changing from '\@tempa' to '\@tempb'}%
1162         \fi
1163         \protected@edef\@tempa{%
1164             \gdef\@nx#1{%
1165                 \@nx\citesel #31{\cite@label}{\bib@label@year}{#7}%
1166             }%
1167         }%
1168         \xp\endgroup
1169         \@tempa
1170     \fi
```

```

1171 }

\bib@label@year
1172 \let\bib@label@year\empty

\DuplicateBibKeyWarning
1173 \def\DuplicateBibKeyWarning{%
1174   \amsrefs@warning{%
1175     Duplicate \protect\bib\space key
1176     '\CurrentBib' detected\MessageBreakNS}%
1177 }

\DuplicateBibLabelWarning
1178 \def\DuplicateBibLabelWarning{%
1179   \amsrefs@warning{%
1180     Duplicate biblabel stem '\current@stem' detected.\MessageBreakNS
1181     This usually means the order of the bibitems\MessageBreakNS
1182     is incompatible with the style of labels\MessageBreakNS
1183     you are using}%
1184 }

\bibcite@write
1185 \def\bibcite@write#1{%
1186   \if@filesw
1187     \begingroup
1188       \let\citesel\citesel@write
1189       \csname b@\#1\endcsname
1190     \endgroup
1191   \fi
1192 }

\citesel@write
1193 \def\citesel@write#1#2#3#4#5{%
1194   \toks@{\{#3}{#4}}%
1195   \immediate\write\auxout{\string\bibcite{\CurrentBib}{\the\toks@}}%
1196 }

Because duplicate bibs are caught immediately, we don't need \bibcite to
run \atenddocument.

1197 \AtEndDocument{\let\bibcite\gobbletwo}

6.12.8 Printing the bibliography

\bibname
1198 \providecommand{\bibname}{Bibliography}

\refname
1199 \providecommand{\refname}{References}

```

\bib@div@mark The AMS document classes automatically take care of the page marks for `\section*` and `\chapter*`, but for the standard classes, we need to make sure that `\@mkboth` gets invoked.

```
1200 \let\bib@div@mark\@gobble
```

This is verbose, but probably safer than any alternative.

```
1201 \@ifclassloaded{amsbook}{}{%
1202   \@ifclassloaded{amsart}{}{%
1203     \@ifclassloaded{amsproc}{}{%
1204       \def\bib@div@mark#1{%
1205         \@mkboth{\MakeUppercase{#1}}{\MakeUppercase{#1}}%
1206       }%
1207     }%
1208   }%
1209 }
```

bibchapter We need to take a little extra trouble here to pre-expand the `\bibname`.

```
1210 \newenvironment{bibchapter}[1][\bibname]{%
1211   \begingroup
1212   \protected@edef\@{%
1213     \endgroup
1214     \protect\chapter*{\#1}%
1215     \protect\bib@div@mark{\#1}%
1216   }%
1217   \@
1218 }{\par}
```

bibsection And here to pre-expand the `\refname`.

```
1219 \newenvironment{bibsection}[1][\refname]{%
1220   \begingroup
1221   \protected@edef\@{%
1222     \endgroup
1223     \ifx\@bibtitlestyle\undefined
1224       \protect\section*{\#1}%
1225     \else
1226       \protect\@bibtitlestyle
1227     \fi
1228     \protect\bib@div@mark{\#1}%
1229   }%
1230   \@
1231 }{\par}
```

bibdiv Here we try to guess whether this is a book-like document or an article-like document.

```
1232 \@ifundefined{chapter}{%
1233   \newenvironment{bibdiv}{\bibsection}{\endbibsection}
1234 }{%
1235   \newenvironment{bibdiv}{\bibchapter}{\endbibchapter}
1236 }
```

This is what the standard `book` class has for the bibliography title:

```
\newenvironment{thebibliography}[1]
  {\chapter*{\bibname
    \@mkboth{\MakeUppercase\bibname}{\MakeUppercase\bibname}}%
   \list{\@biblabel{\@arabic\c@enumiv}}%}

thebibliography
1237 \renewenvironment{thebibliography}[1]{%
1238   \bibdiv
1239   \biblist[\resetbiblist{#1}]%
1240 }{%
1241   \endbiblist
1242   \endbibdiv
1243 }
```

6.13 Name, journal and publisher abbreviations

The commands `\DefineName`, `\DefinePublisher`, and `\DefineJournal` are provided to make abbreviations a little easier.

```
\DefineName
1244 \newcommand{\DefineName}[2]{%
1245   \bib*{\#1}{name}{name=\#2}}%
1246 }
```

```
\DefineJournal
1247 \newcommand{\DefineJournal}[4]{%
1248   \bib*{\#1}{periodical}{%
1249     issn=\#2,
1250     journal=\#4}
1251 }%
1252 }
```

`\DefinePublisher` Note that an explicit `address` field in a `\bib` entry will override the `address` supplied as part of a `\DefinePublisher`.

```
1253 \newcommand{\DefinePublisher}[4]{%
1254   \bib*{\#1}{publisher}{%
1255     publisher=\#3,
1256     address=\#4}
1257 }%
1258 }
```

6.14 Processing .ltb files

If you have a file that contains `amsrefs`-style `\bib` entries, you can use it as a database and extract items from it for use in another document. In typical relatively simple scenarios, the extraction can be done by L^AT_EX itself on the first pass, so that citations in the text will be successfully resolved on the second pass (possibly even the first, depending on what kind of bibliography sorting is used).

```

\bibselect
1259 \newcommand{\bibselect}{%
1260   \@ifstar{%
1261     \let\@bibdef\copy@bibdef
1262     \BibSelect
1263   }{%
1264     \let\@bibdef\selective@bibdef
1265     \BibSelect
1266   }%
1267 }

\BibSelect
1268 \newcommand{\BibSelect}[2][\bblname]{%
1269   \if@filesw
1270     \typeout{Trying to create bbl file '#1.bbl' ...}%
1271     \def\bibselect@msg{%
1272       \typeout{ ... rats. Unable to create bbl file.}%
1273     }%
1274     \let\@open@bbl@file\OpenBBLFile
1275     \@for\@tempa:=#2\do{\ReadBibData{\@tempa}}%
1276   \fi
1277   \@close@bbl@file
1278   \apply@g@undef\bibdefer@list
1279   \global\let\bibdefer@list\empty

Now read the .bbl file we just created.
1280   \let@\bibdef\normal@bibdef
1281   \input{\#1.bbl}%
1282   \let\BibSelect\MultipleBibSelectWarning
1283 }

\MultipleBibSelectWarning
1284 \newcommand\MultipleBibSelectWarning[2][]{%
1285   \amsrefs@warning{%
1286     Multiple \string\bibselect 's found (only one
1287     \string\bibselect\space per biblist environment is allowed)}%
1288   }%
1289 }

\bblname
1290 \def\bblname{\jobname}

\bib@dbfile
1291 \newread\bib@dbfile

\ReadBibData
1292 \newcommand{\ReadBibData}[1]{%
1293   \IfFileExists{#1.ltb}{%
1294     \openin\bib@dbfile=\@filef@und \relax

```

```

1295  }{%
1296      \IfFileExists{#1.ltx}{%
1297          \openin\bib@dbfile=\@filef@und \relax
1298      }{%
1299          \IfFileExists{#1.tex}{%
1300              \openin\bib@dbfile=\@filef@und \relax
1301          }{%
1302              \begingroup
1303                  \NoBibDBFile{#1}%
1304                  \let\ReadBibData@a\endgroup
1305              }%
1306          }%
1307      }%
1308      \ReadBibData@a
1309 }

\noBibDBFile
1310 \def\noBibDBFile#1{%
1311     \amsrefs@warning{No data file #1.ltb (.ltx, .tex) found}%
1312 }

\ReadBibData@a
1313 \def\ReadBibData@a{%
1314     \ProvidesFile{\@filef@und}\relax
1315     \begingroup
1316         \let\star@bibdef\defer@bibdef
1317         \ReadBibLoop
1318     \endgroup
1319     \closein\bib@dbfile
1320 }

\ReadBibLoop
1321 \def\ReadBibLoop{%
1322     \ifeof\bib@dbfile
1323         \@xp\@gobble
1324     \else
1325         \read\bib@dbfile to\CurLine
1326         The \empty is in case \CurLine is empty.
1327         \@xp\ReadBibLoop@a\CurLine\empty\@nil
1328     \fi
1329 }

```

\ReadBibLoop@e This traps top-level \bib commands. Note that:

- If \CurLine doesn't contain a complete \bib entry, the code chokes.
- If \bib is not the very first non-space token in a line, it will not be recognized.

```

1330 \long\def\ReadBibLoop@a#1#2\@nil{%
1331   \ifx\bib#1%
1332     \CurLine % just exec it
1333   \else

```

We're not done yet. The line may contain something like `\DefineName`, so we need to expand the first macro in the line and see if it starts with `\bib`. But first we check to make sure that the token we're about to expand isn't `\endinput`.

```

1334   \ifx\endinput#1%
1335     \let\ReadBibLoop\@empty
1336   \else

```

And this `\@empty` is for the admittedly unlikely case that `\CurLine` isn't empty, but its expansion is.

```

1337   \exp\ReadBibLoop\b#1#2\@empty\@nil
1338   \fi
1339 \fi
1340 }

```

`\ReadBibLoop@b`

```

1341 \long\def\ReadBibLoop@b#1#2\@nil{%
1342   \ifx\bib#1%
1343     \CurLine % just exec it
1344   \fi
1345 }

1346 \let\bblobout=\relax
1347 \let\bblobwrite\gobble
1348 \let\open@bblobfile\relax
1349 \let\close@bblobfile\relax

```

`\OpenBBLFile`

```

1350 \def\OpenBBLFile{%
1351   \if@files
1352     % Just use the next unused output stream
1353     \count@\count17
1354     \advance\count@\@ne
1355     \ifnum\count@<\sixt@n
1356       \global\chardef\bblobout=\count@
1357       \immediate\openout\bblobout=\bblobname.bbl\relax
1358       \global\let\close@bblobfile\CloseBBLFile
1359       \gdef\bblobwrite{\immediate\write\bblobout}%
1360     \else
1361       \ch@ck\count@\sixt@n\write
1362     \fi
1363   \fi
1364   \global\let\open@bblobfile\relax
1365 }

```

`\CloseBBLFile`

```
1366 \def\CloseBBLFile{%
1367     \immediate\closeout\bbb@out\relax
1368     \global\let@\close@bbbl@file\relax
1369     \global\let\bbb@write\gobble
1370     \global\let\bbb@out\relax
1371 }
```

6.15 Citation processing

6.15.1 The \citesel structure

The information used by \cite for key `moo` is stored in `\b@moo` in the form

```
\citesel{status1}{status2}{label}{year}{backref-info}
```

The first status flag is 1 if this key has already been cited earlier in the same document; 0 otherwise. This is used in some bibliography schemes to print a full list of author names for the first citation and an abbreviated author list for subsequent citations.

The second status flag is 1 if this key has already been used by a `define-cite` command (such as `\bib`); 0 otherwise. This makes it possible to issue a warning message as soon as the conflict is seen, on the first L^AT_EX run, instead of on a subsequent run during the processing of the `.aux` file.

When an author/year citation scheme is in use, args 3 and 4 hold respectively author names and year. Otherwise arg 3 simply holds a cite label and arg 4 is empty.

And finally, arg 5 holds a list of backref pointers indicating the locations in the document where this entry has been cited.

```
\citesel@update  
1372 \def\citesel@update#1#2#3#4#5#6{%  
1373     \gdef#6{\citesel 1#2{#3}{#4}{#5}  
1374 }
```

```
1375 \def\citesel@number#1#2#3#4#5{#3}
```

1376 \def\citesel@year#1#2#3#4#5{#4}

```
\citesel  
    1377 \let\citesel\citesel@number
```

6.15.2 The basic \cite command

Here is the difference between the various optional forms of \cite:

```
\cite{xyz}          -> \cite@a\citesel{xyz}{}  
                    -> \cite@bc\b@xyz\citesel{}
```

```
\cite[blub]{xyz} -> \cite@a\citesel{xyz}{blub}
-> \cite@bc\b@xyz\citesel{blub}
```

Cancelling the old L^AT_EX definition of \cite_U prevents certain problems that could arise with the `showkeys` package.

```
1378 \expandafter\let\csname cite \endcsname\relax
```

`\cite` Need to handle the standard [...] option for compatibility's sake.

```
1379 \renewcommand{\cite}[2][] {%
1380   \if\cite@single#2,\@gobble \else\MultipleCiteKeyWarning{\#2}{\#1}\fi
1381   \@ifempty{\#1}{%
1382     \cites@o{\#2}%
1383   }{%
1384     \ObsoleteCiteOptionWarning
1385     \cites@a{*{\#1}}{\#2}%
1386   }%
1387 }
```

`\MultipleCiteKeyWarning`

```
1388 \def\MultipleCiteKeyWarning#1#2{%
1389   \amsrefs@warning{%
1390     Use of \string\cites\space is recommended instead of %
1391     \string\cite\space\MessageBreak
1392     for multiple cites '#1'}%
1393   \ifnotempty{\#2}{%
1394     \amsrefs@warning{Star option requires \string\citelist\space here}%
1395   }%
1396   \global\let\MultipleCiteKeyWarning\gobbletwo
1397 }
```

`\ObsoleteCiteOptionWarning`

```
1398 \def\ObsoleteCiteOptionWarning{%
1399   \amsrefs@warning{%
1400     The form \string\cite{...}*{...} is recommended\MessageBreak
1401     instead of \string\cite{...}{...}%
1402   }\global\let\ObsoleteCiteOptionWarning\empty
1403 }
```

`\cite@single`

```
1404 \edef\cite@single#1,#2{\iffalse{\fi\iffalse{\fi\string}#2.\string}{}{}}
```

`\cites@o`

```
1405 \def\cites@o#1{\star@{\cites@oo{\#1}}{}}
```

`\cites@oo`

```
1406 \def\cites@oo#1#2{\ifempty{\#2}{\cites@a{}{\#1}}{\cites@a{*{\#2}}{\#1}}{}}
```

```

\cites@a
1407 \def\cites@a#1#2{%
1408   \begingroup
1409     \toks@\{\endgroup \cites@b{#1}\}%
1410     \vdef\@tempa{#2}%
1411     \edef\@tempa{%
1412       \the\toks@ \ifx\@tempa\empty\else\@firstofone{\@xp\zap@space\@tempa}\fi\empty
1413     }%
1414     \empty, \empty
1415     \edef\@tempa{\endgroup\@nx\citelist{\the\toks@}}%
1416     \empty
1417 }

\cites@b
1418 \def\cites@b#1#2,#3{%
1419   \begingroup
1420     \toks@\{\InnerCite{#2}{#1}\}%
1421     \ifx\@empty#3\empty\@gobble\fi
1422     \cites@c#3%
1423 }

\cites@c
1424 \def\cites@c#1,#2{%
1425   \add@toks@\{\InnerCite{#1}\}%
1426   \ifx\@empty#2\empty\@gobble\fi
1427   \cites@c#2%
1428 }

```

\citeleft These variables are named to follow the precedent set by Arseneau's `cite` package. **\citeright** `\citemid` is used to separate a citation label from additional information such as "Theorem 4.9". **\citepunct** is used to separate multiple cites, unless one **\citepunct** of the cites has additional associated information, in which case `\CiteAltPunct` is used.

```

1429 \def\citeleft{[}
1430 \def\citeright{]}
1431 \def\citemid{,\penalty9999 \space}
1432 \def\citepunct{,\penalty9999 \hskip.13em plus.1em minus.05em\relax}

```

\citeAltPunct When a citation list contains one or more citations with optional arguments, we replace `\citemid` by `\CiteAltPunct`.

```
1433 \def\citeAltPunct{;\ }
```

\citeform This is used for formatting the citation label. It can be used, for example, to bolden the labels (as in `amsbook` and `amsproc`) or to do more elaborate things such as convert the numbers to roman numerals. By default, it's just a no-op.

Note that currently there is no corresponding macro for changing the formatting of `\cite`'s optional argument. This is probably a bug.

```
1434 \providecommand{\citeform}{\@firstofone}
```

\@citelist The `\@citelist` indirection turns out to be helpful in implementing the `\ocites` command for the `author-year` option.

```
1435 \DeclareRobustCommand{\@citelist}{\@citelist}
```

\@citelist

```
1436 \def\@citelist#1{%
1437   \leavevmode
1438   \begingroup
1439     \citetestyle
1440     \citemleft\nopunct % suppress first \citepunct
1441     \citem@begingroup
1442       \in@\*{#1}%
1443       \ifin@
1444         \let\citepunct\citeAltPunct
1445       \fi
1446       \let\citem@endgroup\@empty
1447       \cites@init
1448       \def\citemleft{\@addpunct{\citepunct}}%
1449       \let\citemright\ignorespaces
1450       \def\citem{\InnerCite}%
1451       \process@citelist{#1}%
1452     \endgroup
1453     \citemright
1454   \endgroup
1455 }
```

\citetestyle Reset the font to an upright, medium font (e.g. `cmr`), per AMS style. Also set `\mathsurround = 0pt` just in case there are subscripts in the cite numbers (from `\etalchar`, for example).

```
1456 \providecommand{\citetestyle}{\math@th\upshape\mdseries}
```

\citem@begingroup Grouping that encloses an entire cite block (a single cite or a list of cites).

```
1457 \def\citem@begingroup{\begingroup\let\citem@begingroup\relax}
```

\citem@endgroup

```
1458 \let\citem@endgroup\endgroup
```

\cites@init This needs to be called at the beginning of a list of cites to reset a few things.

```
1459 \def\cites@init{%
1460   \gdef\prev@names{??}%
1461   \let\cites@init\@empty
1462 }
```

\InnerCite

```
1463 \newcommand{\InnerCite}[1]{\star@{\citem@a\citesel{#1}}{}}
```

\citem@a The job of `\citem@a` is to convert the cite key to all catcode-12 characters and remove any spaces it might contain before passing it on to `\citem@b`.

Arguments:

```

#1 <- \CITESEL.
#2 <- citekey.

1464 \def\cite@a#1#2{%
1465   \BackCite{#2}%
1466   \cite@begingroup
1467   \cites@init
1468   \let\citesel#1\relax
1469   \ifx\citesel\citesel@author
1470     \let\citeleft\@empty
1471     \let\citeright\@empty
1472   \fi
1473   \begingroup
1474     \toks@\{\endgroup \cite@b}%
1475     \vdef\@tempa{#2}%
1476     \edef\@tempa{%
1477       \the\toks@\{@firstofone{\@xp\zap@space\@tempa} \@empty}%
1478     }%
1479   \tempa
1480 }

```

\cite@b *Arguments:*

```

#1 <- citekey.
#2 <- star-optional-arg.

1481 \def\cite@b#1#2{%
1482   \@xp\cite@bc\csname b@#1\@xp\endcsname {#1}{#2}%
1483 }

```

\cite@bc If it's uninitialized, plug in an empty cite structure. \cite@bc should be executed only once for a given instance of a cite key. All further processing should go through \cite@cj.

```

1484 \def\cite@bc#1#2{%
1485   \ifx#1\@undefined \global\let#1\relax \fi
1486   \ifx#1\relax \global\let#1\empty@cite \fi
1487   \xp\cite@nobib@test#1{}{}{}{}@nil#1%
1488   \cite@cj#1%
1489 }

```

\empty@cite

```
1490 \def\empty@cite{\citesel 00{}{}{}}
```

\cite@nobib@test If arg 4 is empty, it means there wasn't any \bib command that defined a valid label.

Arguments:

```

#1 <- \citesel.
#2 <- cited?.
#3 <- used?.

```

```

#4 <- label.
#5 <- backrefs.
#6 <- \b@citekey.

1491 \def\cite@nobib@test#1#2#3#4#5\@nil#6{%
1492     \@ifempty{#4}{%
1493         \G@refundefinedtrue
1494         \UndefinedCiteWarning#6%
1495         \xdef#6{\@nx\citesel #2#3{%
1496             \@nx\CitePrintUndefined{\extr@cite#6}{}{}}%
1497     }{%
1498 }

```

\UndefinedCiteWarning This is a copy of the standard warning from \@citex.

```

1499 \def\UndefinedCiteWarning#1{%
1500     \@latex@warning{%
1501         Citation ‘\extr@cite#1’ on page \thepage\space undefined}%
1502 }

```

\CitePrintUndefined

```

1503 \DeclareRobustCommand{\CitePrintUndefined}[1]{%
1504     \begingroup\fontshape{n}\fontseries{mddefault}\ttfamily ?#1\endgroup
1505 }

```

\CPU@normal This has to be a \let, not a \def.

```
1506 \let\CPU@normal\CitePrintUndefined
```

\cite@cj Arguments:

```

#1 <- \b@citekey.
#2 <- star-optional-arg.

1507 \def\cite@cj#1#2{%
1508     \leavevmode
1509     \begingroup
1510         \cite@cb#1% write info to aux file
1511         \ar@SK@cite#1%
1512         \citeleft
1513         \ar@hyperlink{#1}%
1514         \ifnotempty{#2}{\citemid{#2}}%
1515         \citeright
1516     \endgroup
1517     \ignorespaces % ignore spaces inside \citetlist
1518     \cite@endgroup
1519 }

```

\@citeleft The following definition provides some indirection that helps to deal with author-year object cites.

```
1520 \def\@citeleft{\citeleft}
```

```

\cite@cb
1521 \def\cite@cb#1{%
1522   \if@filesw
1523     \immediate\write\auxout{\string\citation{\extr@cite#1}}%
1524   \fi
1525   Define \citesel to make \b@whatever update itself.
1526   \begingroup
1527     \let\citesel\citesel@update
1528     #1#1%
1529   \endgroup
1530 }

\extr@cite Extract citekey from \b@citekey.
1530 \def\extr@cite{\exp\gobblethree\string}

6.15.3 Fancier \cite commands

\cites A list of simple cites. Make it robust in case used inside a figure caption. (But
then also, by the way, listoffigures should provide special handling.)
1531 \DeclareRobustCommand{\cites}{\cites@a{}}

\citen This is just to keep the showkeys package from clobbering the wrong part of
our definition of \cite:
1532 \providecommand{\citen}{\ocite}

\ycite \cite gets redefined inside of \citelist, so we need to \def \ycite here
instead of just \letting everything to \cite.
1533 \def\ycite{\cite}

\ycites
1534 \let\ycites\cites

\ocite
1535 \let\ocite\ycite

\ocites
1536 \let\ocites\cites

\fullcite
1537 \let\fullcite\cite

\fulllocite
1538 \let\fulllocite\ocite

\citeauthor
1539 \let\citeauthor\ycite

\citeauthory
1540 \let\citeauthory\ycite

```

6.15.4 The \nocite command

```
\nocite
1541 \renewcommand{\nocite}[1]{\othercites{#1}}
```

\othercites

```
1542 \newcommand{\othercites}[1]{%
1543   \cite@begingroup
1544   \let\BackCite\@gobble
1545   \let\cite@endgroup\@empty
1546   \def\citelist{\othercitetlist}%
1547   \cites{#1}%
1548 }
```

\othercitetlist

```
1549 \newcommand{\othercitetlist}[1]{%
1550   \cite@begingroup
1551   \let\cite@endgroup\@empty
1552   \cites@init
1553   \let\citeleft\relax
1554   \let\citeright\ignorespaces
1555   \def\InnerCite{\OtherCite}%
1556   \def\cite@cj {\##1##2{%
1557     \begingroup
1558       \xp\citesel##1%
1559       \cite@cb ##1%
1560     \endgroup
1561   }}
```

If we detect \nocite{*}, we globally alias \selective@bibdef to \copy@bibdef so that all succeeding \bibselect commands act like \bibselect*.

```
1561   \xp\ifx\csname b@\endcsname ##1%
1562     \global\let\selective@bibdef\copy@bibdef
1563   \fi
1564   \ignorespaces
1565   \cite@endgroup
1566 }
1567 #1\relax
1568 \endgroup
1569 }
```

\OtherCite

```
1570 \def\OtherCite#1{\cite@a\citesel@other{#1}{}}}
```

\citesel@other

```
1571 \def\citesel@other#1#2#3#4#5#6{}
```

\b@* This provides a dummy definition to keep things like \nocite{*} from generating an error message.

```
1572 \namedef{b@*}{\citesel 11{*}{*}{*}}
```

6.15.5 Citation sorting

```
\process@citelist@sorted
1573 \def\process@citelist@sorted#1{%
1574   \ifx\citesel\citesel@number
1575     \cite@sorted@s #1\cite@sorted@e
1576   \else
1577     \NonNumericCiteWarning
1578     \process@citelist@unsorted{#1}%
1579   \fi
1580 }

\NonNumericCiteWarning
1581 \def\NonNumericCiteWarning{%
1582   \amsrefs@warning{%
1583     Unable to confirm that cite keys are numeric: not sorting%
1584   }%
1585 }

\process@citelist@unsorted
1586 \def\process@citelist@unsorted#1{%
1587   \ignorespaces#1\relax
1588 }

\process@citelist By default, citation lists will be sorted.
1589 \let\process@citelist\process@citelist@sorted

\CPU@sort By defining this as TeX's maxint, undefined cites migrate to the end of a sorted
list.
1590 \def\CPU@sort#1{2147483647}

\cite@sorted@s Here's where we prepare to sort the citations and (optionally) compress ranges.
1591 \def\cite@sorted@s{%
1592   \begingroup
1593     \let\citePrintUndefined\CPU@sort
1594     \let\cite@cj\cite@cj
1595     \let\cite@cj\cite@compress
1596     \begingroup
1597       \toks@\emptytoks
1598       \let\cite@cj\cite@sort
1599       \ignorespaces
1600 }

\cite@sorted@e
1601 \def\cite@sorted@e{%
1602   \xp\endgroup
1603   \the\toks@
1604   \cite@dash
1605   \prev@cite
1606   \endgroup
1607 }
```

\cite@sort This is essentially an insertion sort. I think.

Arguments:

#1 <- \b@citekey.
#2 <- optional arg.

```
1608 \def\cite@sort#1#2{%
1609   \safe@set\@tempcnta#1% highest number so far
1610   \toks@\{\cite@cj#1{#2}\}%
1611   \temptokena\toks@
1612   \let\cite@cj\cite@sort@a
1613   \ignorespaces
1614 }
```

\cite@sort@a

```
1615 \def\cite@sort@a#1#2{%
1616   \safe@set\@tempcntb#1%
1617   \ifnum\@tempcntb > \@tempcnta
1618     \add@toks@\{\cite@cj#1{#2}\}%
1619     \@tempcnta\@tempcntb
1620   \else
1621     \let\cite@cj\cite@sort@b
1622     \toks@\emptytoks
1623     \def\@tempb{\add@toks@\{\cite@cj#1{#2}\}}%
1624     \the\temptokena
1625     \@tempb
1626     \let\cite@cj\cite@sort@a
1627   \fi
1628   \temptokena\toks@
1629   \ignorespaces
1630 }
```

\cite@sort@b

```
1631 \def\cite@sort@b#1#2{%
1632   \safe@set\count@#1%
1633   \ifnum\@tempcntb < \count@
1634     \@tempb
1635     \let\@tempb\empty
1636   \fi
1637   \add@toks@\{\cite@cj#1{#2}\}%
1638   \ignorespaces
1639 }
```

6.15.6 Range compression

When the time comes to apply compression, we have at our disposal a list of internal cite calls that looks like this:

\cite@cj\b@aaa{opta}\cite@cj\b@bbb{optb}...\cite@cj\b@zzz{optz}

where

\b@aaa < \b@bbb < ... < \b@zzz

and the `opt` arguments are possibly null. To print the citations while collapsing sequences of 3 or more contiguous numbers into ranges of the form $n-m$, we bind `\cite@cj` to a suitably clever function and then execute the list. In the absence of optional arguments, here's the algorithm:

Begin. Enter state 0. This is done by `\cite@sorted@s`.
 State 0. The current citation is the beginning of a range (possibly a singleton range). Print it. Then, set $prevnum := number$ and enter state 1.

State 1. The current citation might be the second element of a range.

Case a) $number = prevnum + 1$. Then the current item is definitely the second element of a range. It might be the last element of the range, but we won't know until we examine the following citation. So, save the current citation in `\prev@cite`, set $prevnum := number$, and go to state 2.

Case b) $number \neq prevnum + 1$. The current citation is the beginning of a new range. Print it, set $prevnum := number$ and remain in state 1. (This is essentially identical to stage 0.)

State 2. The current citation might be the third (or later) element of a range.

Case a) $number = prevnum + 1$. The current element is definitely part of a range. It might be the last element of the range, but again we won't know until we examine the following citation. Save the current citation in `\prev@cite` and set $prevnum := number$. Remain in state 2.

Case b) $number \neq prevnum + 1$. The previous citation was the end of a range and the current citation is the beginning of a new range. Print a dash followed by `\prev@cite`, then set $prevnum := number$ and enter state 1.

End. If `\prev@cite` is not empty, print it, preceded by a dash if we were in the middle of a range. (This is done by `\cite@sorted@e`.)

The presence of optional arguments complicates things somewhat, since a citation with an optional argument should never participate in range compression. In other words, when we come across an optional argument, we should finish off the preceding range, print the current citation, and then return to the initial state. More precisely, here are the actions taken in each state when there is an optional argument:

- State 0. Print the current citation and remain in state 0.
- State 1. Print the current citation and return to state 0.
- State 2. Print a dash followed by `\prev@cite`. Then print the current citation and return to state 0.

```
\prev@cite
1640 \let\prev@cite\@empty
```

\prev@cite@cb There's one further complication: Even though we're suppressing some of the citation numbers, we need to make sure that each citation is recorded in the .aux file. So, in case 2a, before we overwrite \prev@cite, we first invoke \prev@cite@cb to record the previous citation (if any).

```

1641 \def\prev@cite@cb{%
1642   \ifx\@prev@cite\@empty
1643   \else
1644     \begingroup
1645       \def\cite@print##1##2{%
1646         \cite@cb##1%
1647       }%
1648       \prev@cite
1649     \endgroup
1650   \fi
1651 }

\cite@print
1652 \def\cite@print#1#2{%
1653   \begingroup
1654     \let\@CitePrintUndefined\@CPU@normal
1655     \cite@cjs#1{#2}%
1656   \endgroup
1657 }

```

\cite@dash Ok, I lied. There was more than one further complication. Suppose that when we hit the end of the list, we're in state 2. We need to know whether to output a dash or a comma. (For example, both the sequences [2, 3] and [1, 2, 3] will end in state 2 with *prevcite* = 3, but in the former case we want a comma before the 3 and in the latter case we want a dash.) So, rather than printing the dash explicitly, we use \cite@dash to keep track of whether a dash is needed.

```
1658 \let\cite@dash\@empty
```

\print@one@dash

```

1659 \def\print@one@dash{%
1660   \textendash\ @opunct
1661   \let\cite@dash\@empty
1662 }

```

State 0, 1 and 2 each correspond to a different binding for \cite@cj. Here they are. The role of *prevnum* is played by \tempcnta, with \tempcntb assisting as *number* at times.

\cite@compress State 0:

```

1663 \def\cite@compress#1#2{%
1664   \cite@print#1{#2}%
1665   \ifempty{#2}{%
1666     \safe@set\tempcnta#1%
1667     \let\cite@cj\cite@compress@a

```

```

1668      }{%
1669 }

\cite@compress@a State 1:
1670 \def\cite@compress@a#1#2{%
1671   \@ifempty{#2}{%
1672     \advance\tempcnta\@ne
1673     \safe@set\tempcntb#1%
1674     \ifnum\tempcnta=\tempcntb
1675       \def\prev@cite{\cite@print#1{}}
1676       \let\cite@cj\cite@compress@b
1677     \else
1678       \cite@print#1{}%
1679       \tempcnta\tempcntb
1680     \fi
1681   }{%
1682     \cite@print#1{#2}%
1683     \let\cite@cj\cite@compress
1684   }%
1685 }

```

\cite@compress@b State 2:

```

1686 \def\cite@compress@b#1#2{%
1687   \ifempty{#2}{%
1688     \advance\tempcnta\@ne
1689     \safe@set\tempcntb#1%
1690     \ifnum\tempcnta=\tempcntb
1691       \let\cite@dash\print@one@dash
1692       \prev@cite@cb
1693       \def\prev@cite{\cite@print#1{}}
1694     \else
1695       \cite@dash
1696       \prev@cite
1697       \let\prev@cite\empty
1698       \cite@print#1{}%
1699       \tempcnta\tempcntb
1700       \let\cite@cj\cite@compress@a
1701     \fi
1702   }{%
1703     \cite@dash
1704     \prev@cite
1705     \let\prev@cite\empty
1706     \cite@print#1{#2}%
1707     \let\cite@cj\cite@compress
1708   }%
1709 }

```

6.15.7 Munging the .aux file

\amsrefs@bibcite When processing the .aux file at begin-document, this is what \bibcite will do:

```
1710 \def\amsrefs@bibcite#1{\@xp\bibcite@a\csname b@\#1\endcsname}
```

However, `hyperref` also redefines `\bibcite`, so to avoid conflicts and also ensure that it doesn't matter whether `amsrefs` or `hyperref` is loaded first, rather than redefining `\bibcite` directly, we redefine it inside the `.aux` file.

```
1711 \AtBeginDocument{%
1712   \if@filesw
1713     \immediate\write\auxout{%
1714       \string\@ifundefined{amsrefs@bibcite}{}{%
1715         \string\let\string\bibcite\string\amsrefs@bibcite
1716       }%
1717     }%
1718   \fi
1719 }
```

For good measure, we'll redefine it here as well, even though it really shouldn't matter any longer.

```
1719   \let\bibcite\amsrefs@bibcite
1720 }
```

`\bibcite@a` Arguments:

```
#1 <- \b@citekey.
#2 <- {label}{} or {author}{year}.
```

```
1721 \def\bibcite@a#1#2{%
```

Most of the time arg 1 will already be defined, by an earlier `\citedest` command in the `.aux` file. Then we just need to change the number.

```
1722 \ifx\relax#1%
1723   \gdef#1{\citesel 00#2{}}
1724 \else
1725   \begingroup
1726     \@xp\bibcite@b\@xp#1#1{#2}%
1727   \endgroup
1728 \fi
1729 }
```

`\bibcite@b` Arguments:

```
#1 <- \b@citekey.
#2 <- \citesel.
#3 <- cited?.
#4 <- used?.
#5 <- label.
#6 <- year.
#7 <- backrefs.
#8 <- {newlabel}{newyear}.
```

```
1730 \def\bibcite@b#1#2#3#4#5#6#7#8{\gdef#1{\citesel#3#4#8{#7}}}
```

\citedest The \citedest command goes into the .aux file to provide back-reference support.

```
1731 \newcommand{\citedest}[1]{\@xp\cite@dest\csname b@\#1\endcsname}
```

\cite@dest

```
1732 \def\cite@dest#1{%
1733   \ifx\relax#1%
1734     \gdef#1{\citesel 00{}{}{}{}%}
1735   \fi
1736   \xp\cite@dest@b\xp#1#1%
1737 }
```

\cite@dest@b *Arguments:*

```
#1 <- \b@citekey.
#2 <- \citesel.
#3 <- cited?.
#4 <- used?.
#5 <- label.
#6 <- year.
#7 <- backrefs.
#8 <- {more backrefs}.

1738 \def\cite@dest@b#1#2#3#4#5#6#7#8{%
1739   \isempty{#7}{%
1740     \def#1{\citesel #3#4{#5}{#6}{#8}}%
1741   }{%
1742     \gdef#1{\citesel #3#4{#5}{#6}{#7}{#8}}%
1743   }%
1744 }
```

6.15.8 Back references

```
\ifBR@verbose
```

```
1745 \ifundefined{ifBR@verbose}{\let\ifBR@verbose\iffalse \let\fi\fi}{}
```

\BackCite

```
1746 \let\BackCite\gobble
```

\back@cite

```
1747 \def\back@cite#1{%
1748   \ifBR@verbose
1749     \PackageInfo{backref}{back cite \string '\extr@cite#1'}%
1750   \fi
1751   \Hy@backout{#1}%
1752 }
```

\print@backrefs In an AMS-style bibliography, the backref info might follow the final period of the reference, or it might follow some *Mathematical Reviews* info, without a period.

```

1753 \def\print@backrefs#1{%
1754   \space\SentenceSpace$\uparrow\csname br@\#1\endcsname
1755 }

\PprintBackRefs
1756 \let\PprintBackRefs\gobble

6.15.9 hyperref, showkeys and shaderef support

\shade@cite
1757 \newcommand{\shade@cite}{\printref}

\format@cite
1758 \def\format@cite#1{\shade@cite{\citeform{#1}}}

\ar@hyperlink
1759 \def\ar@hyperlink#1{%
1760   \hyper@@link[cite]{}{\cite.\extr@cite#1}{\format@cite{#1}}%
1761 }

\ar@SK@cite
1762 \def\ar@SK@cite#1{@bsphack\xp\SK@\xp\SK@@ref\xp{\extr@cite#1}\esphack}

      Turn off hyperref and showkeys support if those packages don't appear to
      be loaded.

1763 \AtBeginDocument{%
1764   @ifpackageloaded{shaderef}{}{%
1765     \let\shade@cite\@firstofone
1766   }%
1767   @ifpackageloaded{hyperref}{}{%
1768     \def\ar@hyperlink{\format@cite}%
1769     \let\hyper@anchorstart\gobble
1770     \let\hyper@anchorend\relax
1771     \let\Hy@raisedlink\@firstofone
1772   }%
1773   @ifpackageloaded{showkeys}{}{%
1774     @ifpackagewith{showkeys}{notcite}{%
1775       \let\ar@SK@cite\gobble
1776     }{%
1777     }%
1778     \let\ar@SK@cite\gobble
1779     \let\SK@@label\gobble
1780     \let\SK@\gobbletwo
1781   }%
1782 }

```

6.16 Lexical structure of names

Before we can begin parsing names, we need to give some thought to the lexical structure of names. For the remainder of this document, when we refer to a “name” and especially when we speak of a name as a macro argument, we assume that the only tokens contained in the name are

- letters and punctuation (i.e., characters with catcode 11 or 12),
- ties (the token \sim_{13}),
- accent commands, such as \^n or \k ,
- text symbol macros, such as \i , \ae or \cprime ,
- grouping characters (braces).

In addition to their normal function of delimiting macro arguments, braces inside names have the following special functions:

1. They are used to indicate that multiple characters should be considered a single “compound” character when extracting initials. For example, `Yuri` becomes `Y.`, but `{Yu}ri` becomes `Yu`.
An important aspect of this use of braces is that it only applies to the first characters of a given name. As we’ll see below, this has important implications for our parsing code, which must preserve braces at the beginning of given names, but can be more cavalier with braces in other positions.
2. Spaces and commas are ordinarily interpreted as name separators, rather than name components. Similarly, periods and hyphens usually have a special interpretation. All these characters can be stripped of their special meanings by putting them within braces.

In practice, it might be possible to insert other tokens (such as macros) into names as long as they either (a) are non-expandable or (b) expand into a series of tokens of the above enumerated types. However, in such cases it will probably be safer to declare the macro in question as either a text accent or a text symbol.

6.16.1 Text accents

Syntactically, a text accent is a macro that takes a single, undelimited argument, i.e., it has a “prototype” of `macro:#1->`. Semantically, the implication is that it takes a letter (the *base*) as an argument and produces a glyph that for certain purposes can be considered equivalent to the base (see the discussion of stem comparison on page 86).³

`\amsrefs@textaccents` This will contain a list of accent commands in standard L^AT_EX format (i.e., separated by the token `\do`). For example, after registering the `\^n` and `\'` accents, it will contain

```
\do \^n\do \'
```

```
1783 \let\amsrefs@textaccents\empty
```

³Note that this is meant to be a pragmatic definition for the purposes of this package. No claim is made to greater generality.

```
\DeclareNameAccent  Arguments:
#1 <- accent.

1784 \def\DeclareNameAccent{%
1785   \clappend\amsrefs@textaccents
1786 }
```

Here are all the standard L^AT_EX accents, as well as a few nonstandard accents from the `mathscinet` package.

```
1787 \DeclareNameAccent"
1788 \DeclareNameAccent'
1789 \DeclareNameAccent".
1790 \DeclareNameAccent|=
1791 \DeclareNameAccent^
1792 \DeclareNameAccent`^
1793 \DeclareNameAccent`~%
1794 \DeclareNameAccent\b
1795 \DeclareNameAccent\c
1796 \DeclareNameAccent\d
1797 \DeclareNameAccent\H
1798 \DeclareNameAccent\k
1799 \DeclareNameAccent\r
1800 \DeclareNameAccent\t
1801 \DeclareNameAccent\u
1802 \DeclareNameAccent\v
```

From `mathscinet`:

```
1803 \DeclareNameAccent\utilde
1804 \DeclareNameAccent\uarc
1805 \DeclareNameAccent\dudot
1806 \DeclareNameAccent\lfhook
1807 \DeclareNameAccent\udot
1808 \DeclareNameAccent\polhk
1809 \DeclareNameAccent\soft
```

`\etalchar` and `\etaltext` are sort of accent-like if you look at them in the right light.

```
1810 \DeclareNameAccent\etalchar
1811 \% \DeclareNameAccent\etaltext
```

6.16.2 Text symbols

Syntactically, a text symbol is a macro with an empty parameter text, i.e., a prototype of `macro:->`. Semantically, it's a letter-like glyph that should not be considered equivalent to any other glyph or group of glyphs. In addition, it may exist in both upper- and lowercase variants, unlike text accents, where we consider the case to be an attribute of the base letter, not of the accent.⁴

`\amsrefs@textsymbols` This is analogous to `\amsrefs@textaccents` but a little more complicated due to the need to store lowercase equivalents. It consists of a list of double entries of the form

⁴As with text accents, this is not intended as a fully general definition.

```
\do \symbol \do \lcsymbol
```

which means that `\symbol` is a text symbol whose corresponding lowercase version is `\lcsymbol`. (Note that nothing is implied about whether `\symbol` is to be considered as uppercase or lowercase.) For example, in

```
\do \ae \do \ae \do \OE \do \oe
```

the first four tokens indicate that `\ae` is a text symbol with lowercase equivalent `\ae`, while the last four tokens indicate that `\OE` is a text symbol with lowercase equivalent `\oe`. This scheme is somewhat redundant, but pleasingly simple.

This also duplicates some of the information in `\@uclclist`, but it seems safer to do this than to modify `\@uclclist`.

```
1812 \let\amsrefs@textsymbols@\empty
```

`\DeclareNameSymbol` *Arguments:*

```
#1 <- symbol.
#2 <- lowercase.

1813 \def\DeclareNameSymbol#1#2{%
1814   \@append\amsrefs@textsymbols#1%
1815   \@append\amsrefs@textsymbols#2%
1816   \ifx#1#2\else
1817     \@append\amsrefs@textsymbols#2%
1818     \@append\amsrefs@textsymbols#2%
1819   \fi
1820 }
```

Here are the standard L^AT_EX and `mathscinet` text symbols.

Note that `\i` and `\j` are anomalous in being syntactically like text symbols, but semantically more like text accents.

```
1821 \DeclareNameSymbol\i\i
1822 \DeclareNameSymbol\j\j
1823 \DeclareNameSymbol\AE\ae
1824 \DeclareNameSymbol\OE\oe
1825 \DeclareNameSymbol\O\o
1826 \DeclareNameSymbol\DH\dh
1827 \DeclareNameSymbol\DJ\dj
1828 \DeclareNameSymbol\L\l
1829 \DeclareNameSymbol\NG\ng
1830 \DeclareNameSymbol\SS\ss
1831 \DeclareNameSymbol\TH\th
```

From `mathscinet`:

```
1832 \DeclareNameSymbol\bar\bar
1833 \DeclareNameSymbol\lasp\lasp
1834 \DeclareNameSymbol\rasp\rasp
1835 \DeclareNameSymbol\cprime\cprime
1836 \DeclareNameSymbol\cdprime\cdprime
1837 \DeclareNameSymbol\bud\bud
1838 \DeclareNameSymbol\cydot\cydot
```

\sim can be considered a text symbol in much the same way that `\etalchar` can be considered an accent.

```
1839 \DeclareNameSymbol{\sim}{%
```

6.16.3 `\edef-like macros for names`

The following macros all behave sort of like `\edef`, in the sense that

```
\X@edef\foo{name}
```

defines `\foo` to be the result of expanding `name` and applying a certain transformation to it.

`\normalize@edef` This converts accents in the name to a normalized form where the accent and its argument are surrounded by braces. E.g., after

```
\normalize@edef\cs{P\olya}
```

`\cs` will contain `P{\o}lyा`. (This might result in a redundant layer of braces if the original text contained, say, “`P{\o}lyा`”, but that’s ok.) This lets us extract the first n characters from a name by using TeX’s macro argument-gobbling mechanism without worrying that an accent will be separated from its base letter. As a bonus, it also replaces ties (\sim) by spaces.

```
1840 \def\normalize@edef#1#2{%
1841   \begingroup
1842     \apply\auto\protect\amsrefs{textsymbols}
1843     \apply\wrap\accent\amsrefs{textaccents}
```

Redefine `\tabacckludge` in case someone wants to use this with the `inputenc` package.

```
1844   \let\@tabacckludge\use@accent
1845   \let~\space
1846   \edef\@tempa{\def\@nx#1{#2}}%
1847   \exp\endgroup
1848   \@tempa
1849 }
```

`\use@accent` This is identical to `\nameuse` except for the addition of the `\string`, which, as per `ltoutenc.dtx`, guards against the eventuality that something like `'` might be active at the point of use. We don’t expect to find a `\bib` in the middle of a `tabbing` environment (do we?) so we

```
1850 \def\use@accent#1{\csname\string#1\endcsname}
```

`\wrap@accent` Here’s a wrapper macro that causes an accent to become auto-wrapping. E.g., after `\wrap@accent\'`, `\o` will expand to `{\o}`.

```
1851 \def\wrap@accent#1{%
1852   \def#1##1{\{\@nx#1##1\}}%
1853 }
```

`\lc@edef` This converts all the characters in a name to all lowercase, using the mapping defined by `\amsrefs{textsymbols}`. So, after

```
\lc@edef\cs{P\olya}
```

\cs will contain p\olya. Note that accents are not wrapped and ties are passed through unmolested.

```

1854 \def\lc@edef#1#2{%
1855   \begingroup
1856     \let\@tabacckludge\use@accent %%??
1857     \@apply\auto@protect\amsrefs@textaccents
1858     \@apply\lc@do\amsrefs@textsymbols
1859     \edef\@tempa{\lowercase{\def\@nx#1{#2}}}%  

1860   \exp\endgroup
1861   \@tempa
1862 }
```

\lc@do This is a slightly more complicated wrapper macro than previous ones. The first argument is a text symbol; the second argument is the lowercase variant of the symbol. If they're the same (i.e., the first argument is a lowercase text symbol), we \auto@protect it. Otherwise we define the first symbol to expand to the second.

```

1863 \def\lc@do#1#2{%
1864   \ifx#1#2%
1865     \auto@protect#1%
1866   \else
1867     \def#1{#2}%
1868   \fi
1869 }
```

\purge@edef Removes accents and braces from a name and converts ties to spaces, leaving only letters, punctuation and text symbols. For example,

```
\lc@edef\cs{P{\o}lya}
```

will put Polya in \cs.

```

1870 \def\purge@edef#1#2{%
1871   \begingroup
1872     \@apply\auto@protect\amsrefs@textsymbols
1873     \let`\space
1874     \@apply\purge@accent\amsrefs@textaccents
1875     \let\@tabacckludge\gobble
```

As mentioned above (page 71), \i and \j are semantically like text accents; hence, they require special treatment here.

```

1876   \def\i{i}%
1877   \def\j{j}%
1878   \edef\@tempa{#2}%
1879   \toks@\emptytoks
1880   \exp\purge@edef@ \@tempa \nil
1881   \edef\@tempa{\def\@nx#1{\the\toks@}}%
1882   \exp\endgroup
1883   \@tempa
1884 }
```

\purge@edef@ Peek ahead so \purge@edef@a will know whether its argument was originally surrounded by braces.

```
1885 \def\purge@edef@{%
1886   \futurelet\@let@token
1887   \purge@edef@a
1888 }
```

\purge@edef@a Process a single “chunk” (i.e., one macro-argument’s worth) of the name.

```
1889 \def\purge@edef@a#1{%
```

If we’ve run into the \@nil terminator, we’re done.

```
1890   \ifx\@let@token\@nil
1891     \let\@tempa\empty
1892   \else
```

Otherwise, if the argument was originally surrounded by braces, process it recursively before processing the remainder of the token stream.

```
1893   \ifx\@let@token\bgroup
1894     \def\@tempa{%
1895       \purge@edef@ #1\@nil
1896       \purge@edef@
1897     }%
1898   \else
```

If the argument is a single unbracketed token, just copy it into the output.

```
1899   \add@toks@{#1}%
1900   \let\@tempa\purge@edef@
1901   \fi
1902 \fi
1903 \@tempa
1904 }
```

\purge@accent This is similar to \wrap@accent but it removes the accent command (and possibly a layer of braces surrounding the accent’s argument).

```
1905 \def\purge@accent#1{%
1906   \def#1##1##1%
1907 }
```

6.17 Name parsing

Parsing names is somewhat complicated because parts of the name can (in principle) be empty (G=given, S=surname, J=jr):

```
author={Doe, John, Jr.}: G={John} S={Doe} J={Jr.}
author={Doe, John}: G={John} S={Doe} J={}
author={Doe, , Jr.}: G={} S={Doe} J={Jr.}
author={Doe}: G={} S={Doe} J={}
author=, John, Jr.!: G={John} S={} J={Jr.}
author=, John!: G={John} S={} J={}
author=, , Jr.!: G={} S={} J={Jr.}
author=: G={} S={} J={}
```

Not all of these forms are legal, of course, but that's no excuse for not parsing them correctly.

We also want to be somewhat lenient about the placement of spaces:

```
author={ Doe, John, Jr.}: G={John} S={Doe} J={Jr.}
```

However, because one must have some standards, we assume there are no spaces in the following positions in the input:

1. before periods,
2. before commas,
3. at the end of the name,
4. before or after hyphens.

Thus, we make no attempt to compensate for the misplaced spaces in examples like these:

```
author={Doe , J ., Jr. }: G={J .} S={Doe } J={Jr. }
author={Doe, J. - M.}: G={J. - M.} S={Doe} J={}
```

Also, unless we are generating initials, we don't try to normalize spaces *after* periods:

```
author={Doe, J.M.}: G={J.M.} S={Doe} J={}
(not G={J. M.})
```

Finally, since we allow authors to group together characters that should be treated as a single unit, we need to be careful to preserve the author's markup in cases like these:

```
author={Doe, {Yu}ri}: G={{Yu}ri} S={Doe} J={}
author={Doe, {Yu}}: G={{Yu}} S={Doe} J={}
```

This is harder than it seems. For example, consider a naive implementation that uses delimited arguments to pull the name apart:

```
\def\parsename#1,#2\@nil{%
  \def\bib'surname{#1}%
  \def\bib'given{#2}%
}

\parsename Doe, {Yu}ri\@nil
```

Unfortunately, this results in the space after the comma becoming part of `\bib'given`: “ {Yu}ri”.

Our next thought would be to modify the definition slightly to trick TeX into gobbling the space:

```
\def\parsename#1,#2#3\@nil{%
  \def\bib'surname{#1}%
  \def\bib'given{#2#3}%
}

\parsename Doe, {Yu}ri\@nil
```

Now the space is gone, but—surprise!—so are the braces: “Yuri”. In addition, this approach makes it difficult to handle empty name parts correctly.

To sidestep these problems, instead of blindly gobbling macro arguments, we use `\futurelet` to look ahead at certain strategic moments so we can take the appropriate action (see `\get@namepart@d-f`). We only really care about preserving braces at the start of names (page 69), which simplifies things somewhat.

`\name@split` `\name@split` parses a name into its three parts and stores them in `\bib'surname`, `\bib'given` and `\bib'jr`. If the `initials` option is in force, it also extracts the initials from the given name and stores them in `\bib'initials`.

It expects the name to be parsed to be terminated by `\@nil` and to contain at least three commas. Thus the usual way to invoke it is

```
\name@split <name>, , \@nil
```

`\name@split` just uses `\get@namepart` to peal off the surname and then passes control to `\name@split@given`. (Note the spiffy continuation-passing programming style.)

```
1908 \def\name@split{%
1909   \get@namepart\bib'surname\name@split@given
1910 }
```

`\name@split@given` Pretty much the same, *mutatis mutandis...*

```
1911 \def\name@split@given{%
1912   \get@namepart\bib'given\name@split@jr
1913 }
```

`\name@split@jr` And again...

```
1914 \def\name@split@jr{%
1915   \get@namepart\bib'jr\name@split@finish
1916 }
```

`\name@split@finish` We have all three parts now. Do some consistency checking, extract the initials from the given name, and then call `\@nilgobble` to remove anything (such as extra commas) left on the stack.

```
1917 \def\name@split@finish{%
1918   \ifx\bib'surname\empty \EmptyNameWarning \fi
```

Theoretically, we could try to check for uninverted names here, but only at the risk of producing spurious warnings when the name really does only have one part (`author={Arvind}`).

A possible solution: Now that we have the `inverted` attribute, we could issue a warning if the given name is empty and the family name contains a space. I'm sure someone could find valid input that would still generate a spurious warning, but this would take care of the most common cases. This bears more thinking about.

```
1919 %%   \ifx\empty\bib'given
1920 %%     \NameCheck \bib'surname ??\@nil
1921 %%   \else
1922   \extract@initials\bib'given
```

```

1923 %%      \fi
1924   \@nilgobble
1925 }
```

- \get@namepart Now for the fun part. \get@namepart takes two arguments. The first (the destination) should be a control sequence; the second (the continuation) will normally also be a control sequence, though technically we only require that it be a single token. \get@namepart scans everything up to the next level-0 comma, places it in the destination, and then calls the continuation.

```
1926 \def\get@namepart#1#2{%
```

Save the destination in \toks@ and the continuation in \temptokena. It's unfortunate that this trashes the previous contents of those token lists (as well as the contents of \tempa later on), but preliminary attempts to rewrite the code to leave the calling environment unchanged were not encouraging.

```

1927   \toks@{\#1}%
1928   \temptokena{\#2}%
1929   \get@namepart@a
1930 }
```

- \get@namepart@a Now peek ahead at the next token in the stream and call \get@namepart@b to examine it.

```

1931 \def\get@namepart@a{%
1932   \futurelet\@let@token
1933   \get@namepart@b
1934 }
```

- \get@namepart@b If the next token is a space token, we want to delete it. Otherwise we're ready to read the name.

```

1935 \def\get@namepart@b{%
1936   \ifx\@let@token\@spoken
1937     \xp\get@namepart@c
1938   \else
1939     \xp\get@namepart@d
1940   \fi
1941 }
```

- \get@namepart@c The next token is a space; we delete it and restart \get@namepart@a, in case there are multiple spaces.

```

1942 \def\get@namepart@c{%
1943   \after@deleting@token\get@namepart@a
1944 }
```

- \get@namepart@d We're at the beginning of the name part. However, there are still two special cases we have to watch out for. First, the next token might be a comma, meaning that this name part is empty. Second, the next token might be an open brace ({), which we have to be sure to copy into the destination. So, we peek ahead again before proceeding.

```

1945 \def\get@namepart@d{%
1946   \futurelet\@let@token
1947   \get@namepart@e
1948 }

```

\get@namepart@e If the next token is a comma, it means the name part is empty; so, we set the destination to an empty list and then arrange to execute the continuation after deleting the comma. Otherwise we call \get@namepart@f to read a non-empty name, leaving \@let@token undisturbed so that \get@namepart@f knows what's coming up.

```

1949 \def\get@namepart@ef{%
1950   \ifx\@let@token,%
1951     \xp\let\the\toks@\empty
1952     \edef\@tempa{%
1953       \nx\after@deleting@token\the\@temptokena
1954     }%
1955     \xp\@tempa
1956   \else
1957     \xp\get@namepart@f
1958   \fi
1959 }

```

\get@namepart@f We know whether or not the name begins with a brace, but we don't know if the corresponding group contains the entire name or only part of it. By reading the name as two arguments, we can handle all cases correctly.⁵

Note that the arguments are not expanded.

```

1960 \def\get@namepart@f#1#2,{%
1961   \ifx\@let@token\bgroup
1962     \xp\def\the\toks@{\{#1}#2}%
1963   \else
1964     \xp\def\the\toks@{#1#2}%
1965   \fi
1966   \the\@temptokena
1967 }

```

\EmptyNameWarning Or translator or contributor or...

```
1968 \def\EmptyNameWarning{\amsrefs@warning{Empty contributor name}}
```

6.18 Extracting initials

Extracting initials from the author's given name is tricky because of the numerous special cases that need to be handled. Consider the following examples, some of which are admittedly contrived:

```

author={Arvind}: I={}
author={Bing, R H}: I={R H}
author={Harish, \'Etienne}: I={\'E.}

```

⁵More or less. If the second argument is brace-delimited, the braces will be lost. But as mentioned above (page 76), we don't really care.

```

author={Harish, \'E.}: I={\'E.}
author={Harish, '\'{E}.}: I={\'E.}
author={Harish, {\\'E}.}: I={\'E.}
author={Harish, \'E}: I={\'E}
author={Harish, \'Etienne-P\^{\i}erre}: I={\'E.-P.}
author={Jones, David}: I={D.}
author={Jones, David-Michael}: I={D.-M.}
author={Katzenbach, Nicholas deBelleville}: I={N. deB.}
author={Katzenbach, Nicholas deB.}: I={N. deB.}
author={Matiyasevich, {Yu}ri}: I={Yu.}
author={Matiyasevich, {Yu}}: I={Yu}
author={Matiyasevich, Yu.}: I={Yu.}

```

When processing initials, we loosen our strictures on spaces inside the given name by not requiring spaces after periods and tolerating them around hyphens and after the name:

```

author={Jones, D.M.}: I={D. M.}
author={Jones, David - Michael}: I={D.-M.}
author={Jones, David , Jr.}: I={D.}

```

(Strictly speaking, only the support for the first of these examples was a deliberate design decision; the other two are side-effects of the implementation. In any case, toleration of these quirks is in no way an endorsement of them, especially since they may make it more difficult for third-party software to correctly process bibliography entries.)

6.18.1 The algorithm

As a running example, consider the following contrived input:

```
\'E.-P\^{\i}erre J.K. M
```

which we want to turn into “\'E.-P. J. K. M”.

We precede by stages.

1. Normalize the name by surrounding accents and their arguments by braces:

```
{\'E}.-P{\^{\i}}erre J.K. M
```

We also replace \sim s by spaces at this stage.

2. Replace each hyphen (-) by “ $_\backslash ini@\text{hyphen}_$ ”:

```
{\'E}. \backslash ini@\text{hyphen} P{\^{\i}}erre J.K. M
```

3. Add a space after each period:

```
{\'E}. \backslash ini@\text{hyphen} P{\^{\i}}erre J. K. M
```

4. Now we have the name as a list of space-separated components. (In our example, the components are “{\'E}.”, “\backslash ini@\text{hyphen}”, “P{\^{\i}}erre”, “J.”, “K.”, and “M”.) We loop through the components and replace each one by its “initialized” form. There are four cases:

- (a) The component ends in a period. Copy it and add the token \sim . (In our example, these are the components “{\'E}.”, “J.” and “K.”.)

- (b) The component consists of a single (possibly compound) character without a period. Again, copy it and add `~`. (In our example, this is the component “M”.)
- (c) The component is the token `\ini@hyphen`. Copy it.
- (d) The component consts of two or more (possibly compound) characters without a period (e.g., “P{\^i }erre”). Copy the first character and add the tokens `.~`.

5. The token list generated above will end with an unwanted `~`. Delete it.

The end result is

```
{\'E}.~\ini@hyphen P.~J.~K.~M
```

which, when typeset, does indeed produce “É.-P. J. K. M”.⁶

6.18.2 The implementation

`\extract@initials` This is pretty straightforward.

```
1969 \def\extract@initials#1{%
1970   \begingroup
1971     \auto@protect\ini@hyphen
1972     \auto@protect\nobreakspace
1973     \let`\relax
1974     \apply\auto@protect\amsrefs@textsymbols
1975     \apply\auto@protect\amsrefs@textaccents
1976     \normalize@edef\@tempa{#1}%
1977     \ifx\@tempa\empty
1978     \else
```

It would be nice if `\process@hyphens` and `\process@dots` commuted, and they almost do. However, suppose you have the (admittedly contrived) name `Yu.{-}{Yu}`, which should be turned into “Yu.-Yu”. If `\process@dots` is applied first, the braces around the second “Yu” get removed, so the output is “Yu.-Y.”. (Even worse would be `P.-\'E`, which would produce “P.-.”)

```
1979     \process@hyphens\@tempa
1980     \process@dots\@tempa
1981     \process@names\@tempa
1982     \chomp\@tempa{`}%
1983   \fi
1984   \edef\@tempa{\def\@nx\bib'initials{\@tempa}}%
1985 \exp\endgroup
1986 \@tempa
1987 }
```

`\ini@hyphen` The `\unskip` removes the space at the end of a potential (and probable) preceding `~`, but leaves the `\nobreak` penalty.

```
1988 \def\ini@hyphen{\unskip-\nobreak}
```

⁶Tying all the characters together is potentially undesirable when, as in the example, there are a large number of pieces in the given name.

\process@hyphens This follows the same general pattern as \get@namepart, but with an extra layer of grouping to avoid unwanted side-effects. Otherwise, it uses the same parsing techniques.

One difference is that there is no explicit continuation: instead, we iterate by repeatedly calling \process@one@hyphen@d until we run into the \cnil marker.

```
1989 \def\process@hyphens#1{%
1990   \begingroup
1991     \toks@\emptytoks
1992     \exp\process@one@hyphen #1-\cnil
1993     \edef\@tempa{\the\toks@}%
```

Because of the - we have to stick in as a delimiter above, \process@one@hyphen will always generate unwanted code at the end of the name. We now delete it. (This also has the necessary side-effect of expanding the \space macros into space characters.)

```
1994   @chomp\@tempa{ \ini@hyphen\space}%
1995   \edef\@tempa{\def\@nx#1{\@tempa}}%
1996   \exp\endgroup
1997   \@tempa
1998 }
```

\process@one@hyphen Cf. \get@namepart@a.

```
1999 \def\process@one@hyphen{%
2000   \futurelet\@let@token
2001   \process@one@hyphen@a
2002 }
```

\process@one@hyphen@a Cf. \get@namepart@b and \extract@initial@a.

The tests for \cnil and - here are purely to supply better error recovery. Without them, a hyphen at the end of the given name (.e.g, author={Doe, John-}) would produce a very mysterious error message. Since it's unlikely the hyphen really belongs there, we delete it, but we also issue a warning to the author. (It will still show up as part of the full given name, though.)

We borrow \fsa@n from rkeyval to keep track of the appropriate next action.

```
2003 \def\process@one@hyphen@a{%
2004   \ifx\@let@token\cnil
2005     \let\fsa@n\gobble
2006   \else
2007     \ifx\@let@token -%
2008       \TrailingHyphenWarning
2009       \let\fsa@n\process@one@hyphen@b
2010     \else
2011       \ifx\@let@token\@sptoken
2012         \let\fsa@n\process@one@hyphen@b
2013       \else
2014         \let\fsa@n\process@one@hyphen@c
```

```

2015          \fi
2016          \fi
2017      \fi
2018      \fsa@n
2019 }

\process@one@hyphen@b Cf. \get@namepart@c.
2020 \def\process@one@hyphen@b{%
2021     \after@deleting@token\process@one@hyphen
2022 }

\process@one@hyphen@c Cf. \get@namepart@f.
2023 \def\process@one@hyphen@c#1#2-{%
2024     \ifx\bgroup\@let@token
2025         \add@toks@{\#1#2 \ini@hyphen\space}%
2026     \else
2027         \add@toks@{\#1#2 \ini@hyphen\space}%
2028     \fi
2029     \futurelet\@let@token
2030     \process@one@hyphen@d
2031 }

```

\process@one@hyphen@d Here we just check for \nil and terminate if we detect it. Otherwise, we start over.

```

2032 \def\process@one@hyphen@d{%
2033     \ifx\@let@token\@nil
2034         \@xp\@gobble
2035     \else
2036         \@xp\process@one@hyphen
2037     \fi
2038 }

```

\TrailingHyphenWarning Or translator or contributor or...

```

2039 \def\TrailingHyphenWarning{%
2040     \amsrefs@warning{Trailing hyphen deleted from name}%
2041 }

```

\process@dots This is almost completely parallel to \process@hyphens.

```

2042 \def\process@dots#1{%
2043     \begingroup
2044     \toks@\emptytoks
2045     \@xp\process@one@dot #1.\@nil
2046     \edef\@tempa{\the\toks@}%
2047     \@chomp\@tempa{. }%

```

Since it's legitimate for names to end in periods, we might still have an unwanted space at the end of the name, so we delete it too.

```

2048     \@chomp\@tempa{ }%
2049     \edef\@tempa{\def\@nx#1{\@tempa}}%

```

```

2050      \@xp\endgroup
2051      \@tempa
2052 }

\process@one@dot
2053 \def\process@one@dot{%
2054   \futurelet\@let@token
2055   \process@one@dot@a
2056 }

\process@one@dot@a This is a bit different from \process@one@hyphen@a since we expect names
sometimes to end in a period—or even two periods—not least because of the .
we add as a delimiter when invoking \process@one@dot.
2057 \def\process@one@dot@a{%
2058   \ifx\@let@token .%
2059     \def\fsa@n{\after@deleting@token\process@bare@dot}%
2060   \else
2061     \ifx\@let@token\@sptoken
2062       \let\fsa@n\process@one@dot@b
2063     \else
2064       \let\fsa@n\process@one@dot@c
2065     \fi
2066   \fi
2067   \fsa@n
2068 }

\process@bare@dot
2069 \def\process@bare@dot{%
2070   \add@toks@{. }%
2071   \futurelet\@let@token
2072   \process@one@dot@d
2073 }

\process@one@dot@b
2074 \def\process@one@dot@b{%
2075   \after@deleting@token\process@one@dot
2076 }

\process@one@dot@c
2077 \def\process@one@dot@c#1#2.{%
2078   \ifx\bgroup\@let@token
2079     \add@toks@{\{#1\}#2. }%
2080   \else
2081     \add@toks@{\#1#2. }%
2082   \fi
2083   \futurelet\@let@token
2084   \process@one@dot@d
2085 }

```

```

\process@one@dot@d
2086 \def\process@one@dot@d{%
2087   \ifx\@let@token\@nil
2088     \exp\@gobble
2089   \else
2090     \exp\process@one@dot
2091   \fi
2092 }

```

\process@names This is very similar to \process@hyphens and \process@dots, but with a couple of twists, as noted below.

```

2093 \def\process@names#1{%
2094   \begingroup
2095     \toks@\emptytoks
2096     \exp\extract@initial #1 \@nil
2097     \edef\tempa{\def\@nx#1{\the\toks@}}%
2098   \exp\endgroup
2099   \tempa
2100 }

```

\extract@initial Scan through the token stream replacing words by their initials until we hit the terminating '11

```

2101 \def\extract@initial{%
2102   \futurelet\@let@token
2103   \extract@initial@a
2104 }

```

\extract@initial@a As with \process@one@hyphen@a, the test for '11 here is purely to provide better recovery, this time in case the given name has a trailing space (.e.g, author={Doe, John }). But since we're just deleting whitespace, we don't bother issuing a warning.

```

2105 \def\extract@initial@a{%
2106   \ifx\@let@token\@nil
2107     \let\fsa@n\@gobble
2108   \else
2109     \ifx\@let@token\sptoken
2110       \let\fsa@n\extract@initial@b
2111     \else
2112       \let\fsa@n\extract@initial@c
2113     \fi
2114   \fi
2115   \fsa@n
2116 }

```

```

\extract@initial@b
2117 \def\extract@initial@b{%
2118   \after@deleting@token\extract@initial
2119 }

```

\extract@initial@c Here, instead of just copying the name, we extract its initials and copy those.

```
2120 \def\extract@initial@c#1#2 {%
2121   \ifx\@let@token\bgroup
```

Note that we double-brace the first argument to avoid having to test \@let@token again inside \extract@initial.

```
2122   \extract@initial {{#1}}#2\@nil
2123 \else
2124   \extract@initial #1#2\@nil
2125 \fi
2126 \futurelet\@let@token
2127 \extract@initial@d
2128 }
```

\extract@initial@d

```
2129 \def\extract@initial@d{%
2130   \ifx\@let@token\@nil
2131     \xp\@gobble
2132   \else
2133     \xp\extract@initial
2134   \fi
2135 }
```

\@extract@initial This handles the four cases mentioned on page 79.

```
2136 \def\@extract@initial#1#2\@nil{%
2137   \ifx\ini@hyphen#1%
2138     \add@toks@\{\ini@hyphen}\%
2139   \else
2140     \in@{\.\@nil}{#1#2\@nil}\% Look for a period at the end of the name
2141     \ifin@
2142       \add@toks@\{#1#2~}\%
2143     \else
2144       \count@chars\@tempcnta{#1#2}\%
2145       \ifnum\@tempcnta > \one
2146         \add@toks@\{#1.~}\%
2147       \else
2148         \add@toks@\{#1~}\%
2149       \fi
2150     \fi
2151   \fi
2152 }
```

\count@chars This sets its first argument (which is assumed to be a count register) to the number of characters in the second argument. Compound characters are counted as a single character.

```
2153 \def\count@chars#1#2{%
2154   \begingroup
2155     \tempcnta\z@
2156     \count@chars#2\@nil
```

```

2157      \edef\@tempb{\#1=\the\@tempcnta\relax}%
2158      \exp\endgroup
2159      \@tempb
2160 }

\@count@chars
2161 \def\@count@chars#1{%
2162   \ifx #1\@nil
2163   \else
2164     \advance\@tempcnta\@ne
2165     \exp\@count@chars
2166   \fi
2167 }

```

6.19 Generating alphabetic labels

6.19.1 The algorithm

Like Gaul, an alphabetic label is divided into three parts.

1. The author part. In the simplest case, this is formed by extracting the first character of each word of each last name of each author. Thus, if there were two authors with last names “Vaughan Williams” and “Tallis”, the author part would be “VWT”.
 If there are more than four authors, only the first three names are used, and a superscript “+” is appended to represent the elided names. Similarly, if an author name is “others”, it is replaced by a superscript “+” and any following author names (of which there shouldn’t be any) are ignored.
 Finally, if there is only one author and the author’s last name consists of a single word, the first three characters of that name are used.
2. The year part. If the `y2k` option is in force, or if the year is less than 1901, the entire year is used. Otherwise the last two digits of the year are used.⁷
 The combination of author part and year part will be referred to as the *stem*.
3. The suffix. If two or more items have the same stems, a suffix consisting of a lowercase latin letter will be appended to each label to make it unique.

This third part is more subtle than it might first appear. First, case is ignored when comparing stems, so that, for example, “Ahl1999” and “AHL1999” are considered identical. Second, existing practice (in English, at least), is to ignore diacritics so that, for example, “Ahl1999” and “Ähl1999” are considered identical.

Note that when checking for duplicate stems, we assume that bibliography items appear sorted by label, which means that all items with the same stem will be adjacent. This means we can use the naive algorithm (check to see if the current item has the same stem as the previous item and, if so, append a suffix) to detect clashes. This sorting will be done automatically by `amsxport`, but the document author is responsible for ensuring the appropriate order if

⁷Years with more than 4 digits are not currently handled correctly. *Caveat lector.*

`amsxport` is not used. This is why it's an error to mix the `alphabetic` and `citation-order` options.

6.19.2 The implementation

```

2168 \let\previous@stem\empty
2169 \let\current@stem\empty
2170 \let\previous@year\empty
2171 \let\current@year\empty

\amsrefs@label@prefix
2172 \let\amsrefs@label@prefix\empty

\thebib
2173 \def\thebib{\amsrefs@label@prefix\arabic{c}@\bib}

\append@to@stem
2174 \def\append@to@stem{\global\concat\current@stem}

```

\generate@alphalabel

```
2175 \def\generate@alphalabel{%
```

If the user supplied an explicit `label` field, we use it. Otherwise, we generate our own.

```

2176   \ifx\bib'label\empty
2177     \begingroup

```

We begin by saving the previous stem and initializing the current stem to the empty string.

```

2178     \global\let\previous@stem\current@stem
2179     \global\let\current@stem\amsrefs@label@prefix

```

The list of primary contributors is available to us in `\current@primary` in the form

```
  \name{Last1,First1} \name{Last2,First2} ... \name{Lastn,Firstn}
```

We will be executing this list multiple times with various definitions of `\name`. So the first thing we want to do is establish a safe environment and normalize the names.

```

2180   \apply\auto@protect\amsrefs@textsymbols
2181   \apply\auto@protect\amsrefs@textaccents
2182   \auto@protect\name
2183   \auto@protect\etaltext
2184   \normalize@edef\@tempa\current@primary

```

Now we count the number of authors in the list and invoke the appropriate macro to calculate the author part of the reference label.

```

2185   \get@numberof\@tempcnta\name\@tempa
2186   \calc@author@part

```

Next append the year part.

```
2187   \append@label@year
```

At this point, the `\current@stem` is complete and we're ready to determine what (if any) suffix is needed to disambiguate it from the previous label.

```
2188           \calc@alpha@suffix
```

We have all the pieces now. Arrange to end the current group and then define `\bib@label` in the enclosing group. (This keeps `\bib@label` from being defined outside the group started by `\bib@start`. This isn't strictly necessary, but it provides a bit of compartmentalization.)

```
2189           \edef\@tempa{%
2190             \def\@nx\bib'label{%
2191               \current@stem
2192               \alpha@label@suffix
2193             }%
2194             }%
2195           \exp\endgroup
2196           \@tempa
2197         \fi
2198 }
```

`\calc@author@part@`

```
2199 \def\calc@author@part@{%
2200   \ifnum \@tempcnta = 1
2201     \exp\oneauthorlabel\exp{\@tempa}%
2202   \else
2203     \exp\multiauthorlabel\exp{\@tempa}%
2204   \fi
2205 }
```

`\calc@author@part@short`

```
2206 \def\calc@author@part@short@{%
2207   \exp\multiauthorlabel\exp{\@tempa}%
2208 }%
```

`\@firststone` This extracts the first character from a properly prepared author name (i.e., one in which accents are properly wrapped).

```
2209 \def\@firststone{\@car\@empty\@nil}
```

`\@firstthree` And this extracts the first three characters.

```
2210 \def\@firstthree{\@car\@empty\@empty\@empty\@nil}
```

`\@nametoken`

```
2211 \let\@nametoken\@firststone
```

`\hyph@to@space`

```
2212 \def\hyph@to@space{\#1 \hyph@to@space}
```

`\@marknames` Since we have a ' with funny catcode already, let's use it (being able to easily put a space after the ' makes things easier).

```

2213 \def\@marknames#1{%
2214   \ifnotempty{#1}{\surround@names#1 , }%
2215 }

\surround@names
2216 \def\surround@names#1 {%
2217   \ifx '#1%
2218   \else
2219     \@nx\@nametoken{#1}%
2220     \@xp\surround@names
2221   \fi
2222 }

\extract@surnames
2223 \def\extract@surnames#1#2{%
2224   \get@namepart\@tempb\@nilgobble #2,\@nil
2225   \edef\@tempb{\@nx\@marknames{\@xp\hyph@to@space\@tempb\@gobble-}}%
2226   \edef#1{\@tempb}%
2227 }

\@oneauthorlabel This is the easy case.
2228 \newcommand{\@oneauthorlabel}[1]{%
2229   \def\name##1{%
2230     \extract@surnames\@tempa{##1}%
2231     \get@numberof\@tempcnta\@nametoken\@tempa
2232     \ifnum \@tempcnta = 1
2233       \let\@nametoken\@firstthree
2234     \fi
2235     \append@to@stem{\@tempa}%
2236   }%
2237   #1%
2238 }

\@threeauthors
2239 \def\@threeauthors\name#1\name#2\name#3#4\@empty{%
2240   \name{#1}\name{#2}\name{#3}%
2241   \append@to@stem{\etalchar{+}}%
2242 }

\@multiauthorlabel
2243 \newcommand{\@multiauthorlabel}[1]{%
2244   \def\name##1{%
2245     \ifx\etaltext ##1%
2246       \def\@tempa{\@nx\etalchar{+}}%
2247       \let\name\@gobble
2248     \else
2249       \extract@surnames\@tempa{##1}%
2250     \fi
2251     \append@to@stem{\@tempa}%
2252 }

```

```

2252      }%
2253      \ifnum \tempcnta > 4 \exp \threeauthors \fi
2254      #1\empty
2255 }

\etalchar
2256 \newcommand{\etalchar}[1]{$^{\#1}$}

```

\year@short For alphanumeric labels, we want to extract the last 2 digits of the year. Here's a way to do that, assuming a 4-digit year.

```
2257 \def\year@short#1#2#3#4\@nil{#3#4}
```

\append@label@year@

```

2258 \def\append@label@year@{%
2259   \safe@set\tempcnta\bib@year
2260   \edef\bib@citeyear{\the\tempcnta}%
2261   \append@to@stem{%
2262     \ifx\bib@year\empty
2263     \else
2264       \exp\year@short \bib@citeyear \@nil
2265     \fi
2266   }%
2267 }

2268 \let\alpha@label@suffix\empty
2269
2270 \newcount\alpha@suffix
2271 \alpha@suffix\@ne
2272 \let@\suffix@format@\alpha@suffix

```

\calc@alpha@suffix

```

2273 \def\calc@alpha@suffix{%
2274   \tempswafalse
2275   \compare@stems\previous@stem\current@stem
2276   \ifsame@stems

```

Under the `alphabetic` option, `\previous@year` and `\current@year` will always be the same (namely, both will be empty), but including the test allows this code to work with the `author-year` option as well.

```

2277   \ifx\previous@year\current@year
2278     \tempswatrue
2279   \fi
2280   \else
2281     \begingroup
2282       \let\name\firstofone
2283       \apply\auto\stringify\amsrefs@textsymbols
2284       \apply\auto\stringify\amsrefs@textaccents
2285       \ifundefined{amsrefs@stem@\current@stem}{%
2286         \expandafter\gdef\csname amsrefs@stem@\current@stem\endcsname{}%■
2287       }%

```

```

2288          \DuplicateBibLabelWarning
2289          }%
2290          \endgroup
2291          \fi
2292          \if@tempswa
2293              \global\advance\alpha@suffix\@ne
2294              \edef\alpha@label@suffix{\@suffix@format\alpha@suffix}%
2295              \ifnum\alpha@suffix=\tw@
2296                  \immediate\write\auxout{%
2297                      \string\ModifyBibLabel{\prev@citekey}%
2298                  }%
2299              \fi
2300          \else
2301              \let\alpha@label@suffix\@empty
2302              \global\alpha@suffix\@ne
2303              \xp\ifx \csname b@\current@citekey @suffix\endcsname \relax
2304              \else
2305                  \edef\alpha@label@suffix{\@suffix@format\alpha@suffix}%
2306              \fi
2307          \fi
2308      }

\ifsame@stems
2309 \newif\ifsame@stems

\compare@stems
2310 \def\compare@stems#1#2{%
2311     \begingroup
2312         \purge@edef\@tempa{#1}%
2313         \purge@edef\@tempb{#2}%
2314         \lc@edef\@tempa{\@tempa}%
2315         \lc@edef\@tempb{\@tempb}%
2316         \ifx\@tempa\@tempb
2317             \def\@tempa{\same@stemtrue}%
2318         \else
2319             \def\@tempa{\same@stemfalse}%
2320         \fi
2321     \xp\endgroup
2322     \@tempa
2323 }

\ModifyBibLabel
2324 \def\ModifyBibLabel#1{%
2325     \global\xp\let\csname b##1@suffix\endcsname\@empty
2326 }

```

6.20 Generating short alphabetic labels

This style for alphabetic labels is somewhat simpler than the regular alphabetic style. The stem consists only of an author part without a year part. The author

part is formed in the same way, except that even when there is only a single author with a one-word last name, only the first letter of the name is used, not the first three. Finally, the suffix used to disambiguate identical stems is numeric rather than alphabetic.

See section 6.26.2 on page 108 for the implementation.

6.21 Formatting series

The `\PrintSeries` command prints a list of objects in series form. The essential idea is to produce something like “A, B, and C” when we are given three elements “A”, “B”, and “C”, with suitable variations in the punctuation and other intervening material depending on the number of elements.

More precisely, we can envision `\PrintSeries` being called as

```
\PrintSeries{S}{i1}{i2}{i3}{E}{\do{T1} ... \do{Tn}}
```

where S and E are material to be interpolated before the start and after the end of the list, respectively, i_1, \dots, i_3 are material to be interpolated between the elements, and the final argument is a list of indeterminate length where each element consists of a macro and its argument. If there are exactly two elements, i_1 is inserted between them; otherwise, i_2 is inserted between each pair of items except for the last pair, where i_3 is inserted. Thus,

n	output
1	$S T_1 E$
2	$S T_1 i_1 T_2 E$
3	$S T_1 i_2 T_2 i_3 T_3 E$
4	$S T_1 i_2 T_2 i_2 T_3 i_3 T_4 E$

and so forth. For example, a standard comma-separated list could be formatted by

```
\PrintSeries{}{ and }{, }{, and }{...}
```

That is the simple case but in practice there are additional complications. What if user-supplied line breaks have to be supported at the boundaries between elements? What if in addition to adding material between elements we also want to apply some handy function to each element (e.g., `\textsc`)? Even worse, what if we want the function to be different depending on the position of the element in the list? Indeed if this did not happen to be the case with the current application I would not have gone to the extra trouble of supporting it. But if it must be so, then the output that we need from a list `\do{A}\do{B}...` is

```
f0{A}
f0{A} p1 i1 f1{B}
f0{A} p2 i2 f2{B} p3 i3 f3{B}
```

and so on, where

- f_n is a macro taking one argument,
- p_n is punctuation—material that must precede a line break if one occurs at this boundary,
- i_n other interpolated material, as before.

To reduce the number of distinct required objects we decree that each element will get braces wrapped around it as a matter of course; then it is possible for f_1 , f_2 , f_3 to be assimilated onto the tail end of i_1 , i_2 , i_3 . Since we also have to specify the macro that delimits the elements of the list, we end up with the following rather formidable signature:

```
\PrintSeries{\m} {f0} {p1} {i1f1} {p2} {i2f2} {p3} {i3f3}  
{S} {\m{T1}... \m{Tn}} {E}
```

and our comma-separated list example becomes

```
\PrintSeries{\do{ }{ }{ and }{ ,}{ }{ ,}{ and }{ }{ ...}{ }}
```

\series@index First we define a dedicated count register to be used in tracking the ordinal number of the item currently being processed.

```
2327 \newcount\series@index
```

\PrintSeries

```
2328 \def\PrintSeries#1#2#3#4#5#6#7#8{ %  
2329   \begingroup  
2330     \def\series@add@a{#2}%  
2331     \def\series@add@b{\SwapBreak{#3}{#4}}%  
2332     \def\series@add@c{\SwapBreak{#5}{#6}}%  
2333     \def\series@add@d{\SwapBreak{#7}{#8}}%  
2334     \def\series@add@e{\SwapBreak{#7}{}}%  
2335     \PrintSeries@a{#1}%  
2336 }
```

\PrintSeries@a For **\PrintSeries@a** the first arg is the iterator function present in the list which is arg 3. Args 2 and 4 are extra material to be added before and after the list that may require the use of **\Plural** or **\SingularPlural**.

```
2337 \def\PrintSeries@a#1#2#3#4{ %  
2338   \get@numberof\@tempcnta#1{#3}%  
2339   \chardef\series@total=\@tempcnta  
2340   \ifnum\series@total=\@ne  
2341     \let\SingularPlural\@firstoftwo  
2342   \else  
2343     \let\SingularPlural\@secondoftwo  
2344   \fi  
2345   \series@index=\z@  
2346   \let#1\series@add  
2347   #2#3#4\relax  
2348 \endgroup  
2349 }
```

\series@add This is the inner function called by **\PrintSeries** that carefully distributes all the material stored previously in **\series@add@...** macros.

Note that the handling of “et al.” cases is somewhat hardcoded. This seemed preferable to adding yet another argument (or two!) to **\PrintSeries**.

```
2350 \def\series@add#1{ %
```

```

2351      \advance\series@index@ne
2352      \ifx\etaltext#1\relax
2353          \ifnum\series@index=\tw@
2354              \def\@tempa{\space\SubEtal}%
2355          \else
2356              \def\@tempa{\series@add@\space\SubEtal}%
2357          \fi

```

We assume there are fewer than 20,000 items in the list.

```

2358          \series@index@MM
2359      \else
2360          \ifcase\series@index
2361          \or

```

Material before name 1:

```

2362          \let\@tempa\series@add@a
2363          \or

```

Material before name 2:

```

2364          \ifnum\series@total<\thr@@
2365              \let\@tempa\series@add@b
2366          \else
2367              \let\@tempa\series@add@c
2368          \fi
2369      \else

```

Material before names 3, 4, 5,...

```

2370          \ifnum\series@index=\series@total
2371              \let\@tempa\series@add@d
2372          \else
2373              \ifnum\series@index<\series@total
2374                  \let\@tempa\series@add@c
2375              \else
2376                  \let\@tempa@\gobble
2377              \fi
2378          \fi
2379      \fi
2380      \fi
2381      \@tempa{#1}%
2382 }

```

\SwapBreak This takes a single argument, which should begin with a punctuation character, and conditionally appends it to the current horizontal list after removing any preceding whitespace. If there was also a penalty at the end of the hlist (presumed to be the result of a `\linebreak` at the end of a field value), it moves the penalty to *after* the argument.

Known bug: `\SwapBreak` interferes with TeX's kerning mechanism. For example, consider a field value that ends with a "y" and that should have a comma automatically appended. `amsrefs` generates the equivalent of `y\SwapBreak{,}`, which results in "y," (no kern before the comma) rather than "y,". Unfortunately, fixing this would

likely require a disproportionate effort. In cases where the lack of kerning is unacceptable, a workaround is to add the punctuation mark to the field value manually. For example, `title={...y,}` would generate the equivalent of `y,\SwapBreak{},`, which in turn would produce “y,” since `\SwapBreak` is careful not to add duplicate punctuation.

```
2383 \def\SwapBreak#1{%
2384   \relax\ifvmode\leavevmode\fi
2385   \tempcnta\z@MM
2386   \toks@{\#1}%
```

First, remove any preceding glue. (There usually shouldn’t be any of this.)

```
2387   \unskip
```

There might be also be kern, typically an italic correction left there by a previous `TextFontCommand` like `\textit`. But don’t remove the special 1sp kern used to mark the beginning of a bibliography entry.

Known bug: Sometimes we want to keep the italic correction.

```
2388   \ifnum \lastkern>\z@ \unkern \fi
```

And now look for a penalty and stash it in a safe place.

```
2389   \ifnum\lastpenalty=\z@
2390   \else
2391     \tempcnta\lastpenalty
2392     \unpenalty
2393   \fi
```

Now we add the punctuation, *unless* one of the following conditions is true:

1. The last item on the horizontal list was a kern of 1sp, indicating that we’re at the very beginning of a bibliography item.
2. The current space factor is equal to the `\sfcode` of the punctuation mark we are adding, meaning that the mark is already on the list.
3. The current space factor is equal to the special value `\nopunctsfcode`, meaning that `\nopunct` was specified.

This relies on distinct punctuation marks having distinct space factors, as established by our definition of `\frenchspacing`.

```
2394   \edef\tempa{%
2395     \nx\deferredquoteslogical
2396     \ifnum\lastkern=\z@
2397     \else
2398       \ifnum\spacefactor=\sfcode\xp\xp\xp`\xp\car\string#\z@\nil
2399     \else
2400       \ifnum\spacefactor=\nopunctsfcode
2401       \else
2402         \the\toks@
2403       \fi
2404     \fi
2405   \fi
```

```

2406      \@nx\deferredquotes
2407      \ifnum\@tempcnta=\@MM \else \penalty\number\@tempcnta\space \fi
2408      \ifnum\lastkern=\@ne \ignorespaces \fi
2409  }%
2410  \@tempa
2411 }

```

\Plural \Plural takes one argument and prints it if there were two or more elements in the current list. So, to get “editors” instead of “editor” after printing a list of editor names, write `editor\Plural{s}`.

\SingularPlural takes two arguments and prints the first if there was only one element, otherwise prints the second arg.

```

2412 \newcommand{\SingularPlural}[2]{#1}
2413 \newcommand{\Plural}{\SingularPlural{}}

```

6.22 Formatting names and series of names

Now that we have a general mechanism for formatting series, we can easily specialize to the common case of a comma-separated list of names. First we provide specifications for the three most common name formats.

\setbib@nameLE This sets a name in standard western uninverted order, e.g., “John Doe Jr.” (The “LE” stands for little-endian.)

```

2414 \BibSpec{nameLE}{
2415   +{}{}{given}
2416   +{}{\IfEmptyBibField{given}{}{\ }}{surname}
2417   +{}{ }{jr}
2418 }

```

\setbib@nameBE Big-endian order, as used for example in traditional Chinese, Japanese, Vietnamese, and Hungarian names: “Doe John”. Big-endian formatting can be requested for name by setting the “inverted” property to “yes.”

```

2419 \BibSpec{nameBE}{
2420   +{}{}{surname}
2421   +{}{ }{given}

```

I don’t know what should happen if there’s a suffix, so I’m going to just leave it out for now (although I should probably issue a warning). I suspect that either (a) it never comes up or (b) if it does come up, there’s no set standard for how it should be handled.

```

2422 %   +{}{ }{jr}
2423 }

```

\setbib@nameinverted Inverted western-style names: “Doe, John, Jr.”

```

2424 \BibSpec{nameinverted}{
2425   +{} {} {surname}
2426   +{},{} { } {given}
2427   +{},{} { } {jr}
2428 }

```

Incidentally, it would probably be cleaner if names had their own namespace like properties do, i.e., something like

```
\DefineSimpleKey{name}{given}
\DefineSimpleKey{name}{initials}
\DefineSimpleKey{name}{surname}
\DefineSimpleKey{name}{jr}
```

followed by

```
\NameSpec{nameLE}{...}
```

or

```
\BibSpec[name]{nameLE}{...}
```

But this seems a little extravagant at this stage, so I've decided to leave things as-is for now.

`\PrintNames` `\PrintNames` is a simplified interface to `\PrintSeries` that takes only the last three arguments:

```
\PrintNames {S} {E} {\name{T_1}...\name{T_n}}
```

The order of the last two arguments is reversed to make it moderately easier to use; cf. `\PrintEditorsA`, etc.

The first name in a series is treated differently than the other names in the **author-year** style, so we use a separate formatting macro for it.

```
2429 \newcommand{\PrintNames}{%
2430   \@ifstar{\PrintNames@a\set@othername}{\PrintNames@a\set@firstname}%
2431 }
```

```
\PrintNames@a
2432 \newcommand{\PrintNames@a}[4]{%
2433   \PrintSeries{\name{%
2434     {#1}%
2435     {}{ and \set@othername}%
2436     {,}{ \set@othername}%
2437     {,}{ and \set@othername}%
2438     {#2}{#4}{#3}}%
2439 }
```

`\set@firstname` By default, the first name is formatted in little-endian format. The **author-year** option changes this to inverted order.

```
2440 \def\set@firstname#1{%
2441   \set@name{#1}\setbib@nameLE
2442 }
```

`\set@othername` The rest of the names are set in little-endian format by default.

```
2443 \def\set@othername#1{%
2444   \set@name{#1}\setbib@nameLE
2445 }
```

`\set@name` Parse the name into its components and then pass control to `\set@name@a`, which will decide what format to use for the name.

```
2446 \def\set@name#1{%
2447   \name@split#1,,,@stop
2448   \set@name@a
2449 }
```

`\set@namea` Use the requested format unless the `order` property has been set to “inverted.”

```
2450 \def\set@name@a#1{%
2451   \begingroup
2452     \get@current@properties
2453     \select@auxlanguage
2454     \def\@tempa{yes}%
2455     \ifx\@tempa\prop'inverted
2456       \setbib@nameBE
2457     \else
2458       #1%
2459     \fi
2460   \endgroup
2461 }
```

`\PrintPrimary`

```
2462 \def\PrintPrimary{%
2463   \ifx\current@primary\empty
2464     \EmptyPrimaryWarning
2465   \else
2466     \print@primary\current@primary
2467   \fi
2468 }
```

`\EmptyPrimaryWarning`

```
2469 \def\EmptyPrimaryWarning{%
2470   \amsrefs@warning{No authors, editors or translators}%
2471 }
```

`\PrintAuthors` The comparison of `\previous@primary` and `\current@primary` doesn’t look at auxiliary properties (see also `\PrintEditorsA` and `\PrintTranslatorsA`). This is probably ok.

```
2472 \newcommand{\PrintAuthors}[1]{%
2473   \ifx\previous@primary\current@primary
2474     \sameauthors\empty
2475   \else
2476     \def\current@bibfield{\bib'author}%
2477     \PrintNames{}{}{#1}%
2478   \fi
2479 }
```

`\sameauthors`

```
2480 \newcommand{\sameauthors}[1]{\bysame#1}
```

```

\bysame
2481 \def\bysame{%
2482   \leavevmode\hbox to3em{\hrulefill}\thinspace
2483   \kern\z@%
2484 }

```

\PrintNameList This just prints the names without any additional information.

```
2485 \newcommand{\PrintNameList}{\PrintNames{}{}}
```

\PrintEditorsC

```

2486 \newcommand{\PrintEditorsC}[1]{%
2487   \PrintNames{Edited by }{}{\#1}%
2488 }

```

\PrintEditorsA When we consider editor names we have to think about some further complications. First, for the case of a book where editor names are listed in place of author names, just copy the same style with a bit of added text at the end.

```

2489 \newcommand{\PrintEditorsA}[1]{%
2490   \ifx\previous@primary\current@primary
2491     \sameauthors{(ed\Plural{s}.)}%
2492   \else
2493     \def\current@bibfield{\bib'editor}%
2494     \PrintNames{}{(ed\Plural{s}.)}{\#1}%
2495   \fi
2496   \erase@field\bib'editor
2497 }

```

\PrintEditorsB

```

2498 \newcommand{\PrintEditorsB}{%
2499   \PrintNames*{()}{\SwapBreak{,}^ed\Plural{s}.}%
2500 }

```

\PrintContributions

```

2501 \newcommand{\PrintContributions}[1]{%
2502   \PrintSeries
2503   {\fld@elt}
2504   {\print@contribution}
2505   {}{ and \print@contribution}
2506   {,}{ \print@contribution}
2507   {,}{ and \print@contribution}{}{\#1}{}%
2508 }

```

\print@contribution

```

2509 \newcommand{\print@contribution}[1]{%
2510   \in@{\#1}%
2511   \ifin@
2512     \ifnum\series@index=\@ne with \fi
2513     \RestrictedSetKeys{}{bib}%

```

```

2514         \bib@print@inner\setbib@contribution{\the\rsk@toks}%
2515     }{#1}%
2516   \else
2517     #1%
2518   \fi
2519 }

\resolve@inner
2520 \def\resolve@inner#1#2{%
2521   \in@={#2}%
2522   \ifin@
2523     \RestrictedSetKeys[]\bib{#1{\the\rsk@toks}}{#2}%
2524   \else
2525     \@ifundefined{bi@#2}{%
2526       \XRefWarning{#2}%
2527     }{%
2528       #1{\csname bi@#2\endcsname}%
2529     }%
2530   \fi
2531 }

\PprintConference
2532 \def\PprintConference{%
2533   \resolve@inner{\bib@print@inner\setbib@conference}%
2534 }

\PprintConferenceDetails
2535 \def\PprintConferenceDetails#1{%
2536   \ifx\empty\bib'address
2537     \ifx\empty\bib'date
2538       \else
2539         \PprintConferenceDetails@%
2540       \fi
2541     \else
2542       \PprintConferenceDetails@%
2543     \fi
2544 }

\PprintConferenceDetails@
2545 \def\PprintConferenceDetails@{%
2546   \ifnum\lastkern=\one\else\space\fi(\kern 1sp
2547   \ifx\empty\bib'address
2548     \else
2549       \bib'address
2550     \fi
2551   \ifx\empty\bib'date
2552     \else
2553       \SwapBreak{,}\space
2554     \print@date

```

```

2555     \fi
2556     )%\\spacefactor\\sfcode'\\,%
2557 }

\PprintBook
2558 \def\PprintBook{%
2559   \resolve@inner{\bib@print@inner\setbib@innerbook}
2560 }

\PprintReprint
2561 \def\PprintReprint{%
2562   \resolve@inner{\bib@reprint}
2563 }

\bib@reprint
2564 \def\bib@reprint#1{%
2565   \begingroup
2566     #1\relax           % execute definitions locally
2567     \bib@resolve@xrefs
2568     \bib@field@patches
2569     \bib@setup
2570     \IfEmptyBibField{copula}{reprinted in}{\bib'copula} \nopunct
2571     \let\bib'language\empty
2572     \setbib@book
2573   \endgroup
2574 }

\PprintTranslation
2575 \def\PprintTranslation{%
2576   \resolve@inner{\bib@translation}
2577 }

\bib@translation
2578 \def\bib@translation#1{%
2579   \begingroup
2580     #1\relax           % execute definitions locally
2581     \bib@resolve@xrefs
2582     \bib@field@patches
2583     \bib@setup
2584     \let\PrintPrimary\empty
2585     \bib@append{;}{ % keep this space!
2586       \IfEmptyBibField{language}{English}{\bib'language} transl.%}
2587       \IfEmptyBibField{pages}{ in \kern\@ne sp}{, }%
2588     }\bib'transition
2589     \let\bib'language\empty
2590     \setbib@0
2591   \endgroup
2592 }

```

```
\PrintTranslatorsC
2593 \newcommand{\PrintTranslatorsC}[1]{%
2594     \PrintNames{translated by }{}{#1}%
2595 }

\PrintTranslatorsA
2596 \newcommand{\PrintTranslatorsA}[1]{%
2597     \ifx\previous@primary\current@primary
2598         \sameauthors{(trans.)}%
2599     \else
2600         \def\current@bibfield{\bib'translator}%
2601         \PrintNames{}{(trans.)}{#1}%
2602     \fi
2603     \erase@field\bib'translator
2604 }

\PrintTranslatorsB
2605 \newcommand{\PrintTranslatorsB}[1]{%
2606     \PrintNames*{}{\SwapBreak{,}^{\tran\Plural{s}.}}%
2607 }
```

Some special handling for “et alii” or “and others”.

```
2608 \DefineName{alii}{\etaltext}
2609 \DefineName{others}{\etaltext}
```

`\etaltext` The Chicago Manual of Style suggests that it is slightly better not to italicize
`\SubEtal` ‘et al’ and some other extremely common abbreviations inherited from Latin.
(Compare ‘etc’.)

```
2610 \newcommand{\etaltext}{et al.}
2611 \newcommand{\SubEtal}[1]{\etaltext}
```

6.23 The partial field

```
\print@partial
2612 \newcommand{\print@partial}{%
2613     \resolve@inner{\bib@print@inner\setbib@partial}%
2614 }
```

6.24 Special formatting for other fields

`\parenthesize` The `\parenthesize` function adds parentheses around its argument, calling
`\upn` to optionally prevent italic parentheses from being used.

```
2615 \newcommand{\parenthesize}[1]{%
2616     \leavevmode\push@bracket\upn{()#1\pop@bracket}%
2617 }
```

`\upn` By default, `\upn` is a no-op, meaning that this refinement lies dormant unless
the `upref` package or other activation is done. (Probably better done via special
fonts, anyway.)

```
2618 \providecommand{\upn}[1]{#1}
```

```

\push@bracket
\pop@bracket 2619 \let\bracket@stack\empty
2620
2621 \def\push@bracket#1{%
2622   \xdef\bracket@stack{\#1\bracket@stack}%
2623 }
2624
2625 \def\pop@bracket{%
2626   \iffalse{\fi
2627     \xp\pop@bracket@a\bracket@stack \empty}%
2628 }
2629
2630 \def\pop@bracket@a#1{%
2631   \leavevmode\upn{#1}%
2632   \xdef\bracket@stack{\iffalse}\fi
2633 }

\bibquotes
2634 \newcommand{\bibquotes}[1]{%
2635   \textquotedblleft#1%
2636   \gdef\deferredquotes{%
2637     \global\let\deferredquotes\empty
2638     \textquotedblright
2639   }%
2640 }

\mdash Cf. textcmds, where there's also a penalty added.
\ndash 2641 \providecommand{\mdash}{\textemdash}
2642 \providecommand{\ndash}{\textendash}

\strip@MRprefix
2643 \def\strip@MRprefix#1#2#3#4\@nil{%
2644   \def\@tempa{#1#2#3#4}%
2645   \if#1M%
2646     \if#2R%
2647       \def\@tempa{#3#4}%
2648     \fi
2649   \fi
2650 }

\MR
2651 \def\MR#1{%
2652   \relax\ifhmode\unskip\spacefactor3000 \space\fi
2653   \begingroup
2654     \strip@MRprefix#1\@nil
2655     \edef\@tempa{MR\@nx\MRhref{\@tempa}{\@tempa}}%
2656   \xp\endgroup
2657   \@tempa
2658 }

```

\MRhref For older versions of some AMS document classes, this patch is needed.

```
2659 \providecommand{\MRhref}[2]{#1}
```

\PrintReviews Reviews are handled as a list to support the theoretical possibility of multiple reviews.

```
2660 \newcommand{\PrintReviews}[1]{%
2661   \PrintSeries{\fld@elt}{.,}{.,}{.,}{.,}{.,}{#1}{}%
2662 }
```

\PrintPartials

```
2663 \newcommand{\PrintPartials}[1]{%
2664   \PrintSeries
2665     {\fld@elt}
2666     {\print@partial}
2667     {;}{\print@partial}
2668     {;}{\print@partial}
2669     {;}{\print@partial}{#1}{}%
2670 }
```

\PrintISBNs And similarly for ISBNs. There seem to be a few different situations where one book might have two different ISBN numbers. Here are the ones I know of so far [mjd,2002-02-18]: separate ISBN numbers for hardback and paperback; separate ISBN numbers for U.S. edition and European edition.

```
2671 \newcommand{\PrintISBNs}[1]{%
2672   \PrintSeries{\fld@elt}{.,}{.,}{.,}{.,}{ISBN}{#1}{}%
2673 }
```

\voltext

```
2674 \newcommand{\voltext}{\IfEmptyBibField{series}{Vol.~}{vol.~}}
```

\issuetext

```
2675 \newcommand{\issuetext}{no.~}
```

\DashPages Scan the contents of a page value to see if it is a single page. Presence of \ndash or hyphen is taken to mean no. Probably should test also for spaces and commas. [mjd,2000/01/24]

```
2676 \newcommand{\DashPages}[1]{%
2677   p\pp@scan@a#1@\ndash p@\ndash{\pp@scan#1@-p@-{}@\nil}\@nil.~#1%
2678 }
2679
2680 \def\pp@scan#1-#2@-#3#4@\nil{#3}
2681
2682 \def\pp@scan@a#1\ndash#2@\ndash#3#4@\nil{#3}
```

\eprintpages If we have eprint info and pages info and no journal name, the pages information is presumably the number of pages in the eprint.

```
2683 \newcommand{\eprintpages}[1]{%
2684   #1\IfEmptyBibField{eprint}{}{\IfEmptyBibField{journal}{ pp.}{}{}}%
2685 }
```

```

\PprintThesisType
2686 \def\PprintThesisType#1{%
2687   \thesis@type#1?\@nil{#1}%
2688 }
2689
2690 \def\thesis@type#1#2\@nil#3{%
2691   \ifx p#1%
2692     Ph.D. Thesis%
2693   \else
2694     \ifx m#1%
2695       Master's Thesis%
2696     \else
2697       #3%
2698   \fi
2699 \fi
2700 }

```

\PrintDOI Perhaps need to add allowbreak penalties at the parentheses in a DOI. Also what about prohibiting a break after the leading S?

```

2701 \newcommand{\PrintDOI}[1]{%
2702   DOI #1%
2703 }

```

\PrintDatePV Print date in different forms depending on DOI and volume information.

```

2704 \newcommand{\PrintDatePV}[1]{%
2705   \IfEmptyBibField{doi}{%
2706     \let\@tempa\PrintDate
2707   }{%
2708     \IfEmptyBibField{volume}{%
2709       \let\@tempa\PrintDatePosted
2710     }{%
2711       \let\@tempa\PrintDate
2712     }%
2713   }%
2714   \@tempa{#1}%
2715 }

```

\PrintDate The intent is to handle variations such as 1987, August 1987, 1987-08, and 1987-08-14. If the month is present, print August or Aug. or 08 or nothing, at the behest of the bib style.

We've taken some special care to parse out the date info ahead of time, so this function just discards arg 1 and uses the already-parsed value.

```

2716 \newcommand{\PrintDate}[1]{(\print@date)}

```

\PrintDateB The same, but without the parentheses.

```

2717 \newcommand{\PrintDateB}[1]{\print@date}

```

\PrintDateField

```

2718 \newcommand{\PrintDateField}[1]{%
2719   \@ifempty{#1}{}{%
2720     \begingroup
2721       \bib@parsedate{#1}%
2722       \print@full@date
2723     \endgroup
2724   }%
2725 }

\print@full@date
2726 \def\print@full@date{%
2727   \ifx\bib@month\empty
2728   \else
2729     \print@month@day
2730   \fi
2731   \bib@year
2732 }

\print@date
2733 \let\print@date\print@full@date

\print@month@day
2734 \def\print@month@day{%
2735   \bib@monthname
2736   \ifx\empty\bib@day \else \nobreakspace\number 0\bib@day,\fi
2737   \space
2738 }

```

\bib@monthname With the Babel package, month names for a given language are typically available in a macro `\month@language`:

```

\def\month@german{\ifcase\month\or
  Januar\or Februar\or M\"arz\or April\or Mai\or Juni\or
  Juli\or August\or September\or Oktober\or November\or Dezember\fi}

```

However this is not true for English.

```

2739 \newcommand{\bib@monthname}{%
2740   \ifcase 0\bib@month
2741   \or January\or February\or March\or April\or May\or June\or
2742   July\or August\or September\or October\or November\or December\or
2743   Winter\or Spring\or Summer\or Fall\else Unknown Month\%
2744   \fi
2745 }

```

\PrintYear You can use `\PrintYear` if you want to suppress month/day even when supplied in the data.

```
2746 \newcommand{\PrintYear}[1]{\bib@year}
```

\PrintDatePosted This one is special for AMS use.

```
2747 \newcommand{\PrintDatePosted}[1]{\unskip, posted on \print@date}
```

```

\PprintEdition
2748 \newcommand{\PrintEdition}[1]{%
2749   \afterassignment\print@edition
2750   \count@ 0#1\relax\@nil
2751 }

\Pprint@edition If the number assignment swept up all the contents, produce a cardinal number
from \count@.

2752 \def\print@edition#1#2\@nil{%
2753   \ifx\relax#1\relax
2754     \ifnum\count@>\z@%
2755       \CardinalNumeric\count@
2756     \else
2757       ??th%
2758     \fi
2759     \ \editiontext
2760   \else
2761     \ifnum \count@>\z@ \number\count@ \fi
2762     #1#2\relax
2763   \fi
2764 }

\editiontext
2765 \newcommand{\editiontext}{ed.}

\CardinalNumber
2766 \newcommand{\CardinalNumeric}[1]{%
2767   \number#1\relax
2768   \if
2769     \ifnum#1<14
2770       \ifnum#1>\thr@@ T\else F\fi
2771     \else
2772       F%
2773     \fi
2774     T%
2775     th%
2776   \else
2777     \@xp\keep@last@digit\@xp#1\number#1\relax
2778     \ifcase#1th\or st\or nd\or rd\else th\fi
2779   \fi
2780 }

\keep@last@digit
2781 \def\keep@last@digit#1#2{%
2782   \ifx\relax#2%
2783     \@xp\@gobbletwo
2784   \else
2785     #1=#2\relax
2786   \fi

```

```

2787     \keep@last@digit#1%
2788 }

```

\SentenceSpace Note how careful we are here to preserve \frenchspacing.

```
2789 \newcommand{\SentenceSpace}{\relax\ifhmode\spacefactor`\.\. \fi}
```

\eprint For now, this does nothing. Could do a url/hyperlink or something.

```
2790 \newcommand{\eprint}[1]{\url{#1}}
```

The www.arXiv.org recommendations for citing their eprints are found at <http://xxx.lanl.gov/help/faq/references>, including these examples:

```

arXiv:hep-th/9910001
arXiv:math.AT/9910001
arXiv:physics.acc-ph/9911027

```

6.25 BibTeX support

\bibliographystyle Disable \bibliographystyle since we're going to handle that behind the scenes.

```
2791 \let\bibliographystyle\gobble
```

\bibtex@style

```

2792 \def\bibtex@style{amsrn}

2793 \AtBeginDocument{
2794   \if@filesw
2795     \immediate\write\@auxout{\string\bibstyle{\bibtex@style}}%
2796   \fi
2797 }

```

6.26 Implementing package options

6.26.1 The alphabetic option

```

2798 \IfOption{alphabetic}{%
2799   \def\bibtex@style{amsra}%
2800   \let\process@citelist\process@citelist@unsorted
2801   \amsrefs@option@alphabetic
2802 }{}%

```

6.26.2 The shortalphabetic option

```

2803 \IfOption{shortalphabetic}{%
2804   \def\bibtex@style{amsrs}%
2805   \let\process@citelist\process@citelist@unsorted
2806   \amsrefs@option@shortalphabetic
2807 }{}%

```

6.26.3 The backrefs option

Rather than checking for the backrefs option *per se*, we check to see if the backref package is loaded. This accomodates authors who load the backref package explicitly but do not pass the backrefs option to amsrefs.

```
2808 \AtBeginDocument{%
```

```

2809  \@ifpackageloaded{backref}{%
2810      \let\PrintBackRefs\print@backrefs
2811      \let\BackCite\back@cite

```

The `backref` package uses `\@starttoc` inside `\thebibliography` to open and read the `.brf` file. We could do something similar with `\biblist`, but it seems cleaner to use `\AtBeginDocument`. Unfortunately, `amsart` redefines `\@starttoc` in a way that interacts badly with this use. So, we inline the relevant parts of `\@starttoc` here. (The group and `\makeatletter` are unnecessary at present, but I'll leave them in as future-proofing.)

```

2812      \begingroup
2813          \makeatletter
2814          \cinput{\jobname.brf}%
2815          \if@filesw
2816              \newwrite\tf@brf
2817              \immediate\openout\tf@brf \jobname.brf\relax
2818          \fi
2819          \endgroup
2820      }{}%
2821 }

```

6.26.4 The citation-order option

```

2822 \IfOption{citation-order}{%
2823     \IfOption{alphabetic}{%
2824         \amsrefs@warning@nl{%
2825             The citation-order and alphabetic options are
2826             incompatible%
2827         }%
2828     }{
2829         \def\bibtex@style{amsru}%
2830     }
2831 }

```

6.26.5 The initials option

```

2832 \IfOption{initials}{% TRUE:
2833     \BibSpec{nameLE}{%
2834         +{}{}{initials}
2835         +{}{\IfEmptyBibField{initials}{}{}{surname}}
2836         +{}{ }{jr}
2837     }
2838
2839     \BibSpec{nameBE}{%
2840         +{}{}{surname}
2841         +{}{ }{initials}
2842         % +{}{ }{jr}
2843     }
2844
2845     \BibSpec{nameinverted}{%
2846         +{} {} {surname}
2847         +{},{}{ } {initials}

```

```

2848      +{,}{ } {jr}
2849    }
2850 }% initials? FALSE:
2851 %   \let\extract@initials@gobble
2852 } % end conditional code for initials option

```

6.26.6 The logical-quotes option

```
\deferredquotes
2853 \let\deferredquotes\empty
```

```
\deferredquoteslogical
```

```

2854 \IfOption{logical-quotes}{%
2855   \def\deferredquoteslogical{\deferredquotes}%
2856 }%
2857   \let\deferredquoteslogical\relax
2858 }
```

6.26.7 The non-compressed-cites option

```
2859 \IfOption{non-compressed-cites}{%
2860   \let\cite@compress\cite@print
2861 }{}
```

6.26.8 The non-sorted-cites option

```
2862 \IfOption{non-sorted-cites}{%
2863   \let\process@citelist\process@citelist@unsorted
2864 }{}
```

6.26.9 The short-journals option

```

2865 \IfOption{short-journals}{%
2866   \renewcommand{\DefineJournal}[4]{%
2867     \bib*{\#1}{periodical}{%
2868       issn=\#2,
2869       journal=\#3,
2870     }%
2871   }
2872 }{}
```

6.26.10 The short-publishers option

```
2873 \IfOption{short-publishers}{%
2874   \renewcommand{\DefinePublisher}[4]{%
2875     \bib*{\#1}{publisher}{%
2876       publisher=\#2},%
```

Maybe `short-publishers` should suppress the `address`? Or is that a separate option? I sense a combinatorial explosion coming on....

```

2877   address=\#4},
2878 }
2879 }%
2880 }{}
```

6.26.11 The short-months option

```

2881 \IfOption{short-months}{%
2882   \renewcommand{\bib@monthname}{%
2883     \ifcase 0\bib@month
2884       \or Jan.\or Feb.\or Mar.\or Apr.\or May\or June\or
2885       July\or Aug.\or Sep.\or Oct.\or Nov.\or Dec.\or
2886       Winter\or Spring\or Summer\or Fall\else Unknown Month%
2887     \fi
2888   }%
2889 }{}}

```

6.26.12 The *y2k* option

```

2890 \IfOption{y2k}{%
2891   \IfOption{alphabetic}{%
2892     \def\year@short#1\@nil{#1}%
2893     \def\bibtex@style{amsry}%
2894   }%
2895   \amsrefs@warning@nl{%
2896     The y2k option can only be used with the^^J%
2897     alphabetic option%
2898   }%
2899 }%
2900 }{}}

```

6.26.13 The *bibtex-style* option

```

2901 \IfOption{bibtex-style}{%
2902   \RequirePackage{amsbst}%
2903 }{}}

```

6.26.14 The *msc-links* option

```
2904 \IfOption{msc-links}{%
```

Unless you're using pdfTeX, links cannot be broken across lines, which causes problems for long-form MR numbers such as "MR2149145 (2006d:01012)". To mitigate the problem, we manually break such numbers into two separate links.

```

2905 \@ifundefined{href}{}{%
2906   \def\parse@MR#1 (#2)#3\@nil{%
2907     \def\MR@url{http://www.ams.org/mathscinet-getitem?mr=#1}%
2908     \def\@tempd{#1}%
2909     \def\@tempe{#2}%
2910   }%
2911   \def\MRhref#1#2{%
2912     \begingroup
2913       \parse@MR#1 ()\@empty\@nil%
2914       \href{\MR@url}{\@tempd\vphantom{()}}%
2915       \ifx\@tempe\@empty
2916         \else
2917           \ \ href{\MR@url}{(\@tempe)}%
2918         \fi
2919     \endgroup
2920   }%
2921 }{}}

```

2922 }{}

6.26.15 The author-year option

Here ends the `amsrefs` package, unless the `author-year` option is in effect; then we want to use some different bibspecs.

2923 \IfOption{author-year}{}{\PopCatcodes \endinput}

\@biblistsetup

```

2924 \renewcommand{\@biblistsetup}[1]{%
2925   \RestrictedSetKeys{}{\biblist}{\the\rsk@toks}{#1}%
2926   \rvkIfEmpty{\biblist}{\prefix}{}{%
2927     \amsrefs@warning{%
2928       The ‘prefix’ biblist option cannot be used\MessageBreak
2929       with the author-year option.%%
2930     }%
2931   }%
2932   \rvkIfEmpty{\biblist}{\labels}{}{%
2933     \amsrefs@warning{%
2934       The ‘labels’ biblist option cannot be used\MessageBreak
2935       with the author-year option.%%
2936     }%
2937   }%
2938 }
```

\generate@label

2939 \def\generate@label{%

If the user supplied an explicit `label` field, we use it. Otherwise, we generate our own.

```

2940   \ifx\bib'label\empty
2941     \begingroup
```

We begin by saving the previous stem and initializing the current stem to the empty string.

```

2942     \global\let\previous@stem\current@stem
2943     \global\let\current@stem\empty
2944     \global\let\previous@year\current@year
2945     \global\let\current@year\bib@year
```

The list of primary contributors is available to us in `\current@primary` in the form

$$\name{\text{Last}_1, \text{First}_1} \name{\text{Last}_2, \text{First}_2} \dots \name{\text{Last}_n, \text{First}_n}$$

We will be executing this list multiple times with various definitions of `\name`. So the first thing we want to do is establish a safe environment and normalize the names.

```

2946     \@apply\auto@protect\amsrefs@textsymbols
2947     \@apply\auto@protect\amsrefs@textaccents
2948     \def\name##1{\@nx\name{\lnscan@a##1,\@nil}}%
2949     \auto@protect\etaltext
2950     \normalize@edef\current@stem{\current@primary}%
```

```
2951           \xdef\current@stem{\current@stem}%
```

At this point, the `\current@stem` is complete and we're ready to determine what (if any) suffix is needed to disambiguate it from the previous label.

```
2952           \calc@alpha@suffix
```

We have all the pieces now. Arrange to end the current group and then define `\bib@label` in the enclosing group. (This keeps `\bib@label` from being defined outside the group started by `\bib@start`. This isn't strictly necessary, but it provides a bit of compartmentalization.)

```
2953           \edef@\tempa{%
2954             \def@nx\cite@label{\current@stem}%
2955             \def@nx\bib@label@year{%
2956               \current@year
2957               \alpha@label@suffix
2958             }%
2959           }
2960           \exp\endgroup
2961           \tempa
2962         \fi
2963 }
```

```
\lnscan@a
```

```
2964 \def\lnscan@a#1,#2@nil{#1}
```

```
\citesel@author
```

```
2965 \def\citesel@author#1#2#3#4#5{\PrintCiteNames{#3}}
```

```
\citesel@authoryear
```

```
2966 \def\citesel@authoryear#1#2#3#4#5{\PrintCNY{#3}{#4}}
```

```
\citesel@object
```

```
2967 \def\citesel@object#1#2#3#4#5{\PrintCiteNames{#3} \citeleft#4}
```

```
\citesel
```

```
2968 \let\citesel\citesel@authoryear
```

```
\citeleft
```

```
2969 \def\citeleft{}%
```

```
\citeright
```

```
2970 \def\citeright{}%
```

```
@citeleft
```

```
2971 \def@citeleft{\ifx\citesel\citesel@object\else\citeleft\fi}%
```

```
\citempunct
```

```
2972 \def\citempunct{; }
```

```

\BibLabel
2973 \def\BibLabel{%
2974   \Hy@raisedlink{\hyper@anchorstart{cite.\CurrentBib}\relax\hyper@anchorend}%
2975 }

\process@citelist
2976 \let\process@citelist\process@citelist@unsorted

\ycite
2977 \DeclareRobustCommand{\ycite}[1]{%
2978   \star@\{`cite@a\citesel@year{\#1}\}{}}%
2979 }

\ycites
2980 \DeclareRobustCommand{\ycites}[1]{%
2981   \begingroup
2982     \def\citeref{, }%
2983     \let\citesel\citesel@year
2984     \cites{\#1}%
2985   \endgroup
2986 }

\citeyear
2987 \DeclareRobustCommand{\citeyear}[1]{%
2988   \begingroup
2989     \let\citeleft\empty
2990     \let\citeright\empty
2991     \star@\{`cite@a\citesel@year{\#1}\}{}}%
2992   \endgroup
2993 }

\ocite
2994 \DeclareRobustCommand{\ocite}[1]{%
2995   \star@\{`cite@a\citesel@object{\#1}\}{}}%
2996 }

\ocites
2997 \DeclareRobustCommand{\ocites}[1]{%
2998   \begingroup
2999     \let\@citelist\@ocitelist
3000     \cites{\#1}%
3001   \endgroup
3002 }

\ocitelist
3003 \def\@ocitelist#1{%
3004   \PrintSeries{\InnerCite}%
3005   {\ocite}%
3006   {}{ and }{\ocite}%

```

For three or more names: print ‘et al’ instead of the last name. Have to putz around with the space factor a bit or the comma between name and year will not be applied.

```

3007      {,}{ \ocite}%
3008      {,}{ and \ocite}%
3009      {}%
3010      {\#1}%
3011      {}%
3012 }

\citeauthor
3013 \DeclareRobustCommand{\citeauthor}[1]{%
3014   \star@\{\cite@a\citesel@author{\#1}\}{}%
3015 }

\citeauthory
3016 \DeclareRobustCommand{\citeauthory}[1]{%
3017   \citeauthor{\#1} \ycite{\#1}%
3018 }

\fullcite
3019 \DeclareRobustCommand{\fullcite}[1]{%
3020   \begingroup
3021     \let\print@citenames\CiteNamesFull
3022     \star@\{\cite@a\citesel@authoryear{\#1}\}{}%
3023   \endgroup
3024 }

\fullocite
3025 \DeclareRobustCommand{\fullocite}[1]{%
3026   \begingroup
3027     \let\print@citenames\CiteNamesFull
3028     \star@\{\cite@a\citesel@object{\#1}\}{}%
3029   \endgroup
3030 }

Invert the first author's name.
3031 \def\set@firstname#1{%
3032   \set@name{\#1}\setbib@nameinverted
3033 }

\PrintCNY
3034 \def\PrintCNY#1#2{%
3035   \PrintCiteNames{\#1}%
3036   \@ifnotempty{\#2}{\@addpunct{,} \#2}%
3037 }

```

```
\PrintCiteNames
```

```
3038 \def\PrintCiteNames#1{%
3039   \leavevmode
3040   \def\@tempa{#1}%
3041   \ifx\@tempa\prev@names
3042   \else
3043     \gdef\prev@names{#1}%
3044     \exp\ifx\@car\@nil\CitePrintUndefined
3045     #1\relax
3046   \else
3047     \print@citenames{#1}%
3048   \fi
3049 \fi
3050 }
```

```
\CiteNames
```

```
3051 \newcommand{\CiteNames}[1]{%
3052   \PrintSeries{\name}%
3053   {}%
3054   {}{ and }%
```

For three or more names: print ‘et al’ instead of the last name. Have to putz around with the space factor a bit or the comma between name and year will not be applied.

```
3055   {}{@gobble}%
3056   {}{ \etaltext{@{@gobble}}%
3057   {}%
3058   {#1}%
3059   {}%
3060 }
```

```
\print@citenames
```

```
3061 \let\print@citenames\CiteNames
```

```
\CiteNamesFull
```

```
3062 \newcommand{\CiteNamesFull}[1]{%
3063   \PrintSeries{\name}%
3064   {}%
3065   {}{ and }%}
```

For three or more names: print ‘et al’ instead of the last name. Have to putz around with the space factor a bit or the comma between name and year will not be applied.

```
3066   {,}{ }%
3067   {,}{ and }%
3068   {}%
3069   {#1}%
3070   {}%
3071 }
```

```

\PrintDate No parentheses around the year.
3072 \renewcommand{\PrintDate}[1]{\bib@label@year}

\print@date Only print the year, not the month or day.
3073 \def\print@date{%
3074   \IfEmptyBibField{date}{%
3075     \IfEmptyBibField{year}{\BibField{status}}{\bib@year}%
3076   }%
3077   \bib@year
3078 }%
3079 }

3080 \BibSpec{article}{%
3081   +{}  {\PrintAuthors}           {author}
3082   +{.} { \PrintDate}            {date}
3083   +{.} { \textit}              {title}
3084   +{.} { }                     {part}
3085   +{:} { \textit}              {subtitle}
3086   +{,} { \PrintContributions}  {contribution}
3087   +{,} { \PrintPartials}       {partial}
3088   +{,} { }                     {journal}
3089   +{}  { \textbf}               {volume}
3090   +{,} { \issuetext}           {number}
3091   +{,} { \eprintpages}         {pages}
3092   +{,} { }                     {status}
3093   +{,} { \PrintDOI}            {doi}
3094   +{,} { available at \eprint} {eprint}
3095   +{}  { \parenthesize}         {language}
3096   +{}  { \PrintTranslation}    {translation}
3097   +{:} { \PrintReprint}        {reprint}
3098   +{.} { }                     {note}
3099   +{.} {}                      {transition}
3100   +{}  {\SentenceSpace \PrintReviews} {review}
3101 }
3102

3103 \BibSpec{book}{%
3104   +{}  {\PrintPrimary}          {transition}
3105   +{.} { \PrintDate}            {date}
3106   +{.} { \textit}              {title}
3107   +{.} { }                     {part}
3108   +{:} { \textit}              {subtitle}
3109   +{,} { \PrintEdition}         {edition}
3110   +{}  { \PrintEditorsB}        {editor}
3111   +{,} { \PrintTranslatorsC}   {translator}
3112   +{,} { \PrintContributions}  {contribution}
3113   +{,} { }                     {series}
3114   +{,} { \voltext}             {volume}
3115   +{,} { }                     {publisher}
3116   +{,} { }                     {organization}
3117   +{,} { }                     {address}

```

```

3118    +{,} { }
3119    +{} { \parenthesize}
3120    +{} { \PrintTranslation}
3121    +{} { \PrintReprint}
3122    +{.} { }
3123    +{.} {}
3124    +{} {\SentenceSpace \PrintReviews} {review}
3125 }
3126
3127 \BibSpec{collection.article}{%
3128    +{} { \PrintAuthors} {author}
3129    +{.} { \PrintDate} {date}
3130    +{.} { \textit} {title}
3131    +{.} { }
3132    +{:} { \textit} {part}
3133    +{}, { \PrintContributions} {contribution}
3134    +{}, { \PrintConference} {conference}
3135    +{} { \PrintBook} {book}
3136    +{,} { }
3137    +{,} { pp.\~{}} {pages}
3138    +{,} { } {status}
3139    +{,} { \PrintDOI} {doi}
3140    +{,} { available at \eprint} {eprint}
3141    +{} { \parenthesize}
3142    +{} { \PrintTranslation} {translation}
3143    +{} { \PrintReprint} {reprint}
3144    +{.} { }
3145    +{.} {} {transition}
3146    +{} {\SentenceSpace \PrintReviews} {review}
3147 }
3148
3149 \BibSpec{report}{%
3150    +{} { \PrintPrimary} {transition}
3151    +{.} { \PrintDate} {date}
3152    +{.} { \textit} {title}
3153    +{.} { }
3154    +{:} { \textit} {part}
3155    +{,} { \PrintEdition} {edition}
3156    +{,} { \PrintContributions} {contribution}
3157    +{,} { Technical Report } {number}
3158    +{,} { }
3159    +{,} { }
3160    +{,} { }
3161    +{,} { \eprint} {eprint}
3162    +{,} { }
3163    +{} { \parenthesize}
3164    +{} { \PrintTranslation} {translation}
3165    +{} { \PrintReprint} {reprint}
3166    +{.} { }
3167    +{.} {} {transition}

```

```

3168     +{}  {\SentenceSpace \PrintReviews} {review}
3169 }
3170
3171 \BibSpec{thesis}{%
3172     +{}  {\PrintAuthors}           {author}
3173     +{.} { \PrintDate}            {date}
3174     +{.} { \textit}               {title}
3175     +{:} { \textit}               {subtitle}
3176     +{,.} { \PrintThesisType}    {type}
3177     +{,.} { }                  {organization}
3178     +{,.} { }                  {address}
3179     +{,.} { \eprint}              {eprint}
3180     +{,.} { }                  {status}
3181     +{}  {\parenthesize}         {language}
3182     +{}  {\PrintTranslation}    {translation}
3183     +{;} { \PrintReprint}        {reprint}
3184     +{.} { }                  {note}
3185     +{.} {}                   {transition}
3186     +{}  {\SentenceSpace \PrintReviews} {review}
3187 }
3188
3189 \BibSpec{webpage}{%
3190     +{}  {\PrintAuthors}           {author}
3191     +{.} { \PrintDate}            {date}
3192     +{.} { \emph}                {title}
3193     +{:} { \emph}                {subtitle}
3194     +{,.} { \url}                {url}
3195     +{.} { Accessed \PrintDateField} {accessdate}
3196     +{.} { }                  {note}
3197     +{.} {}                   {transition}
3198 }
3199 \PopCatcodes
3200 
```

6.27 The amsbst package

```

3201 <*bst>
3202 \NeedsTeXFormat{LaTeX2e}[1995/12/01]
3203 \ProvidesPackage{amsbst}[2013/03/07 v2.14]
3204 %\RequirePackage{amsrefs}[2004/03/29]
3205 \BibSpec{article}{%
3206     +{}  {\PrintAuthors}           {author}
3207     +{.} { }                   {title}
3208     +{.} { }                   {part}
3209     +{:} { }                   {subtitle}
3210     +{.} { \PrintContributions}   {contribution}
3211     +{.} { \PrintPartials}       {partial}
3212     +{.} { \emph}                {journal}
3213     +{}  { }                   {volume}
3214     +{}  {\parenthesize}         {number}

```

```

3215   +{::} {} {pages}
3216   +{,:} { \PrintDateB} {date}
3217   +{,:} { } {status}
3218   +{.} { \PrintTranslation} {translation}
3219   +{.} { Reprinted in \PrintReprint} {reprint}
3220   +{.} { } {note}
3221   +{.} {} {transition}
3222 }
3223
3224 \BibSpec{partial}{%
3225   +{} {} {part}
3226   +{:} {} {subtitle}
3227   +{.} { \PrintContributions} {contribution}
3228   +{.} { \emph} {journal}
3229   +{} {} {volume}
3230   +{} { \parenthesize} {number}
3231   +{:} {} {pages}
3232   +{,:} { \PrintDateB} {date}
3233 }
3234
3235 \BibSpec{book}{%
3236   +{} { \PrintPrimary} {transition}
3237   +{.} { \emph} {title}
3238   +{.} { } {part}
3239   +{:} { \emph} {subtitle}
3240   +{.} { } {series}
3241   +{,:} { \volttext} {volume}
3242   +{.} { Edited by \PrintNameList} {editor}
3243   +{.} { Translated by \PrintNameList} {translator}
3244   +{.} { \PrintContributions} {contribution}
3245   +{.} { } {publisher}
3246   +{.} { } {organization}
3247   +{,:} { } {address}
3248   +{,:} { \PrintEdition} {edition}
3249   +{,:} { \PrintDateB} {date}
3250   +{,:} { } {note}
3251   +{,:} {} {transition}
3252   +{.} { \PrintTranslation} {translation}
3253   +{.} { Reprinted in \PrintReprint} {reprint}
3254   +{.} {} {transition}
3255 }
3256
3257 \BibSpec{collection.article}{%
3258   +{} { \PrintAuthors} {author}
3259   +{.} { } {title}
3260   +{.} { } {part}
3261   +{:} { } {subtitle}
3262   +{.} { \PrintContributions} {contribution}
3263   +{.} { \PrintConference} {conference}
3264   +{.} { \PrintBook} {book}

```

```

3265   +{.} { In }                      {booktitle}
3266   +{,} { pages~}                   {pages}
3267   +{.} { \PrintDateB}              {date}
3268   +{.} { \PrintTranslation}        {translation}
3269   +{.} { Reprinted in \PrintReprint} {reprint}
3270   +{.} { }                        {note}
3271   +{.} {}                         {transition}
3272 }
3273
3274 \BibSpec{conference}{%
3275   +{} {}                           {title}
3276   +{} {\PrintConferenceDetails} {transition}
3277 }
3278
3279 \BibSpec{innerbook}{%
3280   +{.} { \emph}                     {title}
3281   +{.} { }                          {part}
3282   +{:} { \emph}                     {subtitle}
3283   +{.} { }                          {series}
3284   +{,} { \voltext}                  {volume}
3285   +{.} { Edited by \PrintNameList} {editor}
3286   +{.} { Translated by \PrintNameList} {translator}
3287   +{.} { \PrintContributions}       {contribution}
3288   +{.} { }                          {publisher}
3289   +{.} { }                          {organization}
3290   +{,} { }                          {address}
3291   +{,} { \PrintEdition}             {edition}
3292   +{,} { \PrintDateB}               {date}
3293   +{.} { }                          {note}
3294   +{.} {}                         {transition}
3295 }
3296
3297 \BibSpec{report}{%
3298   +{} {\PrintPrimary}              {transition}
3299   +{.} { \emph}                   {title}
3300   +{.} { }                       {part}
3301   +{:} { \emph}                   {subtitle}
3302   +{.} { \PrintContributions}     {contribution}
3303   +{.} { Technical Report }      {number}
3304   +{,} { }                       {series}
3305   +{.} { }                       {organization}
3306   +{,} { }                       {address}
3307   +{,} { \PrintDateB}             {date}
3308   +{.} { \PrintTranslation}       {translation}
3309   +{.} { Reprinted in \PrintReprint} {reprint}
3310   +{.} { }                         {note}
3311   +{.} {}                        {transition}
3312 }
3313
3314 \BibSpec{thesis}{%

```

```

3315    +{} {\PrintAuthors} {author}
3316    +{,} { \emph} {title}
3317    +{:} { \emph} {subtitle}
3318    +{.} { \PrintThesisType} {type}
3319    +{.} { } {organization}
3320    +{,} { } {address}
3321    +{,} { \PrintDateB} {date}
3322    +{.} { \PrintTranslation} {translation}
3323    +{.} { Reprinted in \PrintReprint} {reprint}
3324    +{.} { } {note}
3325    +{.} {} {transition}
3326 }
3327
3328 \BibSpec{webpage}{%
3329    +{} {\PrintAuthors} {author}
3330    +{.} { } {title}
3331    +{:} { } {subtitle}
3332    +{.} { \PrintDateB} {date}
3333    +{.} { \url} {url}
3334    +{.} { Accessed \PrintDateField} {accessdate}
3335    +{.} { } {note}
3336    +{.} {} {transition}
3337 }

```

\PrintEditorsA When we consider editor names we have to think about some further complications. First, for the case of a book where editor names are listed in place of author names, just copy the same style with a bit of added text at the end.

```

3338 \renewcommand{\PrintEditorsA}[1]{%
3339   \def\current@bibfield{\bib'editor}%
3340   \PrintNames{}{, editor\Plural{s}}{\#1}%
3341   \erase@field\bib'editor
3342 }

```

\PrintTranslatorsA

```

3343 \renewcommand{\PrintTranslatorsA}[1]{%
3344   \def\current@bibfield{\bib'translator}%
3345   \PrintNames{}{, translator\Plural{s}}{\#1}%
3346   \erase@field\bib'translator
3347 }
3348 
```

The usual `\endinput` to ensure that random garbage at the end of the file doesn't get copied by `docstrip`.

```
3349 \endinput
```

References

- [1] David M. Jones, *User's Guide to the `amsrefs` Package*. distributed with the `amsrefs` code.

[2] Ellen Swanson, Arlene O'Sean, and Antoinette Schleyer, *Mathematics into Type*, updated, American Mathematical Society, 1999.

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	
\"	69, 1787
\&	25
\'	40, 69, 1788
\+	24
\,	24, 120, 2556
\-	24
\.	24, 115, 1789, 2789
.aux	<i>9–11</i> , 53, 64–67
.bb1	9, 31, 32, 50
.bib	9
.brf	109
.dtx	8
.ltb	31, 32, 49
\:	24, 118, 685, 701
\;	24, 119
\=	24, 1790
? option	18
\@undefined	1485
\@MM ..	2358, 2385, 2407
\@addpunct	<i>7</i> , 16, 108, 1448, 3036
\@alph	1085, 2272
\@apply	69
\@arabic	1093, 2173
\@bibdef	31, 32, 633, 647, 651, 663, 1261, 1264, 1280
\@bibitem	27, 541
\@biblist	502, 507, 537
\@biblistsetup	557, 559, 2924
\@bibtitlestyle	1223, 1226
\@car	2209, 2398, 3044
\@arcube	2210
\@chomp	86, 1982, 1994, 2047, 2048
\@chomper	15, 89, 103
\@citeleft	1512, 1520, 2971
\@citeright	
\@citelist	56, 1435, 1436, 2999
\@citeteststyle	1439, 1456
\@citere	58
\@close@bb1@file	
\@concat	60, 2174
\@count@chars	2156, 2161
\@currentlabel	1067, 1137
\@currext	136
\@currname	138
\@empty	15, 20, 22, 51, 52
\@endbiblist	504, 509, 572
\@extract@initial	85, 2122, 2124, 2136
\@filef@und	1294, 1297, 1300, 1314
\@firstofone	15, 43, 1043, 1412, 1434, 1477, 1765, 1771, 2282
\@firstoftwo	48, 1057, 2341
\@firstone	2209, 2211
\@firstthree	2210, 2233
\@for	39
\@gobblefour	753
\@gobblethree	1530
\@ifclassloaded	1201–1203
\@ifempty	45, 269, 1153, 1381, 1406, 1492, 1665, 1671, 1687, 1739, 2719
\@ifnextchar	20
\@ifnotempty	45, 240, 718, 742, 1393, 1514, 2214, 3036
\@ifpackage@loaded	1764, 1767, 1773, 2809
\@ifpackage@with	5, 8, 1774
\@ifsame@patterns	1046, 1052
\@ifsame@pat	1053, 1055
\@input@	1281
\@append	62, 1785, 1814, 1815, 1817, 1818
\@latex@warning	574, 1500
\@lbibitem	27, 542
\@let@token	78, 85
\@listctr	533, 547
\@m	111, 552, 606
\@marknames	2213, 2225
\@maxlabelwidth	545, 578, 581, 582, 590
\@mkboth	48, 1205
\@multiauthorlabel	2203, 2207, 2243
\@nametoken	2211, 2219, 2231, 2233
\@nameuse	72
\@nil	15, 43, 74, 76, 81, 82
\@nilgobble	
\@nmbrlistfalse	76, 83, 1924, 2224
\@nmbrlisttrue 519, 1087, 1095
\@noitemerr	574
\@nopunctsfcode	123, 124, 2400
\@ocitelist	2999, 3003

- \@oneauthorlabel
 2201, 2228
 \@open@bb@file 676,
 1274, 1348, 1364
 \@pass@ptions 135
 \@prev@cite 1642
 \@secondoftwo
 ... 48, 1059, 2343
 \@sptoken 1936,
 2011, 2061, 2109
 \@starttoc 109
 \@suffix@format ...
 ... 1085, 1093,
 2272, 2294, 2305
 \@tabacckludge . 72,
 1844, 1856, 1875
 \@tempa 77
 \@tempcnta 14, 64
 \@tempcntb 64
 \@tempd 2908, 2914
 \@tempdim 580–582
 \@tempe 2909, 2915, 2917
 \@tempswafalse ...
 ... 636, 1128, 2274
 \@tempswatrue . 632,
 1146, 1149, 2278
 \@temptokena 77
 \@testdef 47
 \@threeauthors
 ... 2239, 2253
 \@uclclist 71
 \@urlbreak 25, 27
 \@urlfix 24, 32
 \@urlsetup 20, 22
 \@xifempty 45, 47
 \` 107, 1791
 \` 1792
 \` 29, 1793
 \u ... 1433, 2759, 2917
- A**
- \A 604
 abrv BIBTEX style ... 16
 \add@toks@ 61
 address field 4, 49, 110
 \addto@defer@list ...
 ... 764, 768
 \addto@hook ... 61, 881
- \AE 1823
 \ae 71, 1823
 \after@deleting@token ... 41, 1943,
 1953, 2021,
 2059, 2075, 2118
 \afterassignment 13,
 42, 83, 775, 2749
 \aftergroup ... 22, 292
 alpha BIBTEX style ... 16
 \alpha@label ...
 ... 1068, 1077,
 1082, 1090, 1099
 \alpha@label@ ...
 ... 1069, 1082, 1090
 \alpha@label@suffix ...
 ... 2192,
 2268, 2294,
 2301, 2305, 2957
 \alpha@suffix 2270,
 2271, 2293–
 2295, 2302, 2305
 alphabetic option ...
 ... 16, 87, 90, 108
 amsart class 109
 amsbook class 55
 amsbst package 119
 amsgen package 16
 amsproc class 55
 amsrdoc.tex 3
 amsrefs package ...
 ... 1, 3–6, 8, 10,
 18, 27, 49, 66,
 94, 108, 112, 122
 \amsrefs@lbibitem 515
 \amsrefs@bibcite ...
 ... 1710, 1715, 1719
 \amsrefs@bibitem ...
 ... 515, 541
 \amsrefs@error ...
 ... 106, 259, 309, 656
 \amsrefs@label@prefix ...
 ... 562,
 2172, 2173, 2179
 \amsrefs@lbibitem ...
 ... 515, 542
 \amsrefs@option@alphabetic@AtEndDocument ... 1197
 \amsrefs@option@numeric ...
 ... 1081, 2801
 ... 1076
- \amsrefs@option@shortalphabetic ... 1089, 2806
 \amsrefs@textaccents ... 70, 911, 1127,
 1783, 1785,
 1843, 1857,
 1874, 1975,
 2181, 2284, 2947
 \amsrefs@textsymbols ... 72,
 910, 1126, 1812,
 1814, 1815,
 1817, 1818,
 1842, 1858,
 1872, 1974,
 2180, 2283, 2946
 \amsrefs@warning ...
 ... 105, 566,
 954, 955, 1160,
 1174, 1179,
 1285, 1311,
 1389, 1394,
 1399, 1582,
 1968, 2040,
 2470, 2927, 2933
 \amsrefs@warning@nl ... 4, 6, 9, 158,
 168, 2824, 2895
 amsxport BIBTEX style ... 86, 87
 \append@label@year ... 1086, 1094, 2187
 \append@label@year@ ... 1086, 2258
 \append@to@stem ...
 ... 2174, 2235,
 2241, 2251, 2261
 \ar@hyperlink ...
 ... 1513, 1759, 1768
 \ar@SK@cite ... 1511,
 1762, 1775, 1778
 article entry type ... 5, 7
 \AtBeginDocument ...
 ... 109,
 651, 652, 1711,
 1763, 2793, 2808
 author field 6
 author-year option ... 56, 90, 97, 112

\AuthorList 8
 \auto@protect . . 13,
 57, 73, 910,
 911, 1108,
 1125–1127,
 1842, 1857,
 1865, 1872,
 1971, 1972,
 1974, 1975,
 2180–2183,
 2946, 2947, 2949
 \auto@stringify . .
 . . . 58, 2283, 2284
B
 \b 1794
 \b@ 45, 58, 59, 62, 66, 67
 \b@* 1572
 \b@moo 9, 10, 53
 \b@whatever . . 10, 11, 59
 babel package 43
 \back@cite . . 1747, 2811
 \BackCite . . 1465,
 1544, 1746, 2811
 backref package 108, 109
 backrefs option 10, 108
 \bb@copy . . 681, 735
 \bb@copy@a . . 739, 741
 \bb@out 1346,
 1356, 1357,
 1359, 1367, 1370
 \bb@write 678, 682, 745,
 1347, 1359, 1369
 \bb@name 1268, 1290, 1357
 \begin 9, 10
 \bgroup
 90, 1893, 1961,
 2024, 2078, 2121
 \bi@ 35
 \bib 3–5, 8, 11,
 27, 30, 43, 49,
 51–53, 57, 72, 629
 \bib' 39
 \bib@bar 21
 \bib@date 42
 \bib@given 75, 76
 \bib@initials 76
 \bib@jr 76
 \bib@language 42
 \bib'@pages 21
 \bib@surname 76
 \bib* 31, 32
 \bib@append 21,
 22, 247, 260, 2585
 \bib@author 45
 \bib@bar 21
 \bib@cite . . 45, 787, 1097
 \bib@cite@a . . 1102, 1105
 \bib@cite@check . .
 1117, 1120
 \bib@citeyear . . 2260, 2264
 \bib@day 1014,
 1021, 1022, 2736
 \bib@dbfile
 1291, 1294,
 1297, 1300,
 1319, 1322, 1325
 \bib@div@mark
 1200, 1215, 1228
 \bib@end 37, 804, 821
 \bib@exec 12, 32,
 35, 652, 660, 665
 \bib@field@patches
 783, 810,
 965, 2568, 2582
 \bib@label 88, 113
 \bib@label@year
 1111, 1144,
 1158, 1165,
 1172, 2955, 3072
 \bib@language
 42, 1035,
 1037, 1040,
 1042, 1043,
 1046–1048, 1062
 \bib@language@fixup
 1010, 1032
 \bib@mklab 548, 579
 \bib@month 1013,
 1020, 1023,
 2727, 2740, 2883
 \bib@monthname
 2735, 2739, 2882
 \bib@parsedate
 992,
 995, 1015, 2721
 \bib@parsedate@a
 1016, 1018
 \bib@print
 32, 36, 652, 778
 \bib@print@inner
 806, 2514,
 2533, 2559, 2613
 \bib@reprint 2562, 2564
 \bib@reset 915
 \bib@resolve@xrefs
 782, 809,
 829, 2567, 2581
 \bib@selectlanguage
 784, 1045
 \bib@start
 88, 113, 779, 817
 \bib@store 32, 665, 774
 \bib@translation
 2576, 2578
 \bib@year 45,
 990, 999, 1012,
 1019, 1024,
 2259, 2262,
 2731, 2746,
 2945, 3075, 3077
\BibAbbrevWarning 863, 898, 954
bibchapter environment 1210
\bb@name 1235
\bibcite 9–
 11, 47, 65, 66,
 523, 533, 1195,
 1197, 1715, 1719
\bibcite@a 1710, 1721
\bibcite@b 1726, 1730
\bibcite@write
 1103, 1185
\bibdata 9
\bibdefer@list 767,
 771, 1278, 1279
bibdiv environment 1232
\bibdiv 1238
\BibField 8, 185, 3075
\BibItem 634, 637, 640
\bibitem 9, 10, 27
\BibLabel
 543, 614, 620, 2973
\biblanguagedefault
 1035, 1062
\biblanguageEnglish
 1062
\bibliography 9


```

\cites . . . 1390, 1531,          \CPU@normal . 1506, 1654  \DeclareRobustCommand
      1534,   1536,          \CPU@sort . 1590, 1593    .... 18, 1435,
      1547, 2984, 3000  \cs ..... 72, 73    1503,   1531,
\cites@a . . . 1385,          \CurLine 51, 52, 1325,    2977,   2980,
      1406, 1407, 1531    1326, 1332, 1343    2987,   2994,
\cites@b . . . 1409, 1418  \current@bibfield    2997,   3013,
\cites@cc . . . 1422, 1424    .... 22, 268,    3016, 3019, 3025
\cites@init . . . 1447,          \current@citekey .    \def ..... 23, 58, 59
      1459, 1467, 1552    815, 819, 826, 2303  \defer@bibdef ....
\cites@oo . . . 1382, 1405    \current@primary 87,    ... 670, 760, 1316
\cites@oo . . . 1405, 1406    98, 112, 956    \deferredquotes ...
\CITESEL ..... 57    962, 968, 971    .... 2406, 2636,
\citesel .....    975, 2184, 2463, 2637, 2853, 2855
      45, 53, 57, 59,    2466, 2473,    \deferredquoteslogical
      66, 67, 1377, 2968    2490, 2597, 2950    .... 2395, 2854
\citesel@author . . .    \current@stem .. 88,    \DefineAdditiveKey
      . 1469, 2965, 3014    113, 1180,    .... 189–196
\citesel@authoryear . . .    2169, 2174,    \DefineDummyKey .. 235
      . 2966, 2968, 3022    2178, 2179,    \DefineJournal 4, 17,
\citesel@number . . .    2191, 2275,    38, 49, 1247, 2866
      . 1375, 1377, 1574    2285, 2286,    \DefineName .....
\citesel@object . . .    2942, 2943,    . 4, 37, 49, 52,
      .... 2967,    2950, 2951, 2954    1244, 2608, 2609
\citesel@other . . .    2950, 2951, 2954    \DefinePublisher 17,
      .... 1570, 1571    \current@year .....
\citesel@update . . .    90, 2171, 2277,    38, 49, 1253, 2874
      .... 1372, 1526    2944, 2945, 2956    \DefineSimpleKey .
\citesel@write . . .    \CurrentBib .. 517,    .... 197–234,
      .... 1188, 1193    530, 613, 616,    236, 237, 498, 499
\citesel@year 1376,    823, 1071, 1098,    \DH .....
      2978, 2983, 2991    1176, 1195, 2974    1826
\citeyear .... 2987  \CurrentBibType 32, 654  \dh .....
\CloseBBLFile 1358, 1366  \cydot ..... 1838  \DJ .....
\closein ..... 1319  \D ..... 1827
\clubpenalty . 553, 554  \d ..... 1796  \do ..... 14, 19, 69
\cmr font ..... 56  \DashPages ... 7, 2676  \docstrip .....
\cmsy font ..... 7  \dateLANGUAGE .... 43  \dospecials .....
collection entry type 7  \Dbar ..... 1832  \doSK@append .....
\compare@stems . . .    \dbar ..... 1832  \doSK@def .....
      .... 2275, 2310  \DeclareBooleanOption    913
\copy@bibdef . . .    128–133, 143–148  \doSK@def .....
      .. 31, 60, 668,    \DeclareExclusiveOptions    912
      758, 1261, 1562  \DeclaraNameAccent    \dudot .....
\copy@bibdef@a . . .    126, 127, 140–142  \DuplicateBibKeyWarning
      .... 672, 675, 721  \dateLANGUAGE .... 43
\count ..... 14, 1353  \Dbar ..... 1832  . 1122, 1173, 1178
\count@ ..... 107  \dbar ..... 1832  \DuplicateBibLabelWarning
\count@chars 2144, 2153  \DeclareOption ... 134    .... 1178, 2288
\cprime ..... 1835  \E ..... 1827

```

3228, 3237,	\extract@initial .	\get@namepart@b ..
3239, 3280, 2096,	77, 81, 1933, 1935
3282, 3299,	2101, 2118, 2133	\get@namepart@c ..
3301, 3316, 3317	\extract@initial@a 82, 1937, 1942
\empty@cite .. 1486, 1490	81, 2103, 2105	\get@namepart@d ..
\EmptyNameWarning .. 1918, 1968 2110, 2117	... 76, 1939, 1945
\EmptyPrimaryWarning .. 2464, 2469	\extract@initial@c ..	\get@namepart@e ..
\endbibchapter .. 1235 2112, 2120 1947, 1949
\endbibdiv .. 1242	\extract@initial@d ..	\get@namepart@f ..
\endbiblist .. 1241 2127, 2129	78, 82, 1957, 1960
\endbibsection .. 1233	\extract@initials ..	\get@nth@property 296
\endinput .. 52, 122	1922, 1969, 2851	\get@numberof .. 73,
\endlist .. 576	\extract@surnames ..	2185, 2231, 2338
environments:	2223, 2230, 2249	\get@property 879
bibchapter ... 1210	F	H
bibdiv 1232	\fld@elt 187,	\H 1797
biblist . 1, 27, 500	192–196, 2503,	har.bst 9
biblist* 506	2661, 2665, 2672	\hbox 2482
bibsection ... 1219	\font 23	\hfil 584
tabbing 72	\fontseries 1504	\hfill 615
thebibliography	\fontshape 1504	hij.bib 9
1237	\foo 72	\href 2914, 2917
\eprint 330, 392, 435,	\format@cite	\hrulefill 2482
453, 2790, 3094,	1758, 1760, 1768	\Hy@backout 1751
3140, 3161, 3179	\frenchspacing	\Hy@raisedlink
\eprintpages .. 327,	95, 108, 114, 555	.. 616, 1771, 2974
347, 2683, 3091	\fsa@n 81	\hyper@link 1760
\erase@field	\fullcite .. 1537, 3019	\hyper@anchored ..
22, 291, 2496,	\fulllocite .. 1538, 3025	.. 616, 1770, 2974
2603, 3341, 3346	\futurelet 76	\hyper@anchorstart ..
\errmessage 264	G	.. 616, 1769, 2974
\etalchar 56,	\G@refundefinedtrue ..	hyperref package 66, 68
70, 72, 1810, 1493	\hyph@to@space
2241, 2246, 2256	\g@undef .. 59, 725, 1278 2212, 2225
\etaltext 70,	\generate@alphabel ..	\hyphenpenalty 30
1108, 1125,	1083, 1091, 2175	I
1811, 2183,	\generate@label 785,	\i .. 71, 73, 1821, 1876
2245, 2352,	1066, 1078,	\if@tempswa ... 669,
2608, 2609,	1083, 1091, 2939	679, 1152, 2292
2610, 2949, 3056	\get@current@properties ..	\ifBR@verbose 1745, 1748
\ExecuteOptions .. 149	277, 294, 2452	\IfEmptyBibField ..
export-bibtex pack-	\get@namepart 76, 77, 8, 20,
age 32	81, 1909, 1912,	186, 2416, 2570,
\extr@cite .. 1160,	1915, 1926, 2224	2586, 2587,
1496, 1501,	\get@namepart@a ..	2674, 2684,
1523, 1530, 77, 81,	2705, 2708,
1749, 1760, 1762	1929, 1931, 1943	2835, 3074, 3075

- \IfFileExists
 . 11, 155, 165,
 1293, 1296, 1299
- \ifin@ 731,
 935, 1130, 1443,
 2141, 2511, 2522
- ifoption package . . . 16
- \ifsame@stems 2276, 2309
- \ifx 13
- \in@ 730,
 934, 1129, 1442,
 2140, 2510, 2521
- \ini@hyphen
 . 1971, 1988,
 1994, 2025,
 2027, 2137, 2138
- initials option 76, 109
- \InnerCite . . . 1420,
 1425, 1450,
 1463, 1555, 3004
- inputenc package . . . 72
- \interlinepenalty 552
- inverted attribute . . 76
- isbn field 8
- \issuetext . 7, 326,
 346, 2675, 3090
- \itemindent 624
- J**
- \j 71, 73, 1822, 1877
- journal field 38
- K**
- \k 1798
- \keep@last@digit 2777, 2781
- \kern 788,
 2483, 2546, 2587
- klm.bib 9
- L**
- \L 1828
- \l 1828
- label field 87, 112
- \labelsep 540, 600, 626
- \labelwidth
 598, 599, 620–622
- \language 1046, 1062
- \lasp 1833
- \lastkern 270, 2388,
 2396, 2408, 2546
- \lastpenalty 2389, 2391
- \lc@do 1858, 1863
- \lc@edef 1854, 2314, 2315
- \lccode 29
- \lcsymbol 71
- \leftmargin 599, 600,
 621, 623, 624, 626
- \let 23, 58, 59
- \lfhook 1806
- \linebreak 5
- \list 543
- \lite option 18
- \lnscan@a . . . 2948, 2964
- logical-quotes op-
 tion 7, 110
- \lowercase
 . 29, 711, 857,
 894, 1042, 1859
- ltoutenc.dtx 72
- M**
- \m@ne 267, 1056
- \m@th 1456
- \macrotext 52, 55
- \makeatletter 109
- \makelabel 548
- \MakeUppercase 1205
- \mathchar 30
- \mathcode 28, 33
- mathscinet package
 17, 70, 71
- \mathsurround 56
- \mdash 8, 2641
- \mddefault 1504
- \mdseries 1456
- \meaning 20, 52
- \MessageBreak
 107, 1391,
 1400, 2928, 2934
- \MessageBreakNS 107,
 1176, 1180–1182
- \modify@xref@fields 687, 705
- \ModifyBibLabel
 2297, 2324
- \month@ 106
- \moo 21
- \MR 2651
- \MR@url 2907, 2914, 2917
- \MRhref 2655, 2659, 2911
- msc-links option . . . 111
- \MultipleBibSelectWarning 1282, 1284
- \MultipleCiteKeyWarning 1380, 1388
- N**
- name entry type 4
- \name 87, 112,
 187, 189–191,
 844, 860, 864,
 870, 887, 2182,
 2185, 2229,
 2239, 2240,
 2244, 2247,
 2282, 2433,
 2948, 3052, 3063
- \name@split
 76, 1908, 2447
- \name@split@finish
 1915, 1917
- \name@split@given
 76, 1909, 1911
- \name@split@jr
 1912, 1914
- \NameCheck 1920
- \ndash 8, 104,
 2641, 2677, 2682
- \NeedsTeXFormat 2, 3202
- \newcount 2270, 2327
- \newcounter 497, 586
- \newdimen 578
- \newif 2309
- \newlabel 590
- \newread 1291
- \NG 1829
- \ng 1829
- \NoBibDBFile 1303, 1310
- \nobreak 80
- \nobreakspace 1972, 2736
- nobysame option 129
- \nocite 60, 1541
- non-compressed-cites
 option 110
- non-sorted-cites op-
 tion 17, 110
- \NonNumericCiteWarning 1577, 1581

- \nopunct ... 7, 123,
1440, 1660, 2570 \parenthesize ... 5,
6, 102, 331,
371, 393, 437,
455, 2615,
3095, 3119,
3141, 3163,
3181, 3214, 3230
 \parse@MR ... 2906, 2913
 partial field ... 102
 pcatcode package ... 18
 place field ... 4
 \Plural ... 8, 93,
 96, 2412, 2491,
 2494, 2499,
 2606, 3340, 3345
 \polhk ... 1808
 \pop@bracket 2616, 2619
 \pop@bracket@ ...
 ... 2627, 2630
 \PopCatcodes 2923, 3199
 \pp@scan ... 2677, 2680
 \pp@scan@ ... 2677, 2682
 \prev@cite ... 63,
 64, 1605, 1640,
 1648, 1675,
 1693, 1696,
 1697, 1704, 1705
 \prev@cite@cb ...
 ... 64, 1641, 1692
 \prev@citekey ...
 ... 816, 826, 2297
 \prev@names ...
 ... 1460, 3041, 3043
 \previous@primary ...
 ... 98,
 575, 957, 962,
 2473, 2490, 2597
 \previous@stem 2168,
 2178, 2275, 2942
 \previous@year ... 90,
 2170, 2277, 2944
 \prime ... 7
 \print@backrefs ...
 ... 1753, 2810
 \print@citenames ...
 ... 3021,
 3027, 3047, 3061
 \print@contribution ...
 ... 2504–2507, 2509
 \print@date ... 2554,
 2716, 2717,
 2733, 2747, 3073
 \print@edition ...
 ... 2749, 2752
 \print@full@date ...
 ... 2722, 2726, 2733
 \print@month@day ...
 ... 2729, 2734
 \print@one@dash ...
 ... 1659, 1691
 \print@partial ...
 ... 2612, 2666–2669
 \print@primary ...
 969, 972, 976, 2466
 \PrintAuthors ... 6,
 7, 317, 380,
 446, 464, 490,
 976, 2472, 3081,
 3128, 3172,
 3190, 3206,
 3258, 3315, 3329
 \PrintBackRefs ...
 ... 823, 1756, 2810
 \PrintBook ... 386,
 2558, 3135, 3264
 \PrintCiteNames ...
 ... 2965,
 2967, 3035, 3038
 \PrintCNY ... 2966, 3034
 \PrintConference ...
 ... 385,
 2532, 3134, 3263
 \PrintConferenceDetails ... 403, 2535, 3276
 \PrintConferenceDetails@ ... 2539, 2542, 2545
 \PrintContributions ...
 ... 321, 342,
 363, 384, 413,
 429, 2501, 3086,
 3112, 3133,
 3156, 3210,
 3227, 3244,
 3262, 3287, 3302
 \PrintDate ... 8,
 467, 2706,
 2711, 2716,
 3072, 3082,

3105, 3129,
3151, 3173, 3191
\PrintDateB . . . 369,
388, 419, 434,
452, 2717, 3216,
3232, 3249,
3267, 3292,
3307, 3321, 3332
\PrintDateFormat 469,
2718, 3195, 3334
\PrintDatePosted .
. 2709, 2747
\PrintDatePV
. 325, 345, 2704
\PrintDOI 329, 391,
2701, 3093, 3139
\PrintEdition
7, 8, 360, 410,
428, 2748, 3109,
3155, 3248, 3291
\PrintEditorsA
7, 8, 97,
98, 972, 2489, 3338
\PrintEditorsB
7, 361,
411, 2498, 3110
\PrintEditorsC 7, 2486
\PrintSeries@a . 2337
\PrintISBNs 2671
\PrintNameList 352,
2485, 3242,
3243, 3285, 3286
\PrintNames 97,
2429, 2477,
2485, 2487,
2494, 2499,
2594, 2601,
2606, 3340, 3345
\PrintNames@a 2430, 2432
\PrintPartials 322,
2663, 3087, 3211
\PrintPrimary . . 7,
356, 424, 2462,
2584, 3104,
3150, 3236, 3298
\printref 1757
\PrintReprint . 333,
373, 395, 439,
457, 2561, 3097,
3121, 3143,
3165, 3183,
3219, 3253,
3269, 3309, 3323
\PrintReviews . . 8,
336, 376, 398,
442, 460, 2660,
3100, 3124,
3146, 3168, 3186
\PrintSeries 92, 93,
97, 2328, 2433,
2502, 2661,
2664, 2672,
3004, 3052, 3063
\PrintSeries@a 93, 2335, 2337
\PrintThesisType .
. 449,
2686, 3176, 3318
\PrintTranslation 332,
372, 394, 438,
456, 2575, 3096,
3120, 3142,
3164, 3182,
3218, 3252,
3268, 3308, 3322
\PrintTranslatorsA 7,
98, 969, 2596, 3343
\PrintTranslatorsB 7, 2605
\PrintTranslatorsC 7, 362,
412, 2593, 3111
\PrintYear 8, 106, 2746
proceedings entry
type 7
\process@bare@dot 2059, 2069
\process@citelist 1451,
1589, 2800,
2805, 2863, 2976
\process@citelist@sorted 1573, 1589
. 1578, 1586, 2800,
2805, 2863, 2976
\process@citelist@unsorted@purge@edef@a
. 1578, 1586, 2800,
1895, 1896, 1900
. 74, 1887, 1889
\push@bracket 2616, 2619
\PushCatcodes 37

R	S	
\r	560, 660, 705,	\set@firstname . . .
\rasp	2514, 2523, 2925	. 2430, 2440, 3031
\read		\set@name . . . 2441,
\ReadBibData 1275, 1292	\safe@set . . . 82 ,	2444, 2446 , 3032
\ReadBibData@a	1609, 1616,	\set@namea
. 1304, 1308, 1313	1632, 1666,	. 98, 2448, 2450
\ReadBibLoop	1673, 1689, 2259	\set@namea 2450
. 1317, 1321 , 1335	\same@stemsfalse 2319	\set@othername 2430,
\ReadBibLoop@a	\same@stemstrue . 2317	2435–2437, 2443
. 1326, 1330	\sameauthors	\setbib@ 31, 32, 34–36
\ReadBibLoop@b 7, 8, 2474,	\setbib@C 780, 789,
. 1337, 1341	2480 , 2491, 2598	794, 797, 800,
\ReadBibLoop@e	\save@labelwidth	803, 1002, 2590
\refname 48, 1199 , 1219	\save@primary 825, 958	\setbib@article
\RequirePackage 5, 12, 36, 125, 156, 166, 179, 182, 183, 2902, 3204	\section* 48	. 789, 1002
\reset@nth@property 882	\selbibdef@a . 750, 752	\setbib@book 2572
\resetbiblist 596, 619 , 1239	\selbibdef@b . 754, 757	\setbib@conference 2533
\ResetCapSFCodes 556, 603	\select@auxlanguage	\setbib@contribution 2514
\resolve@inner 2520, 2533, 2559, 2562, 2576, 2613	\selective@bibdef 31, 60, 749 , 1264, 1562	\setbib@incollection 483, 794, 797, 800
\restore@labelwidth 544, 594	\selectlanguage 42, 43, 288, 1048	\setbib@innerbook 2559
\RestrictedSetKeys 12, 22, 298, 560, 659, 681, 705, 2513, 2523, 2925	\SentenceSpace 336, 376, 398, 442, 460, 1754, 2789 , 3100, 3124, 3146, 3168, 3186	\setbib@inproceedings 486
review field 6, 8	\series@add . 2346, 2350	\setbib@misc 657
rkeyval package 6, 11, 22, 81	\series@add@ 93	\setbib@nameBE 2419, 2456
\rvk@DSAK 22	\series@add@a 2330, 2362	\setbib@nameinverted 2424, 3032
\rvk@setter 930, 950	\series@add@b 2331, 2365	\setbib@nameLE 2414, 2441, 2444
\rvkIfAdditive 276	\series@add@c 2332, 2367, 2374	\setbib@partial 2613
\rvkIfEmpty 18, 186, 561, 564, 2926, 2932	\series@add@d 2333, 2371	\setbib@TYPE 20
\romannumeral 107	\series@add@e 2334, 2356	\setcounter 501
\rsk@resume 747	\series@index 22, 267, 296, 843, 855, 882, 2327 , 2345, 2351, 2353, 2358, 2360, 2370, 2373, 2512	\settowidth 580, 620
\rsk@set 33, 681	\series@total 2339, 2340, 2364, 2370, 2373	\sfcode 95, 115–120, 606, 2398, 2556
\rsk@set@a 22	\set 688–698	\shade@cite 1757, 1758, 1765
\rsk@set@b 22		shaderef package 68
\rsk@toks 11, 12, 32, 36, 299,		short-journals option 17, 110
		short-months option 110
		short-publishers option 17, 110
		shortalphabetic option 108
		showkeys package 54, 68

\SingularPlural	3132, 3152, 3154, 3174, 3175	\utilde	1803
8, 93, 96,			
2341, 2343, 2412	\textquotedblleft 2635	V	
\sixt@n	\textquotedblright 2638	\v	1802
\SK@	\textsc	\value	533
\SK@label	\textsubscript	\vdef 53, 641, 1410, 1475	
\SK@ref	\textsuperscript	\voltext	7,
\soft	\texttt	365, 415, 2674,	
sorted option	\tf@brf	3114, 3241, 3284	
\space	\TH	\vphantom	2914
\spacefactor	\th		
111, 123, 2398, 2400,	\the	W	
2556, 2652, 2789	\thebib	\widowpenalty	554
\SS	518, 617, 620, 1071,	\wrap@accent	
\ss	1073, 1099, 2173	74, 1843, 1851	
\star@	thebibliography environment	wrapper macros, definition	13
739, 1405, 1463, 2978,	\thebibliography		
2991, 2995, 3014, 3022, 3028	\thesis@type 2687, 2690	X	
\star@bibdef	\thinspace	xref field	39
31, 633, 664, 721, 1316	\thr@	\xref@add@toks 912, 927	
\stepcounter	\toks@	\xref@append	913, 948
\string	\tprime	\xref@check@aa	
\strip@MRprefix	\TrailingHyphenWarning	831–833, 837	
2643, 2654	2008, 2039	\xref@check@aa 844, 854	
\strip@prefix	transition field	\xref@check@ab 866, 873	
\SubEtal 2354, 2356, 2610	\tsub	\xref@check@b	
\surround@names	\tsup	834, 835, 890	
2214, 2216	\ttfamily	\xref@check@c	
\SwapBreak	\tw@	39, 830, 901, 906	
94, 95, 272, 2331–	\typeout	\xref@ID	916–918, 920
2334, 2383,		\XRefWarning	
2499, 2553, 2606		918, 955, 2526	
\symbol		\XrefWarning	955
		xyz.aux	9
T		xyz.bbl	9
\t		xyz.tex	9
tabbing environment			
\textbf 5, 324, 344, 3089		Y	
textcmds package		y2k option	86, 111, 128
8, 17, 103		\ycite	59, 1533,
\textemdash		1535, 1539,	
\textendash		1540, 2977, 3017	
\textfont		\ycites	1534, 2980
\textit 318, 320, 341,		\year@short	
357, 359, 381,		2257, 2264, 2892	
383, 425, 427,		Z	
447, 448, 3083,		\Z	608
3085, 3106,		\zap@space	
3108, 3130,		643, 1412, 1477	