

The `hypcap` package

Heiko Oberdiek*

2024-07-26 v1.13

Abstract

This package tries a solution of the problem with hyperref, that links to floats points below the caption and not at the beginning of the float. Therefore this package divides the task into two part, the link setting with \capstart or automatically at the beginning of a float and the rest in the \caption command.

Contents

1 Usage	2
1.1 Package options	2
1.2 User commands	2
1.3 Limitations	3
2 Implementation	3
3 Installation	5
3.1 Download	5
3.2 Package installation	5
3.3 Refresh file name databases	6
3.4 Some details for the interested	6
4 History	6
[1999/02/13 v1.0]	6
[2000/08/14 v1.1]	6
[2000/09/07 v1.2]	6
[2001/08/27 v1.3]	7
[2001/09/06 v1.4]	7
[2006/02/20 v1.5]	7
[2007/02/19 v1.6]	7
[2007/04/09 v1.7]	7
[2008/04/14 v1.8]	7
[2008/08/11 v1.9]	7
[2008/09/08 v1.10]	7
[2011/02/16 v1.11]	7
[2016/05/16 v1.12]	7
[2024-07-26 v1.13]	7
5 Index	7

*Please report any issues at <https://github.com/ho-tex/hypcap/issues>

1 Usage

The package `hypcap` requires that `hyperref` is loaded first:

```
\usepackage[...]{hyperref}  
\usepackage[...]{hypcap}
```

1.1 Package options

The names of the four float environments `figure`, `figure*`, `table`, or `table*` can be used as option. Then the package redefines the environment in order to insert `\capstart` (see below) in the beginning of the environment automatically.

Option `all` enables the redefinitions of all four float environments. For other environments see the user command `\hypcaprefdef`.

1.2 User commands

`\capstart \capstart`: First this command increments the counter (`\@capttype`). Then it makes an anchor for package `hyperref`. At last `\caption` is redefined to remove the anchor setting part from `hyperref`'s `\caption`.

The package expects the following structure of a float environment:

```
\begin{float}...  
\capstart  
...  
\caption{...}  
...  
\end{float}
```

There can be several `\caption` commands. For these you need `\capstart` again:

```
\capstart ... \caption... \capstart ... \caption...
```

And the `\caption` command itself can be put in a group.

With the options, described above, the extra writing of `\capstart` can be avoided. Consequently, there must be a `\caption` in every environment of this type, specified by the option. If you want to use more than one `\caption` in this environment, you have to state `\capstart` again.

`\hypcapspace \hypcapspace`: Because it looks poor, if the link points exactly at top of the figure, there is additional space: `\hypcapspace`, the default is `0.5\baselineskip`, examples:

```
\renewcommand{\hypcapspace}{0pt} removes the space  
\renewcommand{\hypcapspace}{1pt} sets a fix value
```

`\hypcaprefdef \hypcaprefdef`: If there are other float environments, that should automatically execute `\capstart`, then a redefinition with `\hypcaprefdef` can be tried:

```
\hypcaprefdef{myfloat}
```

Only environments with one optional parameter are supported.

`\capstartfalse \capstartfalse, \capstarttrue`: Since 2008/09/08 v1.10.
`\capstarttrue` They disable and enable `\capstart`. They can be used to cancel the effect of a redefined float environment. Example:

```

\documentclass{article}
\usepackage{hyperref}
\usepackage[figure]{hypcap}[2008/09/08]

\begin{document}
\section{Hello World}
\begin{figure}
\caption{Figure with caption A}
\end{figure}
\capstartfalse
\begin{figure}
Figure without caption
\end{figure}
\capstarttrue
\begin{figure}
\caption{Figure with caption B}
\end{figure}
\end{document}

```

1.3 Limitations

- Packages that redefine \caption or \@caption.

2 Implementation

1 <*package>

Package identification.

2 \NeedsTeXFormat{LaTeX2e}
 3 \ProvidesPackage{hypcap}%
 4 [2024-07-26 v1.13 Adjusting the anchors of captions (HO)]

For unique command names this package uses hc@ as prefix for internal command names.

First we check, if package hyperref is loaded:

5 \@ifundefined{hyper@@anchor}{%
 6 \PackageError{hypcap}{You have to load 'hyperref' first}\@ehc
 7 \endinput
 8 }{%
 9 \RequirePackage{letltxmacro}[2008/06/24]

\hc@org@caption Save the original meaning of \caption:

10 \newcommand*\hc@org@caption{}%
 11 \let\hc@org@caption\caption

\if@capstart The switch \if@capstart helps to detect \capstart commands with missing \caption macros. Because \caption can occur inside a group, assignments to the switch have to be made global.

12 \newif\if@capstart

\hypcapspace The anchor is raised by \hypcapspace.

13 \newcommand*\hypcapspace{.5\baselineskip}

\ifcapstart

14 \newif\ifcapstart%
 15 \capstarttrue

\capstart The macro \capstart contains the first part of the \caption command: Incrementing the counter and setting the anchor.

16 \newcommand*\capstart{%
 17 \ifcapstart
 18 \H@refstepcounter\@capttype % first part of caption

```

19      \hyper@makecurrent\@capttype
20      \global\let\hc@currentHref\@currentHref
21      \vspace*{-\hypcapspace}%
22      \begingroup
23          \let\leavevmode\relax
24          \hyper@anchor\@currentHref\relax
25      \endgroup
26      \vspace*{\hypcapspace}%
27      \hc@hyperref{\let\caption\hc@caption}%
28      \global\@capstarttrue
29      \global\advance\csname c@\@capttype\endcsname\@ne
30  \fi
31 }

32 \ifpackagelater{hyperref}{2007/04/09}%
33     \let\hc@hyperref@gobble
34 \f%
35     \let\hc@hyperref@firstofone
36 }

```

`\hc@caption` The new `\caption` command without the first part is defined in the macro `\hc@caption`.

```

37 \def\hc@caption{%
38     \global\advance\csname c@\@capttype\endcsname\@ne
39     \@dblarg{\hc@@caption\@capttype}%
40 }

```

`\hc@@caption` This is a copy of package hyperref's `\@caption` macro without making the anchor, because this is already done in `\capstart`.

```

41 \long\def\hc@@caption#1[#2]#3{%
42     \let\caption\hc@org@caption
43     \global\@capstartfalse
44     \ifHy@hypertexnames
45         \hyper@makecurrent\@capttype
46     \else
47         \global\let\@currentHref\hc@currentHref
48     \fi
49     \par\addcontentsline{%
50         \csname ext@\#1\endcsname}{\#1}%
51     \protect\numberline{%
52         \csname the\#1\endcsname
53     }{\ignorespaces #2}%
54 }%
55 \begingroup
56     \parboxrestore
57     \normalsize
58     \makecaption{\csname fnum@\#1\endcsname}{%
59         \ignorespaces#3%
60     }%
61     \par
62 \endgroup
63 }

```

`\hypcapredef` The macro `\hypcapredef` prepares the call of `\hc@redef` that will redefine the environment that is given in the argument.

```

64 \def\hypcapredef#1{%
65     \expandafter\hc@redef\csname hc@org\#1\expandafter\endcsname
66             \csname hc@org\#1\expandafter\endcsname
67             \expandafter{\#1}%
68 }

```

`\hc@redef` The old meaning of the environment is saved. Then `\capstart` is appended in the begin part. The end part contains a check that produces an error message in case of `\capstart` without `\capstart` (`\capstart` has incremented the counter).

```

69 \def\hc@redef#1#2#3{%
70   \newcommand#1{}%
71   \expandafter\LetLtxMacro\expandafter#1\csname#3\endcsname
72   \expandafter\LetLtxMacro\expandafter#2\csname end#3\endcsname
73   \renewenvironment*{#3}[1][]{}%
74     \ifx\\##1\\%
75       #1\relax
76     \else
77       #1[##1]% hash-ok (compatibility for float)
78     \fi
79     \capstart
80   }{%
81   \if@capstart
82     \PackageWarning{hypcap}{You have forgotten to use \string\caption}%
83     \global\@capstartfalse
84   \else
85   \fi
86   #2%
87 }%
88 }
```

At last the options are defined and processed.

```

89 \DeclareOption{figure}{\hypcapredef{\CurrentOption}}
90 \DeclareOption{figure*}{\hypcapredef{\CurrentOption}}
91 \DeclareOption{table}{\hypcapredef{\CurrentOption}}
92 \DeclareOption{table*}{\hypcapredef{\CurrentOption}}
93 \DeclareOption{all}{%
94   \hypcapredef{figure}%
95   \hypcapredef{figure*}%
96   \hypcapredef{table}%
97   \hypcapredef{table*}%
98 }
99 \ProcessOptions\relax
100 </package>
```

3 Installation

3.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/hypcap/hypcap.dtx](#) The source file.

[CTAN:macros/latex/contrib/hypcap/hypcap.pdf](#) Documentation.

3.2 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain T_EX:

```
tex hypcap.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

¹[CTAN:pkg/hypcap](#)

```
hypcap.sty → tex/latex/hypcap/hypcap.sty  
hypcap.pdf → doc/latex/hypcap/hypcap.pdf  
hypcap.dtx → source/latex/hypcap/hypcap.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

3.3 Refresh file name databases

If your `TeX` distribution (`TeX Live`, `MiKTeX`, ...) relies on file name databases, you must refresh these. For example, `TeX Live` users run `texhash` or `mktexlsr`.

3.4 Some details for the interested

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain TeX: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
\latex \let\install=y\input{hypcap.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex hypcap.dtx  
makeindex -s gind.ist hypcap.idx  
pdflatex hypcap.dtx  
makeindex -s gind.ist hypcap.idx  
pdflatex hypcap.dtx
```

4 History

[1999/02/13 v1.0]

- A beginning version, published in newsgroup `comp.text.tex`:
“Re: `hyperref` and `figures`”²

[2000/08/14 v1.1]

- Global assignments of `\if@capstart` in order to allow `\caption` in groups.
- Option `all` added.

[2000/09/07 v1.2]

- Package in dtx format.

²Url: <https://groups.google.com/group/comp.text.tex/msg/5c9b47b001a9379c>

[2001/08/27 v1.3]

- Bug fix with hyperref's pdfmark driver
(\leavevmode in \hyper@anchor/\pdf@rect).

[2001/09/06 v1.4]

- Small fixes in the dtx file.

[2006/02/20 v1.5]

- Code is not changed.
- New DTX framework.

[2007/02/19 v1.6]

- Fix for hypertexnames=false.

[2007/04/09 v1.7]

- Stuff in \caption moved to hyperref. This avoids redefinitions of \caption and \@caption (idea of Axel Sommerfeldt).
- Fix for subfigure (Marco Kuhlmann, Amilcar do Carmo Lucas).

[2008/04/14 v1.8]

- \hc@redef fixed to get package float work (Axel Sommerfeldt).

[2008/08/11 v1.9]

- Code is not changed.
- URLs updated.

[2008/09/08 v1.10]

- \capstartfalse and \capstarttrue added.

[2011/02/16 v1.11]

- \hc@redef fixed by using package letltxmacro.

[2016/05/16 v1.12]

- Documentation updates.

[2024-07-26 v1.13]

- Change error into warning, issue #1

5 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	\@capstarttrue	28
\capstartfalse	43, 83	\captype 18, 19, 29, 38, 39, 45

\@currentHref	20, 24, 47	\hc@redef	65, 69
\dblarg	39	\hypcapredef	2,
\ehc	6	64, 89, 90, 91, 92, 94, 95, 96, 97	
\firstofone	35	\hypcapspace	2, 13, 21, 26
\gobble	33	\hyper@@anchor	24
\ifpackagelater	32	\hyper@makecurrent	19, 45
\ifundefined	5		
\makecaption	58	I	
\ne	38	\if@capstart	12, 81
\parboxrestore	56	\ifcapstart	14, 17
\`	74	\ifHy@hypertexnames	44
		\ifx	74
		\ignorespaces	53, 59
		L	
		\leavevmode	23
		\LetLtxMacro	71, 72
		M	
		\m@ne	29
		N	
		\NeedsTeXFormat	2
		\newcommand	10, 13, 16, 70
		\newif	12, 14
		\normalsize	57
		\numberline	51
		P	
		\PackageError	6
		\PackageWarning	82
		\par	49, 61
		\ProcessOptions	99
		\protect	51
		\ProvidesPackage	3
		R	
		\ renewenvironment	73
		\RequirePackage	9
		V	
		\vspace	21, 26